







A Dimensions: [mm]




Scale - 1:2

B Recommended land pattern: [mm]



Scale - 1:2

C Schematic:



D Electrical Properties:


| Properties              | Test conditions         |           | Value          | Unit   | Tol. |
|-------------------------|-------------------------|-----------|----------------|--------|------|
| Inductance              | 100 kHz/ 100 mV         | L         | 400            | μH     | ±10% |
| Turns ratio             |                         | n         | 27 : 6 : 6 : 2 |        | ±3%  |
| Saturation current      | $I_{\Delta L/L} < 20\%$ | $I_{sat}$ | 4.3            | A      | typ. |
| DC Resistance 1         | @ 20°C                  | $R_{DC1}$ | 75             | mΩ     | max. |
| DC Resistance 2         | @ 20°C                  | $R_{DC2}$ | 12.2           | mΩ     | max. |
| DC Resistance 3         | @ 20°C                  | $R_{DC3}$ | 12.2           | mΩ     | max. |
| DC Resistance 4         | @ 20°C                  | $R_{DC4}$ | 150            | mΩ     | max. |
| Leakage inductance      | 100 kHz/ 100 mV         | $L_S$     | 65             | μH     | ±10% |
| Insulation test voltage | W1,4 => W2,3            | $U_T$     | 4000           | V (AC) |      |

E General information:

It is recommended that the temperature of the part does not exceed +125°C under worst case conditions.

- Storage Temperature: -20°C to 60°C
- Operating Temperature: -40°C to 125°C
- Test conditions of Electrical Properties: 20°C, 33% RH if not specified differently

Designed to comply with the following requirements as defined by IEC61558-2-16; Reinforced insulation for a working voltage of 250 V<sub>RMS</sub>


|     |            |     |         |                                                                                                                                                                                                                                                                          |                                       |    |                                                                                                                                                                  |      |
|-----|------------|-----|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------|----|------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
|     |            |     |         | <div>Projection</div>                                                                                                                                                               | DESCRIPTION                           |    |                                                                                                                                                                  |      |
|     |            |     |         |                                                                                                                                                                                                                                                                          | <div>WE-LLCR Resonant Converter</div> |    |                                                                                                                                                                  |      |
|     |            |     |         |                                                                                                                                                                                                                                                                          |                                       |    |                                                                                                                                                                  |      |
|     |            |     |         | <div>Würth Elektronik eiSos GmbH &amp; Co. KG</div> <div>EMC &amp; Inductive Solutions</div> <div>Max-Eyth-Str. 1</div> <div>74638 Waldenburg</div> <div>Germany</div> <div>Tel. +49 (0) 79 42 945 - 0</div> <div>www.we-online.com</div> <div>eiSos@we-online.com</div> | Order.- No.                           |    |  <div>COMPLIANT</div> <div>RoHS&amp;REACH</div> <div>WÜRTH ELEKTRONIK</div> | SIZE |
| 1.1 | 2014-04-01 | SSt | SSt     |                                                                                                                                                                                                                                                                          | <div>760895751</div>                  | A4 |                                                                                                                                                                  |      |
| 1.0 | 2013-07-22 | SSt | WW      |                                                                                                                                                                                                                                                                          |                                       |    |                                                                                                                                                                  |      |
| REV | DATE       | BY  | CHECKED |                                                                                                                                                                                                                                                                          | Size: ETD44                           |    |                                                                                                                                                                  |      |

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eiSos GmbH & Co KG products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarine, transportation (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc.. Würth Elektronik eiSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.



D2 Application Properties:

| Properties          |              | Value   | Unit   |
|---------------------|--------------|---------|--------|
| Input voltage       | $U_i$        | 360-400 | V (DC) |
| Output voltage      | $U_O$        | 48      | V      |
| Output current      | $I_O$        | 5.2     | A      |
| Auxiliary voltage   | $U_{aux}$    | 16.0    | V      |
| Switching frequency | $f_{switch}$ | 70-120  | kHz    |

|     |            |     |         |  |                                                                                                                                                                                                                                                                          |                                                                                                                                                                                                                       |                                                              |      |
|-----|------------|-----|---------|--|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------|------|
|     |            |     |         |  | <div>Projection</div>                                                                                                                                                               |                                                                                                                                                                                                                       | <div>DESCRIPTION</div> <div>WE-LLCR Resonant Converter</div> |      |
|     |            |     |         |  |                                                                                                                                                                                                                                                                          |                                                                                                                                                                                                                       |                                                              |      |
|     |            |     |         |  | <div>Würth Elektronik eiSos GmbH &amp; Co. KG</div> <div>EMC &amp; Inductive Solutions</div> <div>Max-Eyth-Str. 1</div> <div>74638 Waldenburg</div> <div>Germany</div> <div>Tel. +49 (0) 79 42 945 - 0</div> <div>www.we-online.com</div> <div>eiSos@we-online.com</div> | <div>Order.- No.</div> <div>760895751</div> <div> <div>COMPLIANT</div><div>RoHS&amp;REACH</div><div>WÜRTH ELEKTRONIK</div></div> |                                                              | SIZE |
| 1.1 | 2014-04-01 | SSt | SSt     |  |                                                                                                                                                                                                                                                                          |                                                                                                                                                                                                                       |                                                              |      |
| 1.0 | 2013-07-22 | SSt | WW      |  |                                                                                                                                                                                                                                                                          |                                                                                                                                                                                                                       | A4                                                           |      |
| REV | DATE       | BY  | CHECKED |  |                                                                                                                                                                                                                                                                          |                                                                                                                                                                                                                       | Size: ETD44                                                  |      |

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eiSos GmbH & Co KG products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarine, transportation (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc.. Würth Elektronik eiSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

H Soldering Specifications:




H4: Classification Wave Soldering Profile:



H5: Classification Wave Profile

| Profile Feature                                                                                                                                                                                                                                                                                       | Pb-Free Assembly                           | Sn-Pb Assembly                             |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------|--------------------------------------------|
| Preheat <ul style="list-style-type: none"><li>- Temperature Min (<math>T_{smin}</math>)</li><li>- Temperature Typical (<math>T_{stypical}</math>)</li><li>- Temperature Max (<math>T_{smax}</math>)</li><li>- Time (<math>t_s</math>) from (<math>T_{smin}</math> to <math>T_{smax}</math>)</li></ul> | 100°C<br>120°C<br>130°C<br>70 seconds      | 100°C<br>120°C<br>130°C<br>70 seconds      |
| $\Delta$ preheat to max Temperature                                                                                                                                                                                                                                                                   | 150°C max.                                 | 150°C max.                                 |
| Peak temperature ( $T_p$ )                                                                                                                                                                                                                                                                            | 250°C - 260°C                              | 235°C - 260°C                              |
| Time of actual peak temperature ( $t_p$ )                                                                                                                                                                                                                                                             | max. 10 seconds<br>max. 5 second each wave | max. 10 seconds<br>max. 5 second each wave |
| Ramp-down rate <ul style="list-style-type: none"><li>- Min</li><li>- Typical</li><li>- Max</li></ul>                                                                                                                                                                                                  | ~ 2 K/s<br>~ 3.5 K/s<br>~ 5 K/s            | ~ 2 K/s<br>~ 3.5 K/s<br>~ 5 K/s            |
| Time 25°C to 25°C                                                                                                                                                                                                                                                                                     | 4 minutes                                  | 4 minutes                                  |

refer to EN 61760-1:2006

|     |            |     |         |             |                                                                                                                                                                                                                                                                          |             |                                                                                                                                   |           |
|-----|------------|-----|---------|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|-----------------------------------------------------------------------------------------------------------------------------------|-----------|
|     |            |     |         |             | <div>Projection</div>                                                                                                                                                               |             | DESCRIPTION                                                                                                                       |           |
|     |            |     |         |             |                                                                                                                                                                                                                                                                          |             |                                                                                                                                   |           |
|     |            |     |         |             | <div>Würth Elektronik eiSos GmbH &amp; Co. KG</div> <div>EMC &amp; Inductive Solutions</div> <div>Max-Eyth-Str. 1</div> <div>74638 Waldenburg</div> <div>Germany</div> <div>Tel. +49 (0) 79 42 945 - 0</div> <div>www.we-online.com</div> <div>eiSos@we-online.com</div> |             | WE-LLCR Resonant Converter                                                                                                        |           |
|     |            |     |         |             |                                                                                                                                                                                                                                                                          |             |                                                                                                                                   |           |
| 1.1 | 2014-04-01 | SSt | SSt     | Order.- No. |                                                                                                                                                                                                                                                                          |             |  COMPLIANT<br>RoHS&REACH<br>WÜRTH ELEKTRONIK | SIZE      |
| 1.0 | 2013-07-22 | SSt | WW      |             |                                                                                                                                                                                                                                                                          |             |                                                                                                                                   | 760895751 |
| REV | DATE       | BY  | CHECKED |             |                                                                                                                                                                                                                                                                          | Size: ETD44 |                                                                                                                                   |           |

# I Cautions and Warnings:

The following conditions apply to all goods within the product series of **WE-LLCR** of Würth Elektronik eiSos GmbH & Co. KG:

## General:

All recommendations according to the general technical specifications of the data sheet have to be complied with.

The usage and operation of the product within ambient conditions, which probably alloy or harm the wire isolation, has to be avoided.

If the product is potted in customer applications, the potting material might shrink during and after hardening. The product is exposed to the pressure of the potting material with the effect that the core, wire and termination is possibly damaged by this pressure and so the electrical as well as the mechanical characteristics are endangered to be affected. After the potting material is cured, the core, wire and termination of the product have to be checked if any reduced electrical or mechanical functions or destructions have occurred.

The responsibility for the applicability of customer specific products and use in a particular customer design is always within the authority of the customer. All technical specifications for standard products do also apply to customer specific products.

Cleaning agents that are used to clean the customer application might damage or change the characteristics of the component, body, pins or termination.

Direct mechanical impact to the product shall be prevented as the core material could flake or in the worst case could break.

## Product specific:

Follow all instructions mentioned in the data sheet, especially:

- The soldering profile has to be complied with according to the technical reflow soldering specification, otherwise this will void the warranty.
- All products shall be used before the end of the period of 12 months based on the product date code, if not a 100% solderability can't be ensured.
- Violation of the technical product specifications such as exceeding the nominal rated current will void the warranty.



|     |            |     |         |                  |                                                                                                                                                                                                                                                                          |    |                                   |                                                                                       |      |
|-----|------------|-----|---------|------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|-----------------------------------|---------------------------------------------------------------------------------------|------|
|     |            |     |         |                  | <div>Projection</div>                                                                                                                                                               |    | DESCRIPTION                       |                                                                                       |      |
|     |            |     |         |                  |                                                                                                                                                                                                                                                                          |    | <b>WE-LLCR Resonant Converter</b> |                                                                                       |      |
|     |            |     |         |                  | <div>Würth Elektronik eiSos GmbH &amp; Co. KG</div> <div>EMC &amp; Inductive Solutions</div> <div>Max-Eyth-Str. 1</div> <div>74638 Waldenburg</div> <div>Germany</div> <div>Tel. +49 (0) 79 42 945 - 0</div> <div>www.we-online.com</div> <div>eiSos@we-online.com</div> |    | Order.- No.                       |  | SIZE |
| 1.1 | 2014-04-01 | SSt | SSt     | <b>760895751</b> |                                                                                                                                                                                                                                                                          | A4 |                                   |                                                                                       |      |
| 1.0 | 2013-07-22 | SSt | WW      |                  |                                                                                                                                                                                                                                                                          |    |                                   |                                                                                       |      |
| REV | DATE       | BY  | CHECKED |                  |                                                                                                                                                                                                                                                                          |    | Size: ETD44                       |                                                                                       |      |





**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331