

# MC74VHC1G05

## Single Inverter with Open Drain Output

The MC74VHC1G05 is an advanced high speed CMOS inverter with open drain output fabricated with silicon gate CMOS technology.

The internal circuit is composed of three stages, including an open drain output which provides the capability to set output switching level. This allows the MC74VHC1G05 to be used to interface 5 V circuits to circuits of any voltage between  $V_{CC}$  and 7 V using an external resistor and power supply.

The MC74VHC1G05 input structure provides protection when voltages up to 7 V are applied, regardless of the supply voltage.

### Features

- High Speed:  $t_{PD} = 3.8$  ns (Typ) at  $V_{CC} = 5$  V
- Low Internal Power Dissipation:  $I_{CC} = 1$   $\mu$ A (Max) at  $T_A = 25^\circ$ C
- Power Down Protection Provided on Inputs
- Pin and Function Compatible with Other Standard Logic Families
- Chip Complexity: FET = 105
- These Devices are Pb-Free and are RoHS Compliant




Figure 1. Pinout (Top View)




Figure 2. Logic Symbol





ON Semiconductor®

<http://onsemi.com>


### MARKING DIAGRAMS



SC-88A / SOT-353 / SC-70  
DF SUFFIX  
CASE 419A



TSOP-5 / SOT-23 / SC-59  
DT SUFFIX  
CASE 483



VF = Device Code  
M = Date Code\*  
▪ = Pb-Free Package

(Note: Microdot may be in either location)

\*Date Code orientation and/or position may vary depending upon manufacturing location.

### PIN ASSIGNMENT

| Pin | Assignment    |
|-----|---------------|
| 1   | NC            |
| 2   | IN A          |
| 3   | GND           |
| 4   | OUT $\bar{Y}$ |
| 5   | $V_{CC}$      |

### FUNCTION TABLE

| A Input | $\bar{Y}$ Output |
|---------|------------------|
| L       | Z                |
| H       | L                |

### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 4 of this data sheet.

# MC74VHC1G05

## MAXIMUM RATINGS

| Symbol        | Characteristics                                                                                            | Value                  | Unit |
|---------------|------------------------------------------------------------------------------------------------------------|------------------------|------|
| $V_{CC}$      | DC Supply Voltage                                                                                          | -0.5 to +7.0           | V    |
| $V_{IN}$      | DC Input Voltage                                                                                           | -0.5 to +7.0           | V    |
| $V_{OUT}$     | DC Output Voltage                                                                                          | -0.5 to 7.0            | V    |
| $I_{IK}$      | Input Diode Current                                                                                        | -20                    | mA   |
| $I_{OK}$      | Output Diode Current $V_{OUT} < GND$ ; $V_{OUT} > V_{CC}$                                                  | +20                    | mA   |
| $I_{OUT}$     | DC Output Current, per Pin                                                                                 | +25                    | mA   |
| $I_{CC}$      | DC Supply Current, $V_{CC}$ and GND                                                                        | +50                    | mA   |
| $T_{STG}$     | Storage Temperature Range                                                                                  | -65 to +150            | °C   |
| $T_L$         | Lead Temperature, 1 mm from Case for 10 Seconds                                                            | 260                    | °C   |
| $T_J$         | Junction Temperature Under Bias                                                                            | +150                   | °C   |
| $\theta_{JA}$ | Thermal Resistance SC70-5/SC-88A/SOT-353 (Note 1)<br>SOT23-5/TSOP-5/SC59-5                                 | 350<br>230             | °C/W |
| $P_D$         | Power Dissipation in Still Air at 85°C SC70-5/SC-88A/SOT-353<br>SOT23-5/TSOP-5/SC59-5                      | 150<br>200             | mW   |
| MSL           | Moisture Sensitivity                                                                                       | Level 1                |      |
| $F_R$         | Flammability Rating Oxygen Index: 28 to 34                                                                 | UL 94 V-0 @ 0.125 in   |      |
| $V_{ESD}$     | ESD Withstand Voltage Human Body Model (Note 2)<br>Machine Model (Note 3)<br>Charged Device Model (Note 4) | > 2000<br>> 200<br>N/A | V    |
| $I_{LATCHUP}$ | Latchup Performance Above $V_{CC}$ and Below GND at 125°C (Note 5)                                         | ±500                   | mA   |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. Measured with minimum pad spacing on an FR4 board, using 10 mm-by-1 inch, 2-ounce copper trace with no air flow.
2. Tested to EIA/JESD22-A114-A.
3. Tested to EIA/JESD22-A115-A.
4. Tested to JESD22-C101-A.
5. Tested to EIA/JESD78.

## RECOMMENDED OPERATING CONDITIONS

| Symbol     | Characteristics                                                                   | Min    | Max       | Unit |
|------------|-----------------------------------------------------------------------------------|--------|-----------|------|
| $V_{CC}$   | DC Supply Voltage                                                                 | 2.0    | 5.5       | V    |
| $V_{IN}$   | DC Input Voltage                                                                  | 0.0    | 5.5       | V    |
| $V_{OUT}$  | DC Output Voltage                                                                 | 0.0    | 7.0       | V    |
| $T_A$      | Operating Temperature Range                                                       | -55    | +125      | °C   |
| $t_r, t_f$ | Input Rise and Fall Time $V_{CC} = 3.3 V \pm 0.3 V$<br>$V_{CC} = 5.0 V \pm 0.5 V$ | 0<br>0 | 100<br>20 | ns/V |

## DEVICE JUNCTION TEMPERATURE VERSUS TIME TO 0.1% BOND FAILURES

| Junction Temperature °C | Time, Hours | Time, Years |
|-------------------------|-------------|-------------|
| 80                      | 1,032,200   | 117.8       |
| 90                      | 419,300     | 47.9        |
| 100                     | 178,700     | 20.4        |
| 110                     | 79,600      | 9.4         |
| 120                     | 37,000      | 4.2         |
| 130                     | 17,800      | 2.0         |
| 140                     | 8,900       | 1.0         |




Figure 3. Failure Rate vs. Time Junction Temperature

# MC74VHC1G05

## DC ELECTRICAL CHARACTERISTICS

| Symbol           | Parameter                                                                                | Test Conditions                                                                       | V <sub>CC</sub><br>(V)   | T <sub>A</sub> = 25°C      |                   |                            | T <sub>A</sub> ≤ 85°C      |                            | -55 ≤ T <sub>A</sub> ≤ 125°C |                            | Unit |
|------------------|------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|--------------------------|----------------------------|-------------------|----------------------------|----------------------------|----------------------------|------------------------------|----------------------------|------|
|                  |                                                                                          |                                                                                       |                          | Min                        | Typ               | Max                        | Min                        | Max                        | Min                          | Max                        |      |
| V <sub>IH</sub>  | Minimum High-Level Input Voltage                                                         |                                                                                       | 2.0<br>3.0<br>4.5<br>5.5 | 1.5<br>2.1<br>3.15<br>3.85 |                   |                            | 1.5<br>2.1<br>3.15<br>3.85 |                            | 1.5<br>2.1<br>3.15<br>3.85   |                            | V    |
| V <sub>IL</sub>  | Maximum Low-Level Input Voltage                                                          |                                                                                       | 2.0<br>3.0<br>4.5<br>5.5 |                            |                   | 0.5<br>0.9<br>1.35<br>1.65 |                            | 0.5<br>0.9<br>1.35<br>1.65 |                              | 0.5<br>0.9<br>1.35<br>1.65 | V    |
| V <sub>OL</sub>  | Maximum Low-Level Output Voltage<br>V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub> | V <sub>IN</sub> = V <sub>IH</sub><br>I <sub>OL</sub> = 50 μA                          | 2.0<br>3.0<br>4.5        |                            | 0.0<br>0.0<br>0.0 | 0.1<br>0.1<br>0.1          |                            | 0.1<br>0.1<br>0.1          |                              | 0.1<br>0.1<br>0.1          | V    |
|                  |                                                                                          | V <sub>IN</sub> = V <sub>IH</sub><br>I <sub>OL</sub> = 4 mA<br>I <sub>OL</sub> = 8 mA | 3.0<br>4.5               |                            |                   | 0.36<br>0.36               |                            | 0.44<br>0.44               |                              | 0.52<br>0.52               | V    |
| I <sub>LKG</sub> | Z-State Output Leakage Current                                                           | V <sub>IN</sub> = V <sub>IL</sub><br>V <sub>OUT</sub> = V <sub>CC</sub> or GND        | 5.5                      |                            |                   | ±0.25                      |                            | ±2.5                       |                              | ±5.0                       | μA   |
| I <sub>IN</sub>  | Maximum Input Leakage Current                                                            | V <sub>IN</sub> = 5.5 V or GND                                                        | 0 to 5.5                 |                            |                   | ±0.1                       |                            | ±1.0                       |                              | ±1.0                       | μA   |
| I <sub>CC</sub>  | Maximum Quiescent Supply Current                                                         | V <sub>IN</sub> = V <sub>CC</sub> or GND                                              | 5.5                      |                            |                   | 1.0                        |                            | 20                         |                              | 40                         | μA   |
| I <sub>OFF</sub> | Power Off-Output Leakage Current                                                         | V <sub>OUT</sub> = 5.5 V<br>V <sub>IN</sub> = 5.5 V                                   | 0                        |                            |                   | 0.25                       |                            | 2.5                        |                              | 5                          | μA   |

## AC ELECTRICAL CHARACTERISTICS Input t<sub>r</sub> = t<sub>f</sub> = 3.0 ns

| Symbol           | Parameter                                | Test Conditions                                                                                                        | T <sub>A</sub> = 25°C |            |             | T <sub>A</sub> ≤ 85°C |             | -55 ≤ T <sub>A</sub> ≤ 125°C |              | Unit |
|------------------|------------------------------------------|------------------------------------------------------------------------------------------------------------------------|-----------------------|------------|-------------|-----------------------|-------------|------------------------------|--------------|------|
|                  |                                          |                                                                                                                        | Min                   | Typ        | Max         | Min                   | Max         | Min                          | Max          |      |
| t <sub>PZL</sub> | Maximum Output Enable Time, Input A to Y | V <sub>CC</sub> = 3.3 ± 0.3 V C <sub>L</sub> = 15 pF<br>R <sub>L</sub> = R <sub>I</sub> = 500 Ω C <sub>L</sub> = 50 pF |                       | 5.0<br>7.5 | 7.1<br>10.6 |                       | 8.5<br>12.0 |                              | 10.0<br>14.5 | ns   |
|                  |                                          | V <sub>CC</sub> = 5.0 ± 0.5 V C <sub>L</sub> = 15 pF<br>R <sub>L</sub> = R <sub>I</sub> = 500 Ω C <sub>L</sub> = 50 pF |                       | 3.8<br>5.3 | 5.5<br>7.5  |                       | 6.5<br>8.5  |                              | 8.0<br>10.0  |      |
| t <sub>PLZ</sub> | Maximum Output Disable Time              | V <sub>CC</sub> = 3.3 ± 0.3 V C <sub>L</sub> = 50 pF<br>R <sub>L</sub> = R <sub>I</sub> = 500 Ω                        |                       | 7.5        | 10.6        |                       | 12.0        |                              | 14.5         | ns   |
|                  |                                          | V <sub>CC</sub> = 5.0 ± 0.5 V C <sub>L</sub> = 50 pF<br>R <sub>L</sub> = R <sub>I</sub> = 500 Ω                        |                       | 5.3        | 7.5         |                       | 8.5         |                              | 10.0         |      |
| C <sub>IN</sub>  | Maximum Input Capacitance                |                                                                                                                        |                       | 4          | 10          |                       | 10          |                              | 10           | pF   |

|                 |                                        |                                         |    |
|-----------------|----------------------------------------|-----------------------------------------|----|
| C <sub>PD</sub> | Power Dissipation Capacitance (Note 6) | Typical @ 25°C, V <sub>CC</sub> = 5.0 V | pF |
|                 |                                        | 18                                      |    |

6. C<sub>PD</sub> is defined as the value of the internal equivalent capacitance which is calculated from the operating current consumption without load. Average operating current can be obtained by the equation: I<sub>CC(OPR)</sub> = C<sub>PD</sub> • V<sub>CC</sub> • f<sub>in</sub> + I<sub>CC</sub>. C<sub>PD</sub> is used to determine the no-load dynamic power consumption; P<sub>D</sub> = C<sub>PD</sub> • V<sub>CC</sub><sup>2</sup> • f<sub>in</sub> + I<sub>CC</sub> • V<sub>CC</sub>.

# MC74VHC1G05




Figure 4. Output Voltage Mismatch Application





Figure 5. Switching Waveforms



$C_L = 50 \text{ pF}$  equivalent (Includes jig and probe capacitance)  
 $R_L = R_1 = 500 \Omega$  or equivalent  
 $R_T = Z_{OUT}$  of pulse generator (typically  $50 \Omega$ )

Figure 6. Test Circuit




Figure 7. Complex Boolean Functions




Figure 8. LED Driver




Figure 9. GTL Driver

## ORDERING INFORMATION


| Device           | Package                              | Shipping <sup>†</sup> |
|------------------|--------------------------------------|-----------------------|
| MC74VHC1G05DFT1G | SC70-5 / SC-88A / SOT-353 (Pb-Free)  | 3000/Tape & Reel      |
| MC74VHC1G05DFT2G | SC70-5 / SC-88A / SOT-353 (Pb-Free)  |                       |
| MC74VHC1G05DTT1G | SOT23-5 / TSSOP-5 / SC59-5 (Pb-Free) |                       |

<sup>†</sup>For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

# MC74VHC1G05

## PACKAGE DIMENSIONS

SC-88A (SC-70-5/SOT-353)  
CASE 419A-02  
ISSUE K



### NOTES:


1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. 419A-01 OBSOLETE. NEW STANDARD 419A-02.
4. DIMENSIONS A AND B DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.

| DIM | INCHES    |       | MILLIMETERS |      |
|-----|-----------|-------|-------------|------|
|     | MIN       | MAX   | MIN         | MAX  |
| A   | 0.071     | 0.087 | 1.80        | 2.20 |
| B   | 0.045     | 0.053 | 1.15        | 1.35 |
| C   | 0.031     | 0.043 | 0.80        | 1.10 |
| D   | 0.004     | 0.012 | 0.10        | 0.30 |
| G   | 0.026 BSC |       | 0.65 BSC    |      |
| H   | ---       | 0.004 | ---         | 0.10 |
| J   | 0.004     | 0.010 | 0.10        | 0.25 |
| K   | 0.004     | 0.012 | 0.10        | 0.30 |
| N   | 0.008 REF |       | 0.20 REF    |      |
| S   | 0.079     | 0.087 | 2.00        | 2.20 |

# MC74VHC1G05

## PACKAGE DIMENSIONS

### TSOP-5 CASE 483-02 ISSUE H




#### NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH THICKNESS. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.
4. DIMENSIONS A AND B DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.
5. OPTIONAL CONSTRUCTION: AN ADDITIONAL TRIMMED LEAD IS ALLOWED IN THIS LOCATION. TRIMMED LEAD NOT TO EXTEND MORE THAN 0.2 FROM BODY.

| DIM | MILLIMETERS |      |
|-----|-------------|------|
|     | MIN         | MAX  |
| A   | 3.00 BSC    |      |
| B   | 1.50 BSC    |      |
| C   | 0.90        | 1.10 |
| D   | 0.25        | 0.50 |
| G   | 0.95 BSC    |      |
| H   | 0.01        | 0.10 |
| J   | 0.10        | 0.26 |
| K   | 0.20        | 0.60 |
| L   | 1.25        | 1.55 |
| M   | 0°          | 10°  |
| S   | 2.50        | 3.00 |

### SOLDERING FOOTPRINT\*



\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

N. American Technical Support: 800-282-9855 Toll Free  
USA/Canada  
Europe, Middle East and Africa Technical Support:  
Phone: 421 33 790 2910  
Japan Customer Focus Center  
Phone: 81-3-5773-3850

ON Semiconductor Website: [www.onsemi.com](http://www.onsemi.com)

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331