August 2000


FDR8321L
P-Channel MOSFET With Gate Driver For Load Switch Application


General Description

This device is designed for configuration as a load switch and is particularly suited for Power Management in portable battery powered electronic equipment. Designed to operate from 2.5V to 8V input and supply up to 2.9A. The device features a small N-Channel MOSFET (Q1) together with a large P-Channel power MOSFET (Q2) in a single SuperSOT™-8 package.


Features

- V_{DROP} = 0.2V @ V_{IN}= 5V, I_L= 2.9A. $R_{DS(ON)}$ = 0.070 Ω
  V_{DROP} = 0.2V @ V_{IN}= 2.5V, I_L= 2A. $R_{DS(ON)}$ = 0.105 Ω.
- $V_{ON/OFF}$ Zener protection for ESD ruggedness (>6KV Human Body Model).
- High density cell design for extremely low on-resistance.






SuperSOT™-8



See Application Circuit



Absolute Maximum Ratings T_A = 25°C unless otherwise noted

Symbol	Parameter	FDR8321L	Units
V_{IN}	Input Voltage Range	2.5 - 8	V
$V_{ON/OFF}$	On/Off Voltage Range	1.5 - 8	V
I_L	Load Current @ V_{DROP}= 0.2V - Continuous (Note 1)	2.9	A
	- Pulsed	10	
P_D	Maximum Power Dissipation (Note 2)	0.8	W
T_J,T_{STG}	Operating and Storage Temperature Range	-55 to 150	°C
THERMAL CHARACTERISTICS			
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient (Note 2)	156	°C/W
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case (Note 2)	40	°C/W

©2000 Fairchild Semiconductor International

Electrical Characteristics (T_A = 25°C unless otherwise noted)


Symbol	Parameter	Conditions	Min	Typ	Max	Units
OFF CHARACTERISTICS						
I_{FL}	Forward Leakage Current	V_{IN} = 5 V, $V_{ON/OFF}$ = 0 V			1	µA
ON CHARACTERISTICS (Note 3)						
V_{DROP}	Conduction Voltage Drop	V_{IN} = 5 V, $V_{ON/OFF}$ = 3.3 V, I_L = 2.9 A		0.185	0.2	V
		V_{IN} = 2.5 V, $V_{ON/OFF}$ = 3.3 V, I_L= 2 A		0.18	0.2	
$R_{DS(ON)}$	Q_2 - Static Drain-Source On-Resistance	V_{GS} = -5 V, I_D = -2.9 A		0.06	0.07	Ω
		V_{GS} = -2.5 V, I_D = -2 A		0.09	0.105	
I_L	Load Current	V_{DROP} = 0.2 V, V_{IN} = 5 V, $V_{ON/OFF}$ = 3.3 V	2.9			A
		V_{DROP} = 0.2 V, V_{IN} = 2.5 V, $V_{ON/OFF}$ = 3.3 V	2			

Notes:

1. V_{IN}=5V, $V_{ON/OFF}$=8V, V_{DROP}=0.2V, T_A=25°C
2. $R_{\theta JA}$ is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins. $R_{\theta JC}$ is guaranteed by design while $R_{\theta CA}$ is determined by the user's board design. $R_{\theta JA}$ typical =156°C/W when mounted on a minimum 0.0025 in^2 pad on FR-4.
3. Pulse Test: Pulse Width ≤ 300µs, Duty Cycle ≤ 2.0%

FDR8321L Load Switch Application

APPLICATION CIRCUIT



External Component Recommendation

First select R2, 100 - 1kΩ, for Slew Rate control.
C1 ≤ 1000pF can be added in addition to R2 for further In-rush current control.
Then select R1 such that R1/R2 ratio maintains between 10 - 100. R1 is required to turn Q2 off.
For SPICE simulation, users can download a "FDR8321L.MOD" Spice model from Fairchild Web Site at www.fairchildsemi.com

Typical Electrical Characteristics (T_A = 25 °C unless otherwise noted)




Figure 1. Conduction Voltage Drop versus Load Current at Input Voltage 5V.




Figure 2. Conduction Voltage Drop versus Load Current at Input Voltage 2.5V.




Figure 3. Conduction Voltage Drop versus input Voltage at Load Current 2.9A.




Figure 4. Conduction Voltage Drop versus Input Voltage at Load Current 2A.




Figure 5. Switching Variation with R_2 at V_{in} = 5V and R_1 = 10KΩ.




Figure 6. Switching Variation with R_2 at V_{in} = 2.5V and R_1 = 10KΩ.

Typical Electrical Characteristics (T_A = 25 °C unless otherwise noted)





Figure 7. Transient Thermal Response Curve.

Thermal characterization performed on the conditions described in Note 2.

SuperSOT™-8 Tape and Reel Data and Package Dimensions

FAIRCHILD SEMICONDUCTOR™


SSOT-8 Packaging Configuration: Figure 1.0



Packaging Description:


SSOT-8 parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 3,000 units per 13" or 330cm diameter reel. The reels are dark blue in color and is made of polystyrene plastic (anti-static coated). Other option comes in 500 units per 7" or 177cm diameter reel. This and some other options are further described in the Packaging Information table.

These full reels are individually barcode labeled and placed inside a standard intermediate box (illustrated in figure 1.0) made of recyclable corrugated brown paper. One box contains two reels maximum. And these boxes are placed inside a barcode labeled shipping box which comes in different sizes depending on the number of parts shipped.




SSOT-8 Unit Orientation


SSOT-8 Packaging Information		
Packaging Option	Standard (no flow code)	D84Z
Packaging type	TNR	TNR
Qty per Reel/Tube/Bag	3,000	500
Reel Size	13" Dia	7" Dia
Box Dimension (mm)	343x64x343	184x187x47
Max qty per Box	6,000	1,000
Weight per unit (gm)	0.0416	0.0416
Weight per Reel (kg)	0.5615	0.0980
Note/Comments		



F63TNR Label sample




SSOT-8 Tape Leader and Trailer Configuration: Figure 2.0



SuperSOT™-8 Tape and Reel Data and Package Dimensions, continued

SSOT-8 Embossed Carrier Tape

Configuration: Figure 3.0




Dimensions are in millimeter														
Pkg type	**A0**	**B0**	**W**	**D0**	**D1**	**E1**	**E2**	**F**	**P1**	**P0**	**K0**	**T**	**Wc**	**Tc**
SSOT-8 (12mm)	4.47 +/-0.10	5.00 +/-0.10	12.0 +/-0.3	1.55 +/-0.05	1.50 +/-0.10	1.75 +/-0.10	10.25 min	5.50 +/-0.05	8.0 +/-0.1	4.0 +/-0.1	1.37 +/-0.10	0.280 +/-0.150	9.5 +/-0.025	0.06 +/-0.02


Notes: A0, B0, and K0 dimensions are determined with respect to the EIA/Jedec RS-481 rotational and lateral movement requirements (see sketches A, B, and C).



Sketch A (Side or Front Sectional View)
Component Rotation




Sketch B (Top View)
Component Rotation




Sketch C (Top View)
Component lateral movement


SSOT-8 Reel Configuration: Figure 4.0



13" Diameter Option




7" Diameter Option




Dimensions are in inches and millimeters									
Tape Size	**Reel Option**	**Dim A**	**Dim B**	**Dim C**	**Dim D**	**Dim N**	**Dim W1**	**Dim W2**	**Dim W3 (LSL-USL)**
12mm	7" Dia	7.00 177.8	0.059 1.5	512 +0.020/-0.008 13 +0.5/-0.2	0.795 20.2	5.906 150	0.488 +0.078/-0.000 12.4 +2/0	0.724 18.4	0.469 – 0.606 11.9 – 15.4
12mm	13" Dia	13.00 330	0.059 1.5	512 +0.020/-0.008 13 +0.5/-0.2	0.795 20.2	7.00 178	0.488 +0.078/-0.000 12.4 +2/0	0.724 18.4	0.469 – 0.606 11.9 – 15.4

SuperSOT™-8 Tape and Reel Data and Package Dimensions, continued

SuperSOT™-8 (FS PKG Code 34, 35)






Scale 1:1 on letter size paper

Dimensions shown below are in:
inches [millimeters]

Part Weight per unit (gram): 0.0416



NOTES : UNLESS OTHERWISE SPECIFIED

1. STANDARD LEAD FINISH TI BE 200 MICROINCHES / 5.08 MICROMETERS MINIMUM TIN/LEAD (SOLDER) ON COPPER.
2. NO JEDEC REGISTRATION AS JAN. 1996

TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACEx™
Bottomless™
CoolFET™
CROSSVOLT™
DOME™
E²CMOS™
EnSigna™
FACT™
FACT Quiet Series™
FAST®
FASTr™
GlobalOptoisolator™
GTO™
HiSeC™
ISOPLANAR™
MICROWIRE™
OPTOLOGIC™
OPTOPLANAR™
POP™
PowerTrench®
QFET™
QS™
QT Optoelectronics™
Quiet Series™
SuperSOT™-3
SuperSOT™-6
SuperSOT™-8
SyncFET™
TinyLogic™
UHC™
VCX™

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.
As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.

Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург, Промышленная ул, дом № 19, литера Н, помещение 100-Н Офис 331