

# High Performance Schottky Rectifier, 100 A



PowerTab®



## FEATURES

- 175 °C max. operating junction temperature
- High frequency operation
- Low forward voltage drop
- Continuous high current operation
- Guard ring for enhanced ruggedness and long term reliability
- Screw mounting only
- Designed and qualified according to JEDEC®-JESD 47
- PowerTab® package
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)


**RoHS**  
COMPLIANT

## PRODUCT SUMMARY

|                 |                  |
|-----------------|------------------|
| Package         | PowerTab®        |
| $I_{F(AV)}$     | 100 A            |
| $V_R$           | 100 V            |
| $V_F$ at $I_F$  | 0.82 V           |
| $I_{RM}$        | 180 mA at 125 °C |
| $T_J$ max.      | 175 °C           |
| Diode variation | Single die       |
| $E_{AS}$        | 9 mJ             |

## DESCRIPTION

The VS-100BGQ100 Schottky rectifier has been optimized for low reverse leakage at high temperature.

The proprietary barrier technology allows for reliable operation up to 175 °C junction temperature. Typical applications are in switching power supplies, converters, reverse battery protection, and redundant power subsystems.

## MAJOR RATINGS AND CHARACTERISTICS

| SYMBOL      | CHARACTERISTICS        | VALUES      | UNITS |
|-------------|------------------------|-------------|-------|
| $I_{F(AV)}$ | Rectangular waveform   | 100         | A     |
|             | $T_C$                  | 124         | °C    |
| $V_{RRM}$   |                        | 100         | V     |
| $I_{FSM}$   | $t_p = 5 \mu s$ sine   | 6300        | A     |
| $V_F$       | 100 $A_{pk}$ (typical) | 0.77        | V     |
|             | $T_J$                  | 125         | °C    |
| $T_J$       | Range                  | -55 to +175 | °C    |

## VOLTAGE RATINGS

| PARAMETER                            | SYMBOL    | 100BGQ100 | UNITS |
|--------------------------------------|-----------|-----------|-------|
| Maximum DC reverse voltage           | $V_R$     | 100       | V     |
| Maximum working peak reverse voltage | $V_{RWM}$ |           |       |

## ABSOLUTE MAXIMUM RATINGS

| PARAMETER                                           | SYMBOL      | TEST CONDITIONS                                                                                                     | VALUES | UNITS |
|-----------------------------------------------------|-------------|---------------------------------------------------------------------------------------------------------------------|--------|-------|
| Maximum average forward current                     | $I_{F(AV)}$ | 50 % duty cycle at $T_C = 124$ °C, rectangular waveform                                                             | 100    | A     |
| Maximum peak one cycle non-repetitive surge current | $I_{FSM}$   | 5 $\mu s$ sine or 3 $\mu s$ rect. pulse                                                                             | 6300   | A     |
|                                                     |             | 10 ms sine or 6 ms rect. pulse                                                                                      | 800    |       |
| Non-repetitive avalanche energy                     | $E_{AS}$    | $T_J = 25$ °C, $I_{AS} = 2$ A, $L = 4.5$ mH                                                                         | 9      | mJ    |
| Repetitive avalanche current                        | $I_{AR}$    | Current decaying linearly to zero in 1 $\mu s$<br>Frequency limited by $T_J$ maximum $V_A = 1.5 \times V_R$ typical | 2      | A     |

**ELECTRICAL SPECIFICATIONS**

| PARAMETER                      | SYMBOL         | TEST CONDITIONS                                                                             |                                     | VALUES |      | UNITS            |
|--------------------------------|----------------|---------------------------------------------------------------------------------------------|-------------------------------------|--------|------|------------------|
|                                |                |                                                                                             |                                     | TYP.   | MAX. |                  |
| Forward voltage drop           | $V_{FM}^{(1)}$ | 50 A                                                                                        | $T_J = 25\text{ }^{\circ}\text{C}$  | 0.83   | 0.86 | V                |
|                                |                | 100 A                                                                                       |                                     | 1.01   | 1.08 |                  |
|                                |                | 50 A                                                                                        | $T_J = 125\text{ }^{\circ}\text{C}$ | 0.66   | 0.7  |                  |
|                                |                | 100 A                                                                                       |                                     | 0.77   | 0.82 |                  |
| Reverse leakage current        | $I_{RM}^{(1)}$ | $T_J = 25\text{ }^{\circ}\text{C}$                                                          | $V_R = \text{Rated } V_R$           | 22     | 300  | $\mu\text{A}$    |
|                                |                | $T_J = 125\text{ }^{\circ}\text{C}$                                                         |                                     | 14     | 18   | mA               |
| Maximum junction capacitance   | $C_T$          | $V_R = 5\text{ }V_{DC}$ , (test signal range 100 kHz to 1 MHz) $25\text{ }^{\circ}\text{C}$ |                                     | 1320   |      | pF               |
| Typical series inductance      | $L_S$          | Measured from tab to mounting plane                                                         |                                     | 3.5    |      | nH               |
| Maximum voltage rate of change | $dV/dt$        | Rated $V_R$                                                                                 |                                     | 10 000 |      | V/ $\mu\text{s}$ |

**Note**(1) Pulse width < 300  $\mu\text{s}$ , duty cycle < 2 %**THERMAL - MECHANICAL SPECIFICATIONS**

| PARAMETER                                      | SYMBOL                            | TEST CONDITIONS                      | VALUES      | UNITS               |
|------------------------------------------------|-----------------------------------|--------------------------------------|-------------|---------------------|
| Maximum junction and storage temperature range | T <sub>J</sub> , T <sub>Stg</sub> |                                      | -55 to +175 | °C                  |
| Maximum thermal resistance, junction to case   | R <sub>thJC</sub>                 | DC operation                         | 0.50        | °C/W                |
| Typical thermal resistance, case to heatsink   | R <sub>thCS</sub>                 | Mounting surface, smooth and greased | 0.30        |                     |
| Approximate weight                             |                                   |                                      | 5           | g                   |
|                                                |                                   |                                      | 0.18        | oz.                 |
| Mounting torque                                | minimum                           |                                      | 1.2 (10)    | N · m<br>(lbf · in) |
|                                                | maximum                           |                                      | 2.4 (20)    |                     |
| Marking device                                 |                                   | Case style PowerTab®                 | 100BGQ100   |                     |




Fig. 1 - Maximum Forward Voltage Drop Characteristics




Fig. 2 - Typical Values of Reverse Current vs. Reverse Voltage





Fig. 3 - Typical Junction Capacitance vs. Reverse Voltage


Fig. 4 - Maximum Thermal Impedance  $Z_{thJC}$  Characteristics




Fig. 5 - Maximum Allowable Case Temperature vs. Average Forward Current




Fig. 6 - Forward Power Loss Characteristics




Fig. 7 - Maximum Non-Repetitive Surge Current





Fig. 8 - Unclamped Inductive Test Circuit

#### Note

- (1) Formula used:  $T_C = T_J - (P_d + P_{dREV}) \times R_{thJC}$ ;  
 $P_d$  = Forward power loss =  $I_{F(AV)} \times V_{FM}$  at  $(I_{F(AV)}/D)$  (see fig. 6);  
 $P_{dREV}$  = Inverse power loss =  $V_{R1} \times I_R (1 - D)$ ;  $I_R$  at  $V_{R1} = 80\%$  rated  $V_R$



**ORDERING INFORMATION TABLE**



| LINKS TO RELATED DOCUMENTS |                                                                        |
|----------------------------|------------------------------------------------------------------------|
| Dimensions                 | <a href="http://www.vishay.com/doc?95240">www.vishay.com/doc?95240</a> |
| Part marking information   | <a href="http://www.vishay.com/doc?95370">www.vishay.com/doc?95370</a> |
| Application note           | <a href="http://www.vishay.com/doc?95179">www.vishay.com/doc?95179</a> |



## PowerTab®

### DIMENSIONS in millimeters (inches)





## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331