RTV Silicones

RTV Number... GO

ALL MG PRODUCTS

Jump to Product Number

Product Number... GO

- Accessories
- Adhesives
- Brushes
- Cleaners / Degreasers
- Contact Cleaners
- Desoldering Braid
- Dusters & Circuit Coolers
- EMI / RFI Shielding
- Epoxies
- Flux and Flux Remover
- Glass & Screen Cleaners
- Isopropyl Alcohol
- Lead Free Solder
- Lubricants
- Potting & Encapsulating
- Protective Coatings
- Pens
- Prototyping Materials
- RTV Silicones
- Soldering/desoldering
- Specialized Cleaners
- Swabs
- Thermal Management
- Thermally Conductive Adhesives
- Wipes

RTV Silicones by MOMENTIVE performance materials

RoHS COMPLIANT

2-Part Potting/Encapsulating Compound

RTV630

STOCKED ITEM

BUY NOW

Primary Characteristics
- Self leveling
- Addition cure
- Cures in deep sections
- **Very high strength**
- Medium viscosity
- Primer required

Use for:
- Encapsulating applications requiring high tensile strength
- Exceptionally deep potting applications

Will form thin, light-weight molds with excellent durability. The high tear resistance and inherent release ability make it well suited to the manufacture of intricate castings, by reproducing each part exactly to detail. Other applications include prototype parts, production tools for casting epoxies and rubber rolls. Electrical circuits require a tough potting compound with outstanding vibration withstanding capability find RTV630 unequalled. Silicone primeris required.

Available Sizes

Catalog Number	Sizes Available	Description
RTV630-1P	1 pint	1 lb kit
RTV630 requires a primer. Visit our primer guide for details.		

Specifications

Use	Adhesive Sealant
Special Feature	High tensile strength
Cross Reference	RTV630
Uncured Properties	
Consistency	Pourable
Color	Beige (part A) Blue (part B)
Specific Gravity	1.28
Tack Free Time	4 hours
Cure Through Time	7 days @ 25°C 15 min @ 150°C
Useful Temp. Range	-60°C to 204°C (-75°F to 400°F)
Cured Properties - MECHANICAL	
Hardness	60 (Shore A)
Tensile Strength	5.69 MPa (820 psi)
Elongation	250%
Tear Strength	20 kg/cm (110 lb/in)
Cured Properties - ELECTRICAL	
Volume Resistivity	4.5 x 10^{15} ohm · cm
Dielectric Strength	17.7 kV/mm (450 V/mil)
Dielectric Constant	3.2 @ 1000 Hz
Cured Properties - THERMAL	

Technical Support for RTV Silicones

☎1-800-255-8886

M.G. Chemicals Disclaimer for RTV Silicones >

Locate Distributor >

Quick Links

- MSDS
- Catalyst options/MSDS
- Primer options/MSDS
- Specifications
- Available Sizes

Related products:
- RTV21
- RTV31
- RTV60
- RTV88
- RTV560
- RTV566
- RTV577
- RTV630
- RTV656

Resources

- Selection Guide
- One Part Chart
- Two Part Chart

Find by Application

- General Purpose
- Aerospace
- Marine
- High Performance Assembly
- Electronics
- Thermal Conductivity
- High Temperature
- Low Temperature

Google

Google Search MG

Thermal Conductivity	0.25 W/m · °K
Brittle Point	-60°C (-75°F)
Thermal Expansion	21 x 10^{-5} $(°C)^{-1}$
Other	
Viscosity (@ 25°C)	150,000 cps
Mix Ratio (by weight)	10 : 1
Pot Life	4 hours

Return to top ^

© 2000 - 2007 MG Chemicals. All rights reserved. Site Map Terms & Conditions Contact Us

web site design by offbeat studio

Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург, Промышленная ул, дом № 19, литера Н, помещение 100-Н Офис 331