


# PZTA29

## NPN Darlington Transistor

- This device designed for applications requiring extremely high current gain at collector currents to 500mA.
- Sourced from process 03.



1. Base 2.4. Collector 3. Emitter

### Absolute Maximum Ratings \* $T_a = 25^\circ\text{C}$ unless otherwise noted

| Symbol         | Parameter                                        | Value       | Units            |
|----------------|--------------------------------------------------|-------------|------------------|
| $V_{CES}$      | Collector-Emitter Voltage                        | 100         | V                |
| $V_{CBO}$      | Collector-Base Voltage                           | 100         | V                |
| $V_{EBO}$      | Emitter-Base Voltage                             | 12          | V                |
| $I_C$          | Collector Current - Continuous                   | 800         | mA               |
| $T_J, T_{STG}$ | Operating and Storage Junction Temperature Range | -55 to +150 | $^\circ\text{C}$ |

\* These ratings are limiting values above which the serviceability of any semiconductor device may be impaired.

#### NOTES:

1. These ratings are based on a maximum junction temperature of 150 degrees C.
2. These are steady limits. The factory should be consulted on application involving pulsed or low duty cycle operations

### Electrical Characteristics $T_a = 25^\circ\text{C}$ unless otherwise noted

| Symbol                              | Parameter                            | Conditions                                                                              | Min.             | Max        | Units  |
|-------------------------------------|--------------------------------------|-----------------------------------------------------------------------------------------|------------------|------------|--------|
| <b>Off Characteristics</b>          |                                      |                                                                                         |                  |            |        |
| $V_{(BR)CES}$                       | Collector-Emitter Breakdown Voltage  | $I_C = 100\mu\text{A}, V_{BE} = 0$                                                      | 100              |            | V      |
| $V_{(BR)CBO}$                       | Collector-Base Breakdown Voltage     | $I_C = 100\mu\text{A}, I_E = 0$                                                         | 100              |            | V      |
| $V_{(BR)EBO}$                       | Emitter-Base Breakdown Voltage       | $I_E = 10\mu\text{A}, I_C = 0$                                                          | 12               |            | V      |
| $I_{CBO}$                           | Collector Cutoff Current             | $V_{CB} = 80\text{V}, I_E = 0$                                                          |                  | 100        | nA     |
| $I_{CES}$                           | Collector Cutoff Current             | $V_{CE} = 80\text{V}, V_{BE} = 0$                                                       |                  | 500        | nA     |
| $I_{EBO}$                           | Emitter Cut-off Current              | $V_{EB} = 10\text{V}, I_C = 0$                                                          |                  | 100        | nA     |
| <b>On Characteristics</b>           |                                      |                                                                                         |                  |            |        |
| $h_{FE}$                            | DC Current Gain                      | $V_{CE} = 5.0\text{V}, I_C = 10\text{mA}$<br>$V_{CE} = 5.0\text{V}, I_C = 100\text{mA}$ | 10,000<br>10,000 |            |        |
| $V_{CE(sat)}$                       | Collector-Emitter Saturation Voltage | $I_C = 10\text{mA}, I_B = 0.01\text{mA}$<br>$I_C = 100\text{mA}, I_B = 0.1\text{mA}$    |                  | 1.2<br>1.5 | V<br>V |
| $V_{BE(on)}$                        | Base-Emitter On Voltage              | $I_C = 100\text{mA}, V_{CE} = 5.0\text{V}$                                              |                  | 2.0        | V      |
| <b>Small Signal characteristics</b> |                                      |                                                                                         |                  |            |        |
| $f_T$                               | Current Gain Bandwidth Product       | $I_C = 10\text{mA}, V_{CE} = 5.0\text{V}, f = 100\text{MHz}$                            | 125              |            | MHz    |
| $C_{obo}$                           | Output Capacitance                   | $V_{CB} = 1.0\text{V}, I_E = 0, f = 1.0\text{MHz}$                                      |                  | 8.0        | pF     |

\* Pulse Test: Pulse Width  $\leq 300\mu\text{s}$ , Duty Cycle  $\leq 2.0\%$


**Thermal Characteristics**  $T_a = 25^\circ\text{C}$  unless otherwise noted

| Symbol          | Parameter                               | Max.  | Units                |
|-----------------|-----------------------------------------|-------|----------------------|
| $P_D$           | Total Device Dissipation                | 1,000 | mW                   |
|                 | Derate above $25^\circ\text{C}$         | 8.0   | mW/ $^\circ\text{C}$ |
| $R_{\theta JA}$ | Thermal Resistance, Junction to Ambient | 125   | $^\circ\text{C/W}$   |

\* Device mounted on FR-4PCB  $36\text{mm} \times 18\text{mm} \times 1.5\text{mm}$ ; mounting pad for the collector lead min.  $6\text{cm}^2$

## Mechanical Dimensions

## SOT-223



SOT223, 4 LEADS

Dimensions in Millimeters

## TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

|                                                  |                                 |                           |                                 |                             |
|--------------------------------------------------|---------------------------------|---------------------------|---------------------------------|-----------------------------|
| ACE <sup>™</sup>                                 | FAST <sup>®</sup>               | IntelliMAX <sup>™</sup>   | POP <sup>™</sup>                | SPM <sup>™</sup>            |
| ActiveArray <sup>™</sup>                         | FAST <sup>™</sup>               | ISOPLANAR <sup>™</sup>    | Power247 <sup>™</sup>           | Stealth <sup>™</sup>        |
| Bottomless <sup>™</sup>                          | FPS <sup>™</sup>                | LittleFET <sup>™</sup>    | PowerEdge <sup>™</sup>          | SuperFET <sup>™</sup>       |
| CoolFET <sup>™</sup>                             | FRFET <sup>™</sup>              | MICROCOUPLER <sup>™</sup> | PowerSaver <sup>™</sup>         | SuperSOT <sup>™</sup> -3    |
| CROSSVOLT <sup>™</sup>                           | GlobalOptoisolator <sup>™</sup> | MicroFET <sup>™</sup>     | PowerTrench <sup>®</sup>        | SuperSOT <sup>™</sup> -6    |
| DOVE <sup>™</sup>                                | GTO <sup>™</sup>                | MicroPak <sup>™</sup>     | QFET <sup>®</sup>               | SuperSOT <sup>™</sup> -8    |
| EcoSPARK <sup>™</sup>                            | HiSeC <sup>™</sup>              | MICROWIRE <sup>™</sup>    | QS <sup>™</sup>                 | SyncFET <sup>™</sup>        |
| E <sup>2</sup> CMOS <sup>™</sup>                 | I <sup>2</sup> C <sup>™</sup>   | MSX <sup>™</sup>          | QT Optoelectronics <sup>™</sup> | TinyLogic <sup>®</sup>      |
| EnSigna <sup>™</sup>                             | i-Lo <sup>™</sup>               | MSXPro <sup>™</sup>       | Quiet Series <sup>™</sup>       | TINYOPTO <sup>™</sup>       |
| FACT <sup>™</sup>                                | ImpliedDisconnect <sup>™</sup>  | OCX <sup>™</sup>          | RapidConfigure <sup>™</sup>     | TruTranslation <sup>™</sup> |
| FACT Quiet Series <sup>™</sup>                   |                                 | OCXPro <sup>™</sup>       | RapidConnect <sup>™</sup>       | UHC <sup>™</sup>            |
| Across the board. Around the world. <sup>™</sup> |                                 | OPTOLOGIC <sup>®</sup>    | μSerDes <sup>™</sup>            | UltraFET <sup>®</sup>       |
| The Power Franchise <sup>®</sup>                 |                                 | OPTOPLANAR <sup>™</sup>   | SILENT SWITCHER <sup>®</sup>    | UniFET <sup>™</sup>         |
| Programmable Active Droop <sup>™</sup>           |                                 | PACMAN <sup>™</sup>       | SMART START <sup>™</sup>        | VCX <sup>™</sup>            |

## DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

## PRODUCT STATUS DEFINITIONS

### Definition of Terms

| Datasheet Identification | Product Status         | Definition                                                                                                                                                                                                            |
|--------------------------|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Advance Information      | Formative or In Design | This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.                                                                                    |
| Preliminary              | First Production       | This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design. |
| No Identification Needed | Full Production        | This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.                                                       |
| Obsolete                 | Not In Production      | This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.                                                   |

Rev. 115



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331