
BAR46
BAR46AFILM

SMALL SIGNAL SCHOTTKY DIODES

FEATURES AND BENEFITS

- VERY SMALL CONDUCTION LOSSES
- NEGLIGIBLE SWITCHING LOSSES
- LOW FORWARD VOLTAGE DROP
- SURFACE MOUNT DEVICE



BAR46 **BAR46A**

SOT-23
(Plastic)

DESCRIPTION

High voltage Schottky rectifier suited for SLIC protection during the card insertion operation.

ABSOLUTE RATINGS(limiting values)

Symbol	Parameter		Value	Unit
V_{RRM}	Repetitive peak reverse voltage		100	V
I_F	Continuous forward current		150	mA
P_{tot}	Power dissipation (note 1)	Tamb = 25°C	230	mW
T_{stg}	Maximum storage temperature range		- 65 to +150	°C
Tj	Maximum operating junction temperature *		150	°C
T_L	Maximum temperature for soldering during 10s		260	°C

Note 1: for double diodes, Ptot is the total dissipation of both diodes.

$* : \frac{dPtot}{dTj} < \frac{1}{Rth(j-a)}$ thermal runaway condition for a diode on its own heatsink

THERMAL RESISTANCE

Symbol	Parameter	Value	Unit
Rth(j-a)	Junction-ambient *	500	°C/W

* Mounted on epoxy board, with recommended pad layout.

ELECTRICAL CHARACTERISTICS

STATIC CHARACTERISTICS

Symbol	Test conditions		Min.	Typ.	Max.	Unit
V_{BR}	Tj = 25 °C	I_R = 100 µA	100			V
V_F *	Tj = 25 °C	I_F = 0.1 mA			0.25	V
	Tj = 25 °C	I_F = 10 mA			0.45	
	Tj = 25 °C	I_F = 250 mA			1	
I_R**	Tj = 25 °C	V_R = 1.5 V			0.5	µA
	Tj = 60 °C				5	
	Tj = 25 °C	V_R = 10 V			0.8	
	Tj = 60 °C				7.5	
	Tj = 25 °C	V_R = 50 V			2	
	Tj = 60 °C				15	
	Tj = 25 °C	V_R = 75 V			5	
	Tj = 60 °C				20	

Pulse test : * tp = 380µs $\delta < 2\%$
** tp = 5 ms, $\delta < 2\%$

DYNAMIC CHARACTERISTICS

Symbol	Test conditions			Min.	Typ.	Max.	Unit
C	Tj = 25 °C	V_R = 0 V	F = 1MHz		10		pF
	Tj = 25 °C	V_R = 1 V			6		

Fig. 1: Forward current versus forward voltage at different temperatures (typical values).




Fig. 2: Forward current versus forward voltage (typical values).




Fig. 3: Reverse current versus junction temperature (typical values).




Fig. 4: Reverse current versus continuous reverse voltage (typical values).






Fig. 5: Capacitance C versus reverse applied voltage V_R (typical values).




PACKAGE MECHANICAL DATA

SOT-23 (Plastic)



REF.	DIMENSIONS			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	0.89	1.4	0.035	0.055
A1	0	0.1	0	0.004
B	0.3	0.51	0.012	0.02
c	0.085	0.18	0.003	0.007
D	2.75	3.04	0.108	0.12
e	0.85	1.05	0.033	0.041
e1	1.7	2.1	0.067	0.083
E	1.2	1.6	0.047	0.063
H	2.1	2.75	0.083	0.108
L	0.6 typ.		0.024 typ.	
S	0.35	0.65	0.014	0.026

FOOT PRINT DIMENSIONS (Millimeter)



Ordering type	Marking	Package	Weight	Base qty	Delivery mode
BAR46	S46	SOT-23	0.01g	3000	Tape & reel
BAR46AFILM	A46	SOT-23	0.01g	3000	Tape & reel

- Epoxy meets UL94,V0

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied.
STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics

© 2002 STMicroelectronics - Printed in Italy - All rights reserved.

STMicroelectronics GROUP OF COMPANIES
Australia - Brazil - Canada - China - Finland - France - Germany
Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore
Spain - Sweden - Switzerland - United Kingdom - United States.

http://www.st.com

Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург, Промышленная ул, дом № 19, литера Н, помещение 100-Н Офис 331