
THESE DRAWINGS AND SPECIFICATIONS ARE THE SOLE PROPERTY OF I/O INTERCONNECT INC. U.S.A. AND SHALL NOT BE REPRODUCED, COPIED, OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF I/O INTERCONNECT INC. OR ITS AFFILIATED SUBSIDIARIES.

DWG. NO.	ZONE	REV.	DESCRIPTION	DATE	APPROV
X10-0X3		F	ECN 387	06/09/95	G T





BUNDLE SPECIFICATION

NOTES: UNLESS OTHERWISED SPECIFIED.

1.0 PACKAGING SPECIFICATION

1.01 USE CLEAR TAPE TO BUNDLE 25 CABLES TOGETHER AT THE MID SECTION.

1.02 PLACE PLASTIC BAG IN SHIPPING BOX AND LAY 10 BUNDLE OR 250 PIECES MAX. PER SHIPPING BOX. CLOSE PLASTIC BAG AND SEAL BOX ALONG 3 SURFACES WITH TAPE.

CONDUCTORS NUMBER OF	MILLIMETERS RETRACTED LENGTH 'R'	INCHES	DIMENSION MAX. OUTSIDE SHIPPING BOX
4	431.80	[17.000]	L=13.00" X W=20.00" X H=9.0
6	457.20	[18.000]	L=13.00" X W=20.00" X H=9.0
8	558.80	[22.000]	L=13.00" X W=25.00" X H=9.0

TABULATION BLOCK

THIRD ANGLE PROJECTION

UNLESS OTHERWISED NOTED:
1) DIMENSIONS ARE IN MILLIMETER [INCHES]
2) TOLERANCES:
X.X ± 0.20 [0.008]
XXX ± 6.35 [0.250]

I/O INTERCONNECT
SANTA ANA, CALIFORNIA

DR: C. WANG 06/09/95
CHKD:
CHKD:
CHKD:
CHKD: 6/6/95

TITLE: 26 AWG (12/0.12 mm) BARE COPP 5.00 FT EXTENDED, NON-UL, UNSHIELDED, MODULAR CABLE

PART NO: 121-X10-0X3


CUSTOMER: I/O INTERCONNECT


SCALE: NONE

SHEET 2 OF

THESE DRAWINGS AND SPECIFICATIONS ARE THE SOLE PROPERTY OF I/O INTERCONNECT INC. U.S.A. AND SHALL NOT BE REPRODUCED, COPIED, OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF I/O INTERCONNECT INC. OR ITS AFFILIATED SUBSIDIARIES

DWG. NO.	ZONE	REV.	DESCRIPTION	DATE	APPROV
X10-0X2		1	ECN 387	06/09/95	C.T





BUNDLE SPECIFICATION

NOTES: UNLESS OTHERWISED SPECIFIED.

1.0 PACKAGING SPECIFICATION

1.01 USE CLEAR TAPE TO BUNDLE 25 CABLES TOGETHER AT THE MID SECTION.

1.02 PLACE PLASTIC BAG IN SHIPPING BOX AND LAY 10 BUNDLE OR 250 PIECES MAX. PER SHIPPING BOX. CLOSE PLASTIC BAG AND SEAL BOX ALONG 3 SURFACES WITH TAPE.

CONDUCTORS NUMBER OF	MILLIMETERS RETRACTED LENGTH 'R'	INCHES	DIMENSION MAX. OUTSIDE SHIPPING BOX
4	863.60	[34.000]	L=13.00" X W=40.00" X H=9.00
6	1117.60	[44.000]	L=13.00" X W=50.00" X H=9.00
8	1270.00	[50.000]	L=13.00" X W=55.00" X H=9.00

TABULATION BLOCK

THIRD ANGLE PROJECTION

UNLESS OTHERWISED NOTED:
1) DIMENSIONS ARE IN MILLIMETER [INCHES]
2) TOLERANCES:
X.X ± 0.20 [0.008]
X.XX ± 6.35 [0.250]

I/O INTERCONNECT
SANTA ANA, CALIFORNIA

DR: C. WANG 06/09/95
CHKD:
CHKD:
CHKD:
CHKD:

TITLE: 36 AWG (12/0.12 mm) BARE COPP 14.00 FT EXTENDED, NON-UL, UNSHIELDED, MODULAR CABLE


PART NO: 121-X10-0X2


CUSTOMER: I/O INTERCONNECT

SCALE: NONE SHEET 2 OF

THESE DRAWINGS AND SPECIFICATIONS ARE THE SOLE PROPERTY OF I/O INTERCONNECT INC., U.S.A. AND SHALL NOT BE REPRODUCED, COPIED, OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF I/O INTERCONNECT INC. OR ITS AFFILIATED SUBSIDIARIES

DWG. NO	ZONE	REV.	DESCRIPTION	DATE	APPROVED
X10-0X1		I	ECN 387	06/09/95	G.T





BUNDLE SPECIFICATION

NOTES: UNLESS OTHERWISED SPECIFIED.

1.0 PACKAGING SPECIFICATION

1.01 USE CLEAR TAPE TO BUNDLE 25 CABLES TOGETHER AT THE MID SECTION.

1.02 PLACE PLASTIC BAG IN SHIPPING BOX AND LAY 10 BUNDLE OR 250 PIECES MAX. PER SHIPPING BOX. CLOSE PLASTIC BAG AND SEAL BOX ALONG 3 SURFACES WITH TAPE.

CONDUCTORS NUMBER OF	RETRACTED LENGTH "R" MILLIMETERS	RETRACTED LENGTH "R" INCHES	DIMENSION MAX. OUTSIDE SHIPPING BOX
4	762.00	[30.000]	L=10.00" X W=35.00" X H=9.00"
6	812.80	[32.000]	L=10.00" X W=35.00" X H=9.00"
8	1066.80	[42.000]	L=10.00" X W=45.00" X H=9.00"

TABULATION BLOCK

THIRD ANGLE PROJECTION

UNLESS OTHERWISED NOTED:
1) DIMENSIONS ARE IN MILLIMETER [INCHES]
2) TOLERANCES:
X.X ± 0.20 [0.008]
X.XX ± 6.35 [0.250]

I/O INTERCONNECT
SANTA ANA, CALIFORNIA

DR: C. WANG 06/09/95
CHKD:
CHKD:
CHKD:
CHKD:

TITLE: 26 AWG (12/0.12 mm) BARE COPPER 10.00 FT EXTENDED, NON-UL, UNSHIELDED, MODULAR CABLE

PART NO: 121-X10-0X1

CUSTOMER: I/O INTERCONNECT


REV: I


SCALE: NONE

SHEET 2 OF 2

THESE DRAWINGS AND SPECIFICATIONS ARE THE SOLE PROPERTY OF I/O INTERCONNECT INC. U.S.A. AND SHALL NOT BE REPRODUCED, COPIED, OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF I/O INTERCONNECT INC OR ITS AFFILIATED SUBSIDIARIES

DWG NO	ZONE	REV	DESCRIPTION	DATE	APPROV
X10-0X0		D	ECN 387	06/09/95	G.T





BUNDLE SPECIFICATION

NOTES UNLESS OTHERWISED SPECIFIED.

1.0 PACKAGING SPECIFICATION

1.01 USE CLEAR TAPE TO BUNDLE 25 CABLES TOGETHER AT THE MID SECTION.

1.02 PLACE PLASTIC BAG IN SHIPPING BOX AND LAY 10 BUNDLE OR 250 PIECES MAX. PER SHIPPING BOX. CLOSE PLASTIC BAG AND SEAL BOX ALONG 3 SURFACES WITH TAPE.

CONDUCTORS NUMBER OF	MILLIMETERS RETRACTED LENGTH 'R'	INCHES	DIMENSION MAX. OUTSIDE SHIPPING BOX
4	533.40	(21.000)	L=13.00" X W=25.00" X H=9.0
6	609.60	(24.000)	L=13.00" X W=25.00" X H=9.0
8	711.20	(28.000)	L=13.00" X W=30.00" X H=9.0

TABULATION BLOCK

THIRD ANGLE PROJECTION

UNLESS OTHERWISED NOTED:
1) DIMENSIONS ARE IN MILLIMETER (INCHES)
2) TOLERANCES:
X.X ± 0.20 (0.008)
X.XX ± 6.35 (0.250)

I/O INTERCONNECT
SANTA ANA, CALIFORNIA

DR: C. WANG 06/09/95
CHKD:
CHKD:
CHKD:
CHKD:

TITLE: 26 AWG (12/0.12 mm) BARE COPP
7.00 FT EXTENDED, NON-UL
UNSHIELDED, MODULAR CABLE


PART NO 121-X10-0X0

CUSTOMER: I/O INTERCONNECT


SCALE: NONE SHEET 2 OF

THESE DRAWINGS AND SPECIFICATIONS ARE THE SOLE PROPERTY OF I/O INTERCONNECT INC. U.S.A. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF I/O INTERCONNECT INC. OR ITS AFFILIATED SUBSIDIARIES.


DWG. NO.	ZONE	REV.	DESCRIPTION	DATE	APPROVED
X10-0X0		D	ECN 387	06/09/95	G.T



8 CONDUCTOR CABLE



6 CONDUCTOR CABLE



4 CONDUCTOR CABLE

NOTES: UNLESS OTHERWISED SPECIFIED.

1.0 MATERIAL AND SPECIFICATIONS

1.01 CONDUCTORS: 26 AWG (12/0.12 mm) STRANDED BARE COPPER.

1.02 INSULATION: POLYPROPYLENE

1.03 COLOR: PER CALLOUT

1.04 PACKAGING: (SEE PAGE 2)

2.0 ELECTRICAL CHARACTERISTICS

2.01 TEMPERATURE & VOLTAGE RATING: 80°C 30 V

2.02 CONDUCTORS RESISTANCE: 148 OHMS/KM MAX. AT 20°C

2.03 INSULATION RESISTANCE: 100 MEGAOHMS/KM MIN. AT 20°C

2.04 CAPACITANCE: 15 PF/FT (MAX)

2.05 DIELECTRIC TEST: AC-500V PER 1 MINUTE

I/O INTERCONNECT PART NUMBER	NUMBER OF CONDUCTORS	COLOR	Ø 'A'
121-410-000	4	SILVER SATIN	(0.551 ± 0.039) 14.00 ± 1.00
121-410-010	4	BLACK	(0.551 ± 0.039) 14.00 ± 1.00
121-410-020	4	WHITE	(0.551 ± 0.039) 14.00 ± 1.00
121-610-000	6	SILVER SATIN	(0.551 ± 0.039) 14.00 ± 1.00
121-610-010	6	BLACK	(0.551 ± 0.039) 14.00 ± 1.00
121-610-020	6	WHITE	(0.551 ± 0.039) 14.00 ± 1.00
121-810-000	8	SILVER SATIN	(0.748 ± 0.039) 19.00 ± 1.00
121-810-010	8	BLACK	(0.748 ± 0.039) 19.00 ± 1.00
121-810-020	8	WHITE	(0.748 ± 0.039) 19.00 ± 1.00

THIRD ANGLE PROJECTION

UNLESS OTHERWISED NOTED:
1) DIMENSIONS ARE IN MILLIMETER (INCHES)
2) TOLERANCES:
X.X ± 0.20 (0.008)
X.XX ± 6.35 (0.250)

I/O INTERCONNECT
SANTA ANA, CALIFORNIA

DR: C. WANG 06/09/95
CHK'D:
CHK'D:
CHK'D:
CHK'D:

TITLE: 26 AWG (12/0.12 mm) BARE COPPE 7.00 FT EXTENDED, NON-UL, UNSHIELDED, MODULAR CABLE


PART NO: 121-X10-0X0

CUSTOMER: I/O INTERCONNECT


SCALE: NONE SHEET 1 OF

THESE DRAWINGS AND SPECIFICATIONS ARE THE SOLE PROPERTY OF I/O INTERCONNECT INC. U.S.A. AND SHALL NOT BE REPRODUCED, COPIED, OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF I/O INTERCONNECT INC. OR ITS AFFILIATED SUBSIDIARIES.


DWG. NO.	ZONE	REV.	DESCRIPTION	DATE	APPROV
X10-0X3		F	ECN 387	06/09/95	GT



8 CONDUCTOR CABLE



6 CONDUCTOR CABLE



4 CONDUCTOR CABLE

NOTES: UNLESS OTHERWISED SPECIFIED.

1.0 MATERIAL AND SPECIFICATIONS

1.01 CONDUCTORS: 26 AWG (12/0.12 mm) STRANDED BARE COPPER.

1.02 INSULATION: POLYPROPYLENE

1.03 COLOR: PER CALLOUT

1.04 PACKAGING: (SEE PAGE 2)

2.0 ELECTRICAL CHARACTERISTICS

2.01 TEMPERATURE & VOLTAGE RATING: 80°C 30 V

2.02 CONDUCTORS RESISTANCE: 148 OHMS/KM MAX. AT 20°C

2.03 INSULATION RESISTANCE: 100 MEGAOHMS/KM MIN. AT 20°C

2.04 CAPACITANCE: 15 PF/FT (MAX)

2.05 DIELECTRIC TEST: AC-500V PER 1 MINUTE

I/O INTERCONNECT PART NUMBER	NUMBER OF CONDUCTORS	COLOR	Ø "A"
121-410-003	4	SILVER SATIN	[0.551 ± 0.0 14.00 ± 1.0
121-410-013	4	BLACK	[0.551 ± 0.0 14.00 ± 1.0
121-410-023	4	WHITE	[0.551 ± 0.0 14.00 ± 1.0
121-610-003	6	SILVER SATIN	[0.551 ± 0.0 14.00 ± 1.0
121-610-013	6	BLACK	[0.551 ± 0.0 14.00 ± 1.0
121-610-023	6	WHITE	[0.551 ± 0.0 14.00 ± 1.0
121-810-003	8	SILVER SATIN	[0.748 ± 0.0 19.00 ± 1.0
121-810-013	8	BLACK	[0.748 ± 0.0 19.00 ± 1.0
121-810-023	8	WHITE	[0.748 ± 0.0 19.00 ± 1.0

THIRD ANGLE PROJECTION

UNLESS OTHERWISED NOTED:
1) DIMENSIONS ARE IN MILLIMETER [INCHES]
2) TOLERANCES:
X.X ± 0.20 [0.008]
X.XX ± 6.35 [0.250]

I/O INTERCONNECT
SANTA ANA, CALIFORNIA

DR: C. WANG 06/09/95
CHKD:
CHKD:
CHKD:
CHKD:

TITLE: 26 AWG (12/0.12 mm) BARE COPP
5.00 FT EXTENDED, NON-UL,
UNSHIELDED, MODULAR CABLE


PART NO: 121-X10-0X3


CUSTOMER: I/O INTERCONNECT

SCALE: NONE SHEET 1 OF

THESE DRAWINGS AND SPECIFICATIONS ARE THE SOLE PROPERTY OF I/O INTERCONNECT INC., USA, AND SHALL NOT BE REPRODUCED, COPIED, OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF I/O INTERCONNECT INC. OR ITS AFFILIATED SUBSIDIARIES.

DWG. NO.	ZONE	REV.	DESCRIPTION	DATE	APPROVED
X10-0X3		G	ECN B435	09/15/98	R.Z.





BUNDLE SPECIFICATION

NOTES: UNLESS OTHERWISE SPECIFIED.

1.0 MATERIAL AND SPECIFICATIONS

1.01 CONDUCTORS: 26 AWG (12/0.12 mm) STRANDED BARE COPPER.

1.02 INSULATION: POLYPROPYLENE

1.03 COLOR: PER CALLOUT

1.04 PACKAGING: (SEE PAGE 2)

2.0 ELECTRICAL CHARACTERISTICS

2.01 TEMPERATURE & VOLTAGE RATING: 80°C 30 V

2.02 CONDUCTORS RESISTANCE: 140 OHMS/KM MAX. AT 20°C

2.03 INSULATION RESISTANCE: 100 MEGAOHMS/KM MIN. AT 20°C

2.04 CAPACITANCE: 65 PF/FT (MAX)

2.05 DIELECTRIC TEST: AC-500V PER 1 MINUTE

3.0 PACKAGING SPECIFICATION

3.01 USE CLEAR TAPE TO BUNDLE 25 CABLES TOGETHER AT THE MID SECTION.

3.02 PLACE PLASTIC BAG IN SHIPPING BOX AND LAY 10 BUNDLE OR 250 PIECES MAX. PER SHIPPING BOX. CLOSE PLASTIC BAG AND SEAL BOX ALONG 3 SURFACES WITH TAPE.

CONDUCTORS NUMBER OF	RETRACTED LENGTH "R" MILLIMETERS	RETRACTED LENGTH "R" INCHES	DIMENSION MAX. OUTSIDE SHIPPING BOX
4	431.80	(17.000)	L=13.00" X W=20.00" X H=9.00"
6	457.20	(18.000)	L=13.00" X W=20.00" X H=9.00"
8	558.80	(22.000)	L=13.00" X W=20.00" X H=9.00"
10	609.60	(24.000)	L=13.00" X W=20.00" X H=9.00"

TABULATION BLOCK

THIRD ANGLE PROJECTION

I/O INTERCONNECT
SANTA ANA, CALIFORNIA

UNLESS OTHERWISE NOTED
1) DIMENSIONS ARE IN MILLIMETER (INCHES)
2) TOLERANCES:
XX ± 0.20 (0.008)
XXX ± 0.35 (0.250)

DRAWN: CHAN HUI 09/13/98
CHKD:
CHKD:
CHKD:
CHKD:

TITLE: 26 AWG (12/0.12 mm) BARE COPPER 5.00 FT EXTENDED, NON-UL, UNSHIELDED, MODULAR CABLE

PART NO: 12-X10-0X3


CUSTOMER: I/O INTERCONNECT

REV: G


SCALE: NONE SHEET 2 OF 2

THESE DRAWINGS AND SPECIFICATIONS ARE THE SOLE PROPERTY OF I/O INTERCONNECT INC., USA AND SHALL NOT BE REPRODUCED, COPIED, OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF I/O INTERCONNECT INC. OR ITS AFFILIATED SUBSIDIARIES.


DWG. NO.	ZONE	REV.	DESCRIPTION	DATE	APPROVED
XXX-XXX		E	ECN 3435	09/15/98	R.Z.




8 CONDUCTOR CABLE



6 CONDUCTOR CABLE



4 CONDUCTOR CABLE



10 CONDUCTOR CABLE

I/O INTERCONNECT PART NUMBER	NUMBER OF CONDUCTORS	COLOR	A "A"
121-410-000	4	SILVER SATIN	(0.551 ± 0.039) 14.00 ± 1.00
121-410-010	4	BLACK	(0.551 ± 0.039) 14.00 ± 1.00
121-410-020	4	WHITE	(0.551 ± 0.039) 14.00 ± 1.00
121-610-000	6	SILVER SATIN	(0.551 ± 0.039) 14.00 ± 1.00
121-610-010	6	BLACK	(0.551 ± 0.039) 14.00 ± 1.00
121-610-020	6	WHITE	(0.551 ± 0.039) 14.00 ± 1.00
121-810-000	8	SILVER SATIN	(0.748 ± 0.039) 19.00 ± 1.00
121-810-010	8	BLACK	(0.748 ± 0.039) 19.00 ± 1.00
121-810-020	8	WHITE	(0.748 ± 0.039) 19.00 ± 1.00
121-010-000	10	SILVER SATIN	(0.748 ± 0.039) 19.00 ± 1.00
121-010-010	10	BLACK	(0.748 ± 0.039) 19.00 ± 1.00
121-010-020	10	WHITE	(0.748 ± 0.039) 19.00 ± 1.00

THIRD ANGLE PROJECTION

UNLESS OTHERWISED NOTED:
1) DIMENSIONS ARE IN MILLIMETER [INCHES]
2) TOLERANCES
X.X ± 0.20 [0.008]
X.XX ± 6.35 [0.250]

I/O INTERCONNECT
SANTA ANA, CALIFORNIA

DRAWN [illegible] 09/23/98
CHKD
CHKD
CHKD
CHKD

TITLE: 26 AWG (12/0.12 mm) BARE COPPER 7.00 FT EXTENDED, NON-UL, UNSHIELDED, MODULAR CABLE

PART NO. 121-710-0X0

CUSTOMER: I/O INTERCONNECT

REV. E

SCALE: NONE

SHEET 1 OF 2

Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург, Промышленная ул, дом № 19, литера Н, помещение 100-Н Офис 331