
# WorldTran™

**International Power Transformer**

## Series: VDE - Lead Wires

- Power Rating 25VA to 175VA
- Single or Dual Primary, 115V, 230V or 115/230V
- Frequency 50/60Hz
- Series or Parallel Secondary
- Dielectric Strength – 4000 Vrms
- Insulation Class F (155°C)
- Flammability Rating – Bobbin/Shroud UL94V0 or 94H-B




## Agency Approvals:


- UL/cUL 5085-2 Recognized (File E47299)
- VDE Licensed (File 40001595)
- UL/cUL 5085-3 Class 2 Recognized (File E49606)
- Insulation File No. E95662

Class 2

**Mounting Style C**





**Mounting Style B**





Horizontal Mounting Available for Low Profile Applications

Single Primary




Dual Primary




● Indicates Like Polarity

Primaries and Secondaries are designed to be used simultaneously. That is, they must be used either series or parallel connected (as one winding). Same applies to secondaries also.

| VA Rating | Dimensions (Inches) | | | | | | | Weight lbs |
|---|---|---|---|---|---|---|---|---|
| | L | W | H | A | Mtg. Style | MC | WC | |
| 25 | 2.81 | 2.14 | 2.31 | 1.95 | C | 2.38 | - | 1.25 |
| 43 | 3.12 | 2.14 | 2.68 | 2.25 | C | 2.81 | - | 1.60 |
| 80 | 2.50 | 2.50 | 3.00 | - | B | 2.00 | 2.50 | 2.80 |
| 100 | 2.81 | 3.00 | 3.37 | - | B | 2.25 | 2.50 | 4.10 |
| 130 | 2.81 | 3.00 | 3.37 | - | B | 2.25 | 2.50 | 4.10 |
| 150 | 3.12 | 3.12 | 3.75 | - | B | 2.50 | 2.50 | 5.50 |
| 175 | 3.12 | 3.12 | 3.75 | - | B | 2.50 | 2.50 | 5.50 |

**Any application, Any requirement, Contact us for our Custom Designs**



Wabash Transformer
Sales Office:
300 W Factory Road, Addison IL 60101 ● Phone: (630) 628-9999 ● Fax: (630) 628-9922 ● www.wabashtransformer.com

## Series: VDE - Lead Wires

### Partial Selection Guide

All models are VDE approved

| VA | Part Number | | | Secondary | | Class 2 |
|---|---|---|---|---|---|---|
| | 115/230V | 115V | 230V | Series | Parallel | |
| 25 | VDE-25L-10 | VDE1-25L-10 | VDE2-25L-10 | 10VCT @ 2.50A | 5V @ 5.00A | ✓ |
| | VDE-25L-126 | VDE1-25L-126 | VDE2-25L-126 | 12.6VCT @ 1.98A | 6.3V @ 3.96A | ✓ |
| | VDE-25L-16 | VDE1-25L-16 | VDE2-25L-16 | 16VCT @ 1.56A | 8V @ 3.12A | ✓ |
| | VDE-25L-18 | VDE1-25L-18 | VDE2-25L-18 | 18VCT @ 1.39A | 9V @ 2.78A | ✓ |
| | VDE-25L-20 | VDE1-25L-20 | VDE2-25L-20 | 20VCT @ 1.25A | 10V @ 2.50A | ✓ |
| | VDE-25L-24 | VDE1-25L-24 | VDE2-25L-24 | 24VCT @ 1.04A | 12V @ 2.08A | ✓ |
| | VDE-25L-28 | VDE1-25L-28 | VDE2-25L-28 | 28VCT @ 892mA | 14V @ 1.78A | - |
| | VDE-25L-36 | VDE1-25L-36 | VDE2-25L-36 | 36VCT @ 694mA | 18V @ 1.38A | - |
| 43 | VDE-43L-10 | VDE1-43L-10 | VDE2-43L-10 | 10VCT @ 4.30A | 5V @ 8.60A | - |
| | VDE-43L-126 | VDE1-43L-126 | VDE2-43L-126 | 12.6VCT @ 3.41A | 6.3V @ 6.82A | ✓ |
| | VDE-43L-16 | VDE1-43L-16 | VDE2-43L-16 | 16VCT @ 2.68A | 8V @ 5.37A | ✓ |
| | VDE-43L-18 | VDE1-43L-18 | VDE2-43L-18 | 18VCT @ 2.38A | 9V @ 4.76A | ✓ |
| | VDE-43L-20 | VDE1-43L-20 | VDE2-43L-20 | 20VCT @ 2.15A | 10V @ 4.30A | ✓ |
| | VDE-43L-24 | VDE1-43L-24 | VDE2-43L-24 | 24VCT @ 1.79A | 12V @ 3.58A | - |
| | VDE-43L-28 | VDE1-43L-28 | VDE2-43L-28 | 28VCT @ 1.53A | 14V @ 3.06A | - |
| | VDE-43L-36 | VDE1-43L-36 | VDE2-43L-36 | 36VCT @ 1.19A | 18V @ 2.38A | - |
| | VDE-43L-230 | VDE1-43L-230 | VDE2-43L-230 | 230VCT @ 186mA | 115V @ 372mA | - |
| 80 | VDE-80L-10 | VDE1-80L-10 | VDE2-80L-10 | 10VCT @ 8.00A | 5V @ 16.00A | - |
| | VDE-80L-126 | VDE1-80L-126 | VDE2-80L-126 | 12.6VCT @ 6.34A | 6.3V @ 12.69A | - |
| | VDE-80L-16 | VDE1-80L-16 | VDE2-80L-16 | 16VCT @ 5.00A | 8V @ 10.00A | - |
| | VDE-80L-18 | VDE1-80L-18 | VDE2-80L-18 | 18VCT @ 4.44A | 9V @ 8.88A | - |
| | VDE-80L-20 | VDE1-80L-20 | VDE2-80L-20 | 20VCT @ 4.00A | 10V @ 8.00A | - |
| | VDE-80L-24 | VDE1-80L-24 | VDE2-80L-24 | 24VCT @ 3.33A | 12V @ 6.66A | - |
| | VDE-80L-28 | VDE1-80L-28 | VDE2-80L-28 | 28VCT @ 2.85A | 14V @ 5.70A | - |
| | VDE-80L-36 | VDE1-80L-36 | VDE2-80L-36 | 36VCT @ 2.22A | 18V @ 4.44A | - |
| | VDE-80L-230 | VDE1-80L-230 | VDE2-80L-230 | 230VCT @ 347mA | 115V @ 695mA | - |
| 100 | VDE-100L-10 | VDE1-100L-10 | VDE2-100L-10 | 10VCT @ 10.0A | 5V @ 20.00A | - |
| | VDE-100L-126 | VDE1-100L-126 | VDE2-100L-126 | 12.6VCT @ 7.93A | 6.3V @ 15.8A | - |
| | VDE-100L-16 | VDE1-100L-16 | VDE2-100L-16 | 16VCT @ 6.25A | 8V @ 12.50A | - |
| | VDE-100L-18 | VDE1-100L-18 | VDE2-100L-18 | 18VCT @ 5.55A | 9V @ 11.11A | - |
| | VDE-100L-20 | VDE1-100L-20 | VDE2-100L-20 | 20VCT @ 5.00A | 10V @ 10.00A | - |
| | VDE-100L-24 | VDE1-100L-24 | VDE2-100L-24 | 24VCT @ 4.16A | 12V @ 8.33A | - |
| | VDE-100L-28 | VDE1-100L-28 | VDE2-100L-28 | 28VCT @ 3.57A | 14V @ 7.14A | - |
| | VDE-100L-36 | VDE1-100L-36 | VDE2-100L-36 | 36VCT @ 2.77A | 18V @ 5.55A | - |
| | VDE-100L-230 | VDE1-100L-230 | VDE2-100L-230 | 230VCT @ 434mA | 115V @ 869mA | - |

Continued...

**Any application, Any requirement, Contact us for our Custom Designs**

## Series: VDE - Lead Wires

### Partial Selection Guide (Continued)

All models are VDE approved

| VA | Part Number | | | Secondary | |
|---|---|---|---|---|---|
| | 115/230V | 115V | 230V | Series | Parallel |
| 130 | VDE-130L-10 | VDE1-130L-10 | VDE2-130L-10 | 10VCT @ 13.00A | 5V @ 26.00A |
| | VDE-130L-126 | VDE1-130L-126 | VDE2-130L-126 | 12.6VCT @ 10.31A | 6.3V @ 20.63A |
| | VDE-130L-16 | VDE1-130L-16 | VDE2-130L-16 | 16VCT @ 8.125A | 8V @ 16.25A |
| | VDE-130L-18 | VDE1-130L-18 | VDE2-130L-18 | 18VCT @ 7.22A | 9V @ 14.44A |
| | VDE-130L-20 | VDE1-130L-20 | VDE2-130L-20 | 20VCT @ 6.50A | 10V @ 13.00A |
| | VDE-130L-24 | VDE1-130L-24 | VDE2-130L-24 | 24VCT @ 5.41A | 12V @ 10.83A |
| | VDE-130L-28 | VDE1-130L-28 | VDE2-130L-28 | 28VCT @ 4.64A | 14V @ 9.28A |
| | VDE-130L-36 | VDE1-130L-36 | VDE2-130L-36 | 36VCT @ 3.61A | 18V @ 7.22A |
| | VDE-130L-230 | VDE1-130L-230 | VDE2-130L-230 | 230VCT @ 565mA | 115V @ 1.13A |
| 150 | VDE-150L-10 | VDE1-150L-10 | VDE2-150L-10 | 10VCT @ 15.00A | 5V @ 30.00A |
| | VDE-150L-126 | VDE1-150L-126 | VDE2-150L-126 | 12.6VCT @ 11.90A | 6.3V @ 23.80A |
| | VDE-150L-16 | VDE1-150L-16 | VDE2-150L-16 | 16VCT @ 9.375A | 8V @ 18.75A |
| | VDE-150L-18 | VDE1-150L-18 | VDE2-150L-18 | 18VCT @ 8.33A | 9V @ 16.66A |
| | VDE-150L-20 | VDE1-150L-20 | VDE2-150L-20 | 20VCT @ 7.50A | 10V @ 15.00A |
| | VDE-150L-24 | VDE1-150L-24 | VDE2-150L-24 | 24VCT @ 6.25A | 12V @ 12.50A |
| | VDE-150L-28 | VDE1-150L-28 | VDE2-150L-28 | 28VCT @ 5.35A | 14V @ 10.71A |
| | VDE-150L-36 | VDE1-150L-36 | VDE2-150L-36 | 36VCT @ 4.16A | 18V @ 8.33A |
| | VDE-150L-230 | VDE1-150L-230 | VDE2-150L-230 | 230VCT @ 652mA | 115V @ 1.30A |
| 175 | VDE-175L-10 | VDE1-175L-10 | VDE2-175L-10 | 10VCT @ 17.50A | 5V @ 35.00A |
| | VDE-175L-126 | VDE1-175L-126 | VDE2-175L-126 | 12.6VCT @ 13.88A | 6.3V @ 27.77A |
| | VDE-175L-16 | VDE1-175L-16 | VDE2-175L-16 | 16VCT @ 10.93A | 8V @ 21.87A |
| | VDE-175L-18 | VDE1-175L-18 | VDE2-175L-18 | 20VCT @ 9.72A | 9V @ 19.44A |
| | VDE-175L-20 | VDE1-175L-20 | VDE2-175L-20 | 24VCT @ 8.75A | 10V @ 17.50A |
| | VDE-175L-24 | VDE1-175L-24 | VDE2-175L-24 | 24VCT @ 7.29A | 12V @ 14.58A |
| | VDE-175L-28 | VDE1-175L-28 | VDE2-175L-28 | 28VCT @ 6.25A | 14V @ 12.50A |
| | VDE-175L-36 | VDE1-175L-36 | VDE2-175L-36 | 36VCT @ 4.86A | 18V @ 9.72A |
| | VDE-175L-230 | VDE1-175L-230 | VDE2-175L-230 | 230VCT @ 760mA | 115V @ 1.52A |

**Any application, Any requirement, Contact us for our Custom Designs**

Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** sales@st-electron.ru

**Адрес:** 198099, Санкт-Петербург, Промышленная ул, дом № 19, литера Н, помещение 100-Н Офис 331