FEC15

SINGLE AND DUAL OUTPUT, HIGH DENSITY 15 WATTS DC/DC CONVERTERS



FEATURES

- *2:1 INPUT RANGE*
- *INCLUDE 3.3VDC OUTPUT*
- *SIX-SIDED SHIELD*
- *2 YEAR WARRANTY*
- *DELIVERS 15 WATTS AT 71˚C AMBIENT*
- *SMALL 1"X2" X0.375" PACKAGE*

SAFETIES / EMI

CE UL SA TUV

ELECTRICAL SPECIFICATIONS

All specifications are typical at nominal input, full load, and 25˚C unless otherwise noted.

INPUT SPECIFICATIONS

Input Voltage Range 12V nominal.....9 to 18V
24V nominal.....18 to 36V
48V nominal.....36 to 72V
Input Filter.....Pi Network

OUTPUT SPECIFICATIONS

Voltage Accuracy.....±1%
Ripple and Noise, 20 MHz BW
Single Output.....50mV P-P, 20mV RMS
Dual Output.....75mV P-P, 20mV RMS
Line Regulation, HL-LL.....±1.0%
Load Regulation, 100% to 10%.....±1.0% (Single)
±2.0% (Dual)
Temperature Coefficient.....±0.02%/˚C
Short Circuit Protection.....Continuous
Overvoltage Protection Threshold:
3.3V Output.....3.9V
5V Output.....6.2V
12V Output.....15V
15V Output.....18V
Transient Response Recovery Time,
25% Load Step Change.....500µsec

GENERAL SPECIFICATIONS

Switching Frequency.....500kHz, (Single) typ.
300kHz, (Dual) typ.
Isolation Voltage.....1600VDC, min
Isolation Resistance.....10˚Ohms , min

ENVIRONMENTAL SPECIFICATIONS


Operating Temperature Range.....-25˚C to +71˚C
Storage Temperature Range.....-55˚C to +125˚C
Cooling.....Free-air Convection
EMI/RFI.....Six-sided Continuous Shield
MTBF.....5.651×10^5 Hours
(MIL-HDBK-217F TA=25˚C Full Load)

PHYSICAL SPECIFICATIONS

Case Material.....Nickel-Coated Copper with Non-Conductive Base
Dimensions.....2.0x1.0x0.375 Inches (50.8x25.4x9.5 mm)


Series

MODEL NUMBER	INPUT RANGE	OUTPUT VOLTAGE	OUTPUT CURRENT	% typ. EFF
FEC15-12S33	9-18VDC	3.3VDC	4000mA	79
FEC15-12S05	9-18VDC	5VDC	3000mA	82
FEC15-12S12	9-18VDC	12VDC	1250mA	83
FEC15-12S15	9-18VDC	15VDC	1000mA	83
FEC15-12D05	9-18VDC	± 5VDC	±1500mA	82
FEC15-12D12	9-18VDC	±12VDC	± 635mA	85
FEC15-12D15	9-18VDC	±15VDC	± 500mA	85
FEC15-24S33	18-36VDC	3.3VDC	4000mA	80
FEC15-24S05	18-36VDC	5VDC	3000mA	83
FEC15-24S12	18-36VDC	12VDC	1250mA	84
FEC15-24S15	18-36VDC	15VDC	1000mA	84
FEC15-24D05	18-36VDC	± 5VDC	±1500mA	83
FEC15-24D12	18-36VDC	±12VDC	± 635mA	86
FEC15-24D15	18-36VDC	±15VDC	± 500mA	86
FEC15-48S33	36-72VDC	3.3VDC	4000mA	80
FEC15-48S05	36-72VDC	5VDC	3000mA	83
FEC15-48S12	36-72VDC	12VDC	1250mA	84
FEC15-48S15	36-72VDC	15VDC	1000mA	84
FEC15-48D05	36-72VDC	± 5VDC	±1500mA	83
FEC15-48D12	36-72VDC	±12VDC	± 635mA	86
FEC15-48D15	36-72VDC	±15VDC	± 500mA	86



ALL DIMENSIONS IN INCHES (mm)
PIN PITCH TOLERANCE ±0.5 mm

OPERATING TEMPERATURE LIMITS AND OUTPUT POWER RANGE



Pin Connections

Pin#	Single	Dual
1	+Vin	+Vin
2	-Vin	-Vin
3	+Vout	+Vout
4	No Pin	Common
5	-Vout	-Vout

Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург, Промышленная ул, дом № 19, литера Н, помещение 100-Н Офис 331