









1041125617	56
ORDER No.	Ckt

NEW RELEASED EC NO: KOR2013-0022 DRWN: JHCHANG 2012/08/16 CHKD: YSKIM02 APPR: YSKIM02 2012/08/31	DESCRIPTION	QUALITY SYMBOLS ▽=0 ◻=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION 			
				mm	INCH	DRAWN BY	DATE	TITLE 0.5MM FPC/FFC FRONTFLIP SLIM CONN. 56P (H=1.5) HOUSING ASS'Y				
			4 PLACES	± ---	± ---	JHCHANG	2012/08/16					
			3 PLACES	± 0.005	± ---	CHECKED BY	DATE	MOLEX MOLEX INCORPORATED				
			2 PLACES	± 0.05	± ---	KSKIM	2012/08/16					
			1 PLACE	± 0.1	± ---	APPROVED BY	DATE					
			ANGULAR ± 1 °		YSKIM02	2012/08/31	SHEET NO. 1 OF 3					
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		MATERIAL NO.		SEE TABLE								
A	REV	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION										



NOTES

1. MATERIAL

HOUSING ACTUATOR LCP GLASS FILLED,UL94V-0(NATURAL)
PPS GLASS FILLED,UL94V-0(BLACK)
(CHLORINE CONTROLLED MATERIAL)
TERMINAL PHOSPHOR BRONZE
FITTING NAIL PHOSPHOR BRONZE

2. PLATING

TERMINAL : SELECTIVE GOLD[Au] OVER NICKEL[Ni] PLATING.
CONTACT AREA : GOLD[Au] 0.1 MICROMETER MIN. OVER
NICKEL[Ni] 1.0 MICROMETER MIN.(UNDER PLATING)
SOLDER AREA : GOLD[Au] 0.05 MICROMETER MIN. OVER
NICKEL[Ni] 1.0 MICROMETER MIN.(UNDER PLATING)
FITTING NAIL : TIN[Sn] OVER NICKEL[Ni] PLATING.
Tin[Sn] 1~3 MICROMETER.
NICKEL[Ni] 1~3 MICROMETER (UNDER PLATING)

3. PRODUCT SPECIFICATION : PS-104112-001

4. ACTUATOR IS CLOSED IN THE EMBOSSED PACKING

5. FITTING NAIL FOR PREVENTION OF PEELING OF PCB PATTERN.

△ R0.3 MUST NOT BE OVERLAPPED TO PATTERN OF FPC.

7. N : CIRCUIT.

8. COPLANARITY IS 0.10MAX.

ABOUT FPC/FFC

RECOMMENDED PUNCHER DIRECTION : FROM CONDUCTOR SIDE TO STIFFENER FILM SIDE.
RECOMMENDED CONDUCTOR THICKNESS OF SOFT COPPER FOIL : 35 μ m OR 50 μ m.

ABOUT FPC




RECOMMENDED MATERIAL/THICKNESS.
STIFFENER FILM : POLYIMIDE
BONDING AGENT : THERMOSETTING BONDING AGENT
BASE FILM THICKNESS : 25 μ m
PLEASE PUT APPROPRIATE AMOUNT OF ADHESIVE ON THE CONTACT AREA BECAUSE THE EXTRA ADHESIVE MAY CAUSE THE DEFECT IN ELECTRICAL CONTINUITY.

ABOUT METAL MASK

RECOMMENDED METAL MASK THICKNESS : 0.121
RECOMMENDED METAL MASK OPEN RATIO : OVER 80%


NEW RELEASED EC NO: KOR2013-0022 DRWN: JHCHANG 2012/08/16 CHKD: APPR: YSKIM02 2012/08/31	DESCRIPTION KOR2013-0022	QUALITY SYMBOLS KOR2013-0022	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 5:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION			
			mm	INCH	DRAWN BY JHCHANG	DATE 2012/08/16	TITLE 0.5MM FPC/FFC FRONTFLIP SLIM CONN. 56P (H=1.5) HOUSING ASS'Y					
			4 PLACES ± ---	± ---	CHECKED BY KSKIM	DATE 2012/08/16						
			3 PLACES ± 0.005	± ---	APPROVED BY YSKIM02	DATE 2012/08/31						
			2 PLACES ± 0.05	± ---	MATERIAL NO. SEE SHEET 1		DOCUMENT NO. SD-104112-001				SHEET NO. 2 OF 3	
			1 PLACE ± 0.1	± ---								
			ANGULAR ± 1 °									
			DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS									
A	REV	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION										

10 9 8 7 6 5 4 3 2 1



NOTES

1. QUANTITY OF CONNECTORS : 3000PCS/REEL
2. LEAD LENGTH



3. THIS PRODUCT IS HALOGEN FREE (LV.2)

56	57.5	30.29	32.7	104112-5617	56
CARRIER TAPE WIDTH	C	(B)	(A)	ORDER No.	Ckt

NEW RELEASED EC NO: KOR2013-0022 DRWN: JHCHANG CHKD: APPR: YSKIM02	2012/08/16 2012/08/31	DESCRIPTION	QUALITY SYMBOLS ▽=0 ◇=0	GENERAL TOLERANCES (UNLESS SPECIFIED)				DIMENSION STYLE MM ONLY		SCALE 5:1	DESIGN UNITS METRIC	 THIRD ANGLE PROJECTION
								DRAWN BY JHCHANG	DATE 2012/08/16	TITLE 0.5MM FPC/FFC FRONTFLIP SLIM CONN. 56P (H=1.5) HOUSING ASS'Y		
								CHECKED BY KSKIM	DATE 2012/08/16			
								APPROVED BY YSKIM02	DATE 2012/08/31			
								MATERIAL NO.				
								SEE SHEET 1		SD-104112-001		
								SIZE A3		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		
								DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				

9 8 7 6 5 4 3 2 1



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331