

# 74HC4040; 74HCT4040

## 12-stage binary ripple counter

Rev. 03 — 14 September 2005

Product data sheet

## 1. General description

The 74HC4040; 74HCT4040 are high-speed Si-gate CMOS devices and are pin compatible with the HEF4040B series. They are specified in compliance with JEDEC standard no. 7A.

The 74HC4040; 74HCT4040 are 12-stage binary ripple counters with a clock input ( $\overline{CP}$ ), an overriding asynchronous master reset input (MR) and twelve parallel outputs (Q0 to Q11). The counter advances on the HIGH-to-LOW transition of  $\overline{CP}$ .

A HIGH on MR clears all counter stages and forces all outputs LOW, independent of the state of  $\overline{CP}$ .

Each counter stage is a static toggle flip-flop.

## 2. Features

- Multiple package options
- Complies with JEDEC standard no. 7A
- ESD protection:
  - ◆ HBM JESD22-A114-C exceeds 2000 V
  - ◆ MM JESD22-A115-A exceeds 200 V
- Specified from  $-40\text{ }^{\circ}\text{C}$  to  $+85\text{ }^{\circ}\text{C}$  and from  $-40\text{ }^{\circ}\text{C}$  to  $+125\text{ }^{\circ}\text{C}$

## 3. Applications

- Frequency dividing circuits
- Time delay circuits
- Control counters

## 4. Quick reference data

**Table 1: Quick reference data**  
 $GND = 0\text{ V}$ ;  $T_{amb} = 25\text{ }^{\circ}\text{C}$ ;  $t_r = t_f = 6\text{ ns}$ .

| Symbol                | Parameter             | Conditions                                   | Min | Typ | Max | Unit |
|-----------------------|-----------------------|----------------------------------------------|-----|-----|-----|------|
| <b>Type 74HC4040</b>  |                       |                                              |     |     |     |      |
| $t_{PHL}$ , $t_{PLH}$ | propagation delay     |                                              |     |     |     |      |
|                       | $\overline{CP}$ to Q0 | $C_L = 15\text{ pF}$ ; $V_{CC} = 5\text{ V}$ | -   | 14  | -   | ns   |
|                       | Qn to Qn+1            | $C_L = 15\text{ pF}$ ; $V_{CC} = 5\text{ V}$ | -   | 8   | -   | ns   |

**PHILIPS**

Table 1: Quick reference data ...continued

GND = 0 V;  $T_{amb} = 25\text{ }^{\circ}\text{C}$ ;  $t_r = t_f = 6\text{ ns}$ .

| Symbol    | Parameter                     | Conditions                                   | Min | Typ | Max | Unit |
|-----------|-------------------------------|----------------------------------------------|-----|-----|-----|------|
| $f_{max}$ | maximum operating frequency   | $C_L = 15\text{ pF}$ ; $V_{CC} = 5\text{ V}$ | -   | 90  | -   | MHz  |
| $C_i$     | input capacitance             |                                              | -   | 3.5 | -   | pF   |
| $C_{PD}$  | power dissipation capacitance | $V_I = \text{GND to } V_{CC}$                | -   | 20  | -   | pF   |

**Type 74HCT4040**

|                    |                               |                                              |   |     |   |     |
|--------------------|-------------------------------|----------------------------------------------|---|-----|---|-----|
| $t_{PHL}, t_{PLH}$ | propagation delay             |                                              |   |     |   |     |
|                    | $\overline{CP}$ to Q0         | $C_L = 15\text{ pF}$ ; $V_{CC} = 5\text{ V}$ | - | 16  | - | ns  |
|                    | Qn to Qn+1                    | $C_L = 15\text{ pF}$ ; $V_{CC} = 5\text{ V}$ | - | 8   | - | ns  |
| $f_{max}$          | maximum operating frequency   | $C_L = 15\text{ pF}$ ; $V_{CC} = 5\text{ V}$ | - | 79  | - | MHz |
| $C_i$              | input capacitance             |                                              | - | 3.5 | - | pF  |
| $C_{PD}$           | power dissipation capacitance | $V_I = \text{GND to } V_{CC} - 1.5\text{ V}$ | - | 20  | - | pF  |

[1]  $C_{PD}$  is used to determine the dynamic power dissipation ( $P_D$  in  $\mu\text{W}$ ): $P_D = C_{PD} \times V_{CC}^2 \times f_i + \Sigma(C_L \times V_{CC}^2 \times f_o)$  where: $f_i$  = input frequency in MHz; $f_o$  = output frequency in MHz; $\Sigma(C_L \times V_{CC}^2 \times f_o)$  = sum of outputs; $C_L$  = output load capacitance in pF; $V_{CC}$  = supply voltage in V.

## 5. Ordering information



Table 2: Ordering information


| Type number | Package           |          |                                                                                                                                                   |          |
|-------------|-------------------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------|----------|
|             | Temperature range | Name     | Description                                                                                                                                       | Version  |
| 74HC4040N   | -40 °C to +125 °C | DIP16    | plastic dual in-line package; 16 leads (300 mil); long body                                                                                       | SOT38-1  |
| 74HC4040D   | -40 °C to +125 °C | SO16     | plastic small outline package; 16 leads; body width 3.9 mm                                                                                        | SOT109-1 |
| 74HC4040DB  | -40 °C to +125 °C | SSOP16   | plastic shrink small outline package; 16 leads; body width 5.3 mm                                                                                 | SOT338-1 |
| 74HC4040PW  | -40 °C to +125 °C | TSSOP16  | plastic thin shrink small outline package; 16 leads; body width 4.4 mm                                                                            | SOT403-1 |
| 74HC4040BQ  | -40 °C to +125 °C | DHVQFN16 | plastic dual in-line compatible thermal enhanced very thin quad flat package; no leads; 16 terminals; body $2.5 \times 3.5 \times 0.85\text{ mm}$ | SOT763-1 |
| 74HCT4040N  | -40 °C to +125 °C | DIP16    | plastic dual in-line package; 16 leads (300 mil); long body                                                                                       | SOT38-1  |
| 74HCT4040D  | -40 °C to +125 °C | SO16     | plastic small outline package; 16 leads; body width 3.9 mm                                                                                        | SOT109-1 |

Table 2: Ordering information ...continued

| Type number | Package           |          |                                                                                                                                |          |
|-------------|-------------------|----------|--------------------------------------------------------------------------------------------------------------------------------|----------|
|             | Temperature range | Name     | Description                                                                                                                    | Version  |
| 74HCT4040DB | −40 °C to +125 °C | SSOP16   | plastic shrink small outline package; 16 leads; body width 5.3 mm                                                              | SOT338-1 |
| 74HCT4040PW | −40 °C to +125 °C | TSSOP16  | plastic thin shrink small outline package; 16 leads; body width 4.4 mm                                                         | SOT403-1 |
| 74HCT4040BQ | −40 °C to +125 °C | DHVQFN16 | plastic dual in-line compatible thermal enhanced very thin quad flat package; no leads; 16 terminals; body 2.5 × 3.5 × 0.85 mm | SOT763-1 |



6. Functional diagram





7. Pinning information

7.1 Pinning



## 7.2 Pin description

Table 3: Pin description

| Symbol                 | Pin | Description                               |
|------------------------|-----|-------------------------------------------|
| Q11                    | 1   | output 11                                 |
| Q5                     | 2   | output 5                                  |
| Q4                     | 3   | output 4                                  |
| Q6                     | 4   | output 6                                  |
| Q3                     | 5   | output 3                                  |
| Q2                     | 6   | output 2                                  |
| Q1                     | 7   | output 1                                  |
| GND                    | 8   | ground (0 V)                              |
| Q0                     | 9   | output 0                                  |
| $\overline{\text{CP}}$ | 10  | clock input (HIGH-to-LOW, edge-triggered) |
| MR                     | 11  | master reset input (active HIGH)          |
| Q8                     | 12  | output 8                                  |
| Q7                     | 13  | output 7                                  |
| Q9                     | 14  | output 9                                  |
| Q10                    | 15  | output 10                                 |
| V <sub>CC</sub>        | 16  | positive supply voltage                   |

## 8. Functional description


### 8.1 Function table

Table 4: Function table

| Input |    | Output    |
|-------|----|-----------|
| CP    | MR | Q0 to Q11 |
| ↑     | L  | no change |
| ↓     | L  | count     |
| X     | H  | L         |

- [1] H = HIGH voltage level;  
 L = LOW voltage level;  
 X = don't care;  
 ↑ = LOW-to-HIGH clock transition;  
 ↓ = HIGH-to-LOW clock transition.

## 8.2 Timing diagram



## 9. Limiting values

**Table 5: Limiting values**

In accordance with the Absolute Maximum Rating System (IEC 60134). Voltages are referenced to GND (ground = 0 V).

| Symbol    | Parameter                                   | Conditions                                             | Min  | Max      | Unit |
|-----------|---------------------------------------------|--------------------------------------------------------|------|----------|------|
| $V_{CC}$  | supply voltage                              |                                                        | -0.5 | +7       | V    |
| $I_{IK}$  | input diode current                         | $V_I < -0.5\text{ V}$ or $V_I > V_{CC} + 0.5\text{ V}$ | -    | $\pm 20$ | mA   |
| $I_{OK}$  | output diode current                        | $V_I < -0.5\text{ V}$ or $V_I > V_{CC} + 0.5\text{ V}$ | -    | $\pm 20$ | mA   |
| $I_O$     | output source or sink current               | $-0.5\text{ V} < V_O < V_{CC} + 0.5\text{ V}$          | -    | $\pm 25$ | mA   |
| $I_{CC}$  | quiescent supply current                    |                                                        | -    | $\pm 50$ | mA   |
| $I_{GND}$ | ground current                              |                                                        | -    | $\pm 50$ | mA   |
| $T_{stg}$ | storage temperature                         |                                                        | -65  | +150     | °C   |
| $P_{tot}$ | power dissipation                           | $T_{amb} = -40\text{ °C to }+125\text{ °C}$            | [1]  |          |      |
|           | DIP16 package                               |                                                        | -    | 750      | mW   |
|           | SO16, SSOP16, TSSOP16 and DHVQFN16 packages |                                                        | -    | 500      | mW   |

- [1] For DIP16 packages: above 70 °C,  $P_{tot}$  derates linearly with 12 mW/K.  
For SO16, SSOP16, TSSOP16 and DHVQFN16 packages, above 70 °C,  $P_{tot}$  derates linearly with 8 mW/K.

## 10. Recommended operating conditions

Table 6: Recommended operating conditions

| Symbol                | Parameter                 | Conditions                                                       | Min | Typ | Max      | Unit |
|-----------------------|---------------------------|------------------------------------------------------------------|-----|-----|----------|------|
| <b>type 74HC4040</b>  |                           |                                                                  |     |     |          |      |
| $V_{CC}$              | supply voltage            |                                                                  | 2.0 | 5.0 | 6.0      | V    |
| $V_I$                 | input voltage             |                                                                  | 0   | -   | $V_{CC}$ | V    |
| $V_O$                 | output voltage            |                                                                  | 0   | -   | $V_{CC}$ | V    |
| $T_{amb}$             | ambient temperature       | see <a href="#">Section 11</a> and <a href="#">12</a> per device | -40 | -   | +125     | °C   |
| $t_r, t_f$            | input rise and fall times | except for Schmitt-trigger inputs                                |     |     |          |      |
|                       |                           | $V_{CC} = 2.0\text{ V}$                                          | -   | -   | 1000     | ns   |
|                       |                           | $V_{CC} = 4.5\text{ V}$                                          | -   | 6.0 | 500      | ns   |
|                       |                           | $V_{CC} = 6.0\text{ V}$                                          | -   | -   | 400      | ns   |
| <b>type 74HCT4040</b> |                           |                                                                  |     |     |          |      |
| $V_{CC}$              | supply voltage            |                                                                  | 4.5 | 5.0 | 5.5      | V    |
| $V_I$                 | input voltage             |                                                                  | 0   | -   | $V_{CC}$ | V    |
| $V_O$                 | output voltage            |                                                                  | 0   | -   | $V_{CC}$ | V    |
| $T_{amb}$             | ambient temperature       | see <a href="#">Section 11</a> and <a href="#">12</a> per device | -40 | -   | +125     | °C   |
| $t_r, t_f$            | input rise and fall times | except for Schmitt-trigger inputs                                |     |     |          |      |
|                       |                           | $V_{CC} = 2.0\text{ V}$                                          | -   | -   | -        | ns   |
|                       |                           | $V_{CC} = 4.5\text{ V}$                                          | -   | 6.0 | 500      | ns   |
|                       |                           | $V_{CC} = 6.0\text{ V}$                                          | -   | -   | -        | ns   |

## 11. Static characteristics

Table 7: Static characteristics for 74HC4040

Voltages are referenced to GND (ground = 0 V).

| Symbol                                     | Parameter                 | Conditions                                            | Min  | Typ  | Max  | Unit |
|--------------------------------------------|---------------------------|-------------------------------------------------------|------|------|------|------|
| <b><math>T_{amb} = 25\text{ °C}</math></b> |                           |                                                       |      |      |      |      |
| $V_{IH}$                                   | HIGH-level input voltage  | $V_{CC} = 2.0\text{ V}$                               | 1.5  | 1.2  | -    | V    |
|                                            |                           | $V_{CC} = 4.5\text{ V}$                               | 3.15 | 2.4  | -    | V    |
|                                            |                           | $V_{CC} = 6.0\text{ V}$                               | 4.2  | 3.2  | -    | V    |
| $V_{IL}$                                   | LOW-level input voltage   | $V_{CC} = 2.0\text{ V}$                               | -    | 0.8  | 0.5  | V    |
|                                            |                           | $V_{CC} = 4.5\text{ V}$                               | -    | 2.1  | 1.35 | V    |
|                                            |                           | $V_{CC} = 6.0\text{ V}$                               | -    | 2.8  | 1.8  | V    |
| $V_{OH}$                                   | HIGH-level output voltage | $V_I = V_{IH}$ or $V_{IL}$                            |      |      |      |      |
|                                            |                           | $I_O = -20\text{ }\mu\text{A}; V_{CC} = 2.0\text{ V}$ | 1.9  | 2.0  | -    | V    |
|                                            |                           | $I_O = -20\text{ }\mu\text{A}; V_{CC} = 4.5\text{ V}$ | 4.4  | 4.5  | -    | V    |
|                                            |                           | $I_O = -20\text{ }\mu\text{A}; V_{CC} = 6.0\text{ V}$ | 5.9  | 6.0  | -    | V    |
|                                            |                           | $I_O = -4.0\text{ mA}; V_{CC} = 4.5\text{ V}$         | 3.98 | 4.32 | -    | V    |
|                                            |                           | $I_O = -5.2\text{ mA}; V_{CC} = 6.0\text{ V}$         | 5.48 | 5.81 | -    | V    |

Table 7: Static characteristics for 74HC4040 ...continued

Voltages are referenced to GND (ground = 0 V).

| Symbol                                                                                 | Parameter                 | Conditions                                                         | Min  | Typ  | Max  | Unit          |
|----------------------------------------------------------------------------------------|---------------------------|--------------------------------------------------------------------|------|------|------|---------------|
| $V_{OL}$                                                                               | LOW-level output voltage  | $V_I = V_{IH}$ or $V_{IL}$                                         |      |      |      |               |
|                                                                                        |                           | $I_O = 20\ \mu\text{A}; V_{CC} = 2.0\ \text{V}$                    | -    | 0    | 0.1  | V             |
|                                                                                        |                           | $I_O = 20\ \mu\text{A}; V_{CC} = 4.5\ \text{V}$                    | -    | 0    | 0.1  | V             |
|                                                                                        |                           | $I_O = 20\ \mu\text{A}; V_{CC} = 6.0\ \text{V}$                    | -    | 0    | 0.1  | V             |
|                                                                                        |                           | $I_O = 4.0\ \text{mA}; V_{CC} = 4.5\ \text{V}$                     | -    | 0.15 | 0.26 | V             |
|                                                                                        |                           | $I_O = 5.2\ \text{mA}; V_{CC} = 6.0\ \text{V}$                     | -    | 0.16 | 0.26 | V             |
| $I_{LI}$                                                                               | input leakage current     | $V_I = V_{CC}$ or GND; $V_{CC} = 6.0\ \text{V}$                    | -    | -    | 0.1  | $\mu\text{A}$ |
| $I_{CC}$                                                                               | quiescent supply current  | $V_I = V_{CC}$ or GND; $I_O = 0\ \text{A}; V_{CC} = 6.0\ \text{V}$ | -    | -    | 8.0  | $\mu\text{A}$ |
| $C_I$                                                                                  | input capacitance         |                                                                    | -    | 3.5  | -    | pF            |
| <b><math>T_{amb} = -40\ ^\circ\text{C}</math> to <math>+85\ ^\circ\text{C}</math></b>  |                           |                                                                    |      |      |      |               |
| $V_{IH}$                                                                               | HIGH-level input voltage  | $V_{CC} = 2.0\ \text{V}$                                           | 1.5  | -    | -    | V             |
|                                                                                        |                           | $V_{CC} = 4.5\ \text{V}$                                           | 3.15 | -    | -    | V             |
|                                                                                        |                           | $V_{CC} = 6.0\ \text{V}$                                           | 4.2  | -    | -    | V             |
| $V_{IL}$                                                                               | LOW-level input voltage   | $V_{CC} = 2.0\ \text{V}$                                           | -    | -    | 0.5  | V             |
|                                                                                        |                           | $V_{CC} = 4.5\ \text{V}$                                           | -    | -    | 1.35 | V             |
|                                                                                        |                           | $V_{CC} = 6.0\ \text{V}$                                           | -    | -    | 1.8  | V             |
| $V_{OH}$                                                                               | HIGH-level output voltage | $V_I = V_{IH}$ or $V_{IL}$                                         |      |      |      |               |
|                                                                                        |                           | $I_O = -20\ \mu\text{A}; V_{CC} = 2.0\ \text{V}$                   | 1.9  | -    | -    | V             |
|                                                                                        |                           | $I_O = -20\ \mu\text{A}; V_{CC} = 4.5\ \text{V}$                   | 4.4  | -    | -    | V             |
|                                                                                        |                           | $I_O = -20\ \mu\text{A}; V_{CC} = 6.0\ \text{V}$                   | 5.9  | -    | -    | V             |
|                                                                                        |                           | $I_O = -4.0\ \text{mA}; V_{CC} = 4.5\ \text{V}$                    | 3.84 | -    | -    | V             |
|                                                                                        |                           | $I_O = -5.2\ \text{mA}; V_{CC} = 6.0\ \text{V};$                   | 5.34 | -    | -    | V             |
| $V_{OL}$                                                                               | LOW-level output voltage  | $V_I = V_{IH}$ or $V_{IL}$                                         |      |      |      |               |
|                                                                                        |                           | $I_O = 20\ \mu\text{A}; V_{CC} = 2.0\ \text{V}$                    | -    | -    | 0.1  | V             |
|                                                                                        |                           | $I_O = 20\ \mu\text{A}; V_{CC} = 4.5\ \text{V}$                    | -    | -    | 0.1  | V             |
|                                                                                        |                           | $I_O = 20\ \mu\text{A}; V_{CC} = 6.0\ \text{V}$                    | -    | -    | 0.1  | V             |
|                                                                                        |                           | $I_O = 4.0\ \text{mA}; V_{CC} = 4.5\ \text{V}$                     | -    | -    | 0.33 | V             |
|                                                                                        |                           | $I_O = 5.2\ \text{mA}; V_{CC} = 6.0\ \text{V}$                     | -    | -    | 0.33 | V             |
| $I_{LI}$                                                                               | input leakage current     | $V_I = V_{CC}$ or GND; $V_{CC} = 6.0\ \text{V}$                    | -    | -    | 1.0  | $\mu\text{A}$ |
| $I_{CC}$                                                                               | quiescent supply current  | $V_I = V_{CC}$ or GND; $I_O = 0\ \text{A}; V_{CC} = 6.0\ \text{V}$ | -    | -    | 80.0 | $\mu\text{A}$ |
| <b><math>T_{amb} = -40\ ^\circ\text{C}</math> to <math>+125\ ^\circ\text{C}</math></b> |                           |                                                                    |      |      |      |               |
| $V_{IH}$                                                                               | HIGH-level input voltage  | $V_{CC} = 2.0\ \text{V}$                                           | 1.5  | -    | -    | V             |
|                                                                                        |                           | $V_{CC} = 4.5\ \text{V}$                                           | 3.15 | -    | -    | V             |
|                                                                                        |                           | $V_{CC} = 6.0\ \text{V}$                                           | 4.2  | -    | -    | V             |
| $V_{IL}$                                                                               | LOW-level input voltage   | $V_{CC} = 2.0\ \text{V}$                                           | -    | -    | 0.5  | V             |
|                                                                                        |                           | $V_{CC} = 4.5\ \text{V}$                                           | -    | -    | 1.35 | V             |
|                                                                                        |                           | $V_{CC} = 6.0\ \text{V}$                                           | -    | -    | 1.8  | V             |

**Table 7: Static characteristics for 74HC4040 ...continued**

Voltages are referenced to GND (ground = 0 V).

| Symbol          | Parameter                 | Conditions                                                                                | Min | Typ | Max   | Unit |
|-----------------|---------------------------|-------------------------------------------------------------------------------------------|-----|-----|-------|------|
| V <sub>OH</sub> | HIGH-level output voltage | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub>                                       |     |     |       |      |
|                 |                           | I <sub>O</sub> = -20 µA; V <sub>CC</sub> = 2.0 V                                          | 1.9 | -   | -     | V    |
|                 |                           | I <sub>O</sub> = -20 µA; V <sub>CC</sub> = 4.5 V                                          | 4.4 | -   | -     | V    |
|                 |                           | I <sub>O</sub> = -20 µA; V <sub>CC</sub> = 6.0 V                                          | 5.9 | -   | -     | V    |
|                 |                           | I <sub>O</sub> = -4.0 mA; V <sub>CC</sub> = 4.5 V                                         | 3.7 | -   | -     | V    |
|                 |                           | I <sub>O</sub> = -5.2 mA; V <sub>CC</sub> = 6.0 V;                                        | 5.2 | -   | -     | V    |
| V <sub>OL</sub> | LOW-level output voltage  | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub>                                       |     |     |       |      |
|                 |                           | I <sub>O</sub> = 20 µA; V <sub>CC</sub> = 2.0 V                                           | -   | -   | 0.1   | V    |
|                 |                           | I <sub>O</sub> = 20 µA; V <sub>CC</sub> = 4.5 V                                           | -   | -   | 0.1   | V    |
|                 |                           | I <sub>O</sub> = 20 µA; V <sub>CC</sub> = 6.0 V                                           | -   | -   | 0.1   | V    |
|                 |                           | I <sub>O</sub> = 4.0 mA; V <sub>CC</sub> = 4.5 V                                          | -   | -   | 0.4   | V    |
|                 |                           | I <sub>O</sub> = 5.2 mA; V <sub>CC</sub> = 6.0 V                                          | -   | -   | 0.4   | V    |
| I <sub>LI</sub> | input leakage current     | V <sub>I</sub> = V <sub>CC</sub> or GND; V <sub>CC</sub> = 6.0 V                          | -   | -   | 1.0   | µA   |
| I <sub>CC</sub> | quiescent supply current  | V <sub>I</sub> = V <sub>CC</sub> or GND; I <sub>O</sub> = 0 A;<br>V <sub>CC</sub> = 6.0 V | -   | -   | 160.0 | µA   |

**Table 8: Static characteristics for 74HCT4040**

Voltages are referenced to GND (ground = 0 V).

| Symbol                                    | Parameter                           | Conditions                                                                                       | Min  | Typ  | Max  | Unit |
|-------------------------------------------|-------------------------------------|--------------------------------------------------------------------------------------------------|------|------|------|------|
| <b>T<sub>amb</sub> = 25 °C</b>            |                                     |                                                                                                  |      |      |      |      |
| V <sub>IH</sub>                           | HIGH-level input voltage            | V <sub>CC</sub> = 4.5 V to 5.5 V                                                                 | 2.0  | 1.6  | -    | V    |
| V <sub>IL</sub>                           | LOW-level input voltage             | V <sub>CC</sub> = 4.5 V to 5.5 V                                                                 | -    | 1.2  | 0.8  | V    |
| V <sub>OH</sub>                           | HIGH-level output voltage           | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub>                                              |      |      |      |      |
|                                           |                                     | I <sub>O</sub> = -20 µA; V <sub>CC</sub> = 4.5 V                                                 | 4.4  | 4.5  | -    | V    |
|                                           |                                     | I <sub>O</sub> = -4.0 mA; V <sub>CC</sub> = 4.5 V                                                | 3.98 | 4.32 | -    | V    |
| V <sub>OL</sub>                           | LOW-level output voltage            | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub>                                              |      |      |      |      |
|                                           |                                     | I <sub>O</sub> = 20 µA; V <sub>CC</sub> = 4.5 V                                                  | -    | 0    | 0.1  | V    |
|                                           |                                     | I <sub>O</sub> = 4.0 mA; V <sub>CC</sub> = 4.5 V                                                 | -    | 0.15 | 0.26 | V    |
| I <sub>LI</sub>                           | input leakage current               | V <sub>I</sub> = V <sub>CC</sub> or GND; V <sub>CC</sub> = 5.5 V                                 | -    | -    | 0.1  | µA   |
| I <sub>CC</sub>                           | quiescent supply current            | V <sub>I</sub> = V <sub>CC</sub> or GND; I <sub>O</sub> = 0 A;<br>V <sub>CC</sub> = 5.5 V        | -    | -    | 8.0  | µA   |
| ΔI <sub>CC</sub>                          | additional quiescent supply current | V <sub>I</sub> = V <sub>CC</sub> - 2.1 V; V <sub>CC</sub> = 4.5 V to 5.5 V; I <sub>O</sub> = 0 A |      |      |      |      |
|                                           |                                     | $\overline{\text{CP}}$                                                                           | -    | 85   | 306  | µA   |
|                                           |                                     | MR                                                                                               | -    | 110  | 396  | µA   |
| C <sub>I</sub>                            | input capacitance                   |                                                                                                  | -    | 3.5  | -    | pF   |
| <b>T<sub>amb</sub> = -40 °C to +85 °C</b> |                                     |                                                                                                  |      |      |      |      |
| V <sub>IH</sub>                           | HIGH-level input voltage            | V <sub>CC</sub> = 4.5 V to 5.5 V                                                                 | 2.0  | -    | -    | V    |
| V <sub>IL</sub>                           | LOW-level input voltage             | V <sub>CC</sub> = 4.5 V to 5.5 V                                                                 | -    | -    | 0.8  | V    |

**Table 8: Static characteristics for 74HCT4040 ...continued**

Voltages are referenced to GND (ground = 0 V).

| Symbol                               | Parameter                           | Conditions                                                                                       | Min  | Typ | Max   | Unit |
|--------------------------------------|-------------------------------------|--------------------------------------------------------------------------------------------------|------|-----|-------|------|
| V <sub>OH</sub>                      | HIGH-level output voltage           | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub>                                              |      |     |       |      |
|                                      |                                     | I <sub>O</sub> = −20 μA; V <sub>CC</sub> = 4.5 V                                                 | 4.4  | -   | -     | V    |
|                                      |                                     | I <sub>O</sub> = −4.0 mA; V <sub>CC</sub> = 4.5 V                                                | 3.84 | -   | -     | V    |
| V <sub>OL</sub>                      | LOW-level output voltage            | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub>                                              |      |     |       |      |
|                                      |                                     | I <sub>O</sub> = 20 μA; V <sub>CC</sub> = 4.5 V                                                  | -    | -   | 0.1   | V    |
|                                      |                                     | I <sub>O</sub> = 4.0 mA; V <sub>CC</sub> = 4.5 V                                                 | -    | -   | 0.33  | V    |
| I <sub>LI</sub>                      | input leakage current               | V <sub>I</sub> = V <sub>CC</sub> or GND; V <sub>CC</sub> = 5.5 V                                 | -    | -   | 1.0   | μA   |
| I <sub>CC</sub>                      | quiescent supply current            | V <sub>I</sub> = V <sub>CC</sub> or GND; I <sub>O</sub> = 0 A; V <sub>CC</sub> = 5.5 V           | -    | -   | 80.0  | μA   |
| ΔI <sub>CC</sub>                     | additional quiescent supply current | V <sub>I</sub> = V <sub>CC</sub> − 2.1 V; V <sub>CC</sub> = 4.5 V to 5.5 V; I <sub>O</sub> = 0 A |      |     |       |      |
|                                      |                                     | $\overline{\text{CP}}$                                                                           | -    | -   | 383   | μA   |
|                                      |                                     | MR                                                                                               | -    | -   | 495   | μA   |
| T <sub>amb</sub> = −40 °C to +125 °C |                                     |                                                                                                  |      |     |       |      |
| V <sub>IH</sub>                      | HIGH-level input voltage            | V <sub>CC</sub> = 4.5 V to 5.5 V                                                                 | 2.0  | -   | -     | V    |
| V <sub>IL</sub>                      | LOW-level input voltage             | V <sub>CC</sub> = 4.5 V to 5.5 V                                                                 | -    | -   | 0.8   | V    |
| V <sub>OH</sub>                      | HIGH-level output voltage           | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub>                                              |      |     |       |      |
|                                      |                                     | I <sub>O</sub> = −20 μA; V <sub>CC</sub> = 4.5 V                                                 | 4.4  | -   | -     | V    |
|                                      |                                     | I <sub>O</sub> = −4.0 mA; V <sub>CC</sub> = 4.5 V                                                | 3.7  | -   | -     | V    |
| V <sub>OL</sub>                      | LOW-level output voltage            | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub>                                              |      |     |       |      |
|                                      |                                     | I <sub>O</sub> = 20 μA; V <sub>CC</sub> = 4.5 V                                                  | -    | -   | 0.1   | V    |
|                                      |                                     | I <sub>O</sub> = 4.0 mA; V <sub>CC</sub> = 4.5 V                                                 | -    | -   | 0.4   | V    |
| I <sub>LI</sub>                      | input leakage current               | V <sub>I</sub> = V <sub>CC</sub> or GND; V <sub>CC</sub> = 5.5 V                                 | -    | -   | 1.0   | μA   |
| I <sub>CC</sub>                      | quiescent supply current            | V <sub>I</sub> = V <sub>CC</sub> or GND; I <sub>O</sub> = 0 A; V <sub>CC</sub> = 5.5 V           | -    | -   | 160.0 | μA   |
| ΔI <sub>CC</sub>                     | additional quiescent supply current | V <sub>I</sub> = V <sub>CC</sub> − 2.1 V; V <sub>CC</sub> = 4.5 V to 5.5 V; I <sub>O</sub> = 0 A |      |     |       |      |
|                                      |                                     | $\overline{\text{CP}}$                                                                           | -    | -   | 417   | μA   |
|                                      |                                     | MR                                                                                               | -    | -   | 539   | μA   |

## 12. Dynamic characteristics

**Table 9:** Dynamic characteristics for type 74HC4040

$GND = 0\text{ V}$ ;  $t_r = t_f = 6\text{ ns}$ . For test circuit see [Figure 9](#).

| Symbol                   | Parameter                                  | Conditions                                     | Min | Typ | Max | Unit |
|--------------------------|--------------------------------------------|------------------------------------------------|-----|-----|-----|------|
| $T_{amb} = 25\text{ °C}$ |                                            |                                                |     |     |     |      |
| $t_{PHL}, t_{PLH}$       | propagation delay $\overline{CP}$ to $Q_0$ | see <a href="#">Figure 8</a>                   |     |     |     |      |
|                          |                                            | $V_{CC} = 2.0\text{ V}$ ; $C_L = 50\text{ pF}$ | -   | 47  | 150 | ns   |
|                          |                                            | $V_{CC} = 4.5\text{ V}$ ; $C_L = 50\text{ pF}$ | -   | 17  | 30  | ns   |
|                          |                                            | $V_{CC} = 5.0\text{ V}$ ; $C_L = 15\text{ pF}$ | -   | 14  | -   | ns   |
|                          |                                            | $V_{CC} = 6.0\text{ V}$ ; $C_L = 50\text{ pF}$ | -   | 14  | 26  | ns   |
|                          | propagation delay $Q_n$ to $Q_{n+1}$       | see <a href="#">Figure 8</a>                   |     |     |     |      |
|                          |                                            | $V_{CC} = 2.0\text{ V}$ ; $C_L = 50\text{ pF}$ | -   | 28  | 100 | ns   |
|                          |                                            | $V_{CC} = 4.5\text{ V}$ ; $C_L = 50\text{ pF}$ | -   | 10  | 20  | ns   |
|                          |                                            | $V_{CC} = 5.0\text{ V}$ ; $C_L = 15\text{ pF}$ | -   | 8   | -   | ns   |
| $t_{PHL}$                | propagation delay $MR$ to $Q_n$            | see <a href="#">Figure 8</a>                   |     |     |     |      |
|                          |                                            | $V_{CC} = 2.0\text{ V}$ ; $C_L = 50\text{ pF}$ | -   | 61  | 185 | ns   |
|                          |                                            | $V_{CC} = 4.5\text{ V}$ ; $C_L = 50\text{ pF}$ | -   | 22  | 37  | ns   |
|                          |                                            | $V_{CC} = 6.0\text{ V}$ ; $C_L = 50\text{ pF}$ | -   | 18  | 31  | ns   |
| $t_{THL}, t_{TLH}$       | output transition time                     | see <a href="#">Figure 8</a>                   |     |     |     |      |
|                          |                                            | $V_{CC} = 2.0\text{ V}$ ; $C_L = 50\text{ pF}$ | -   | 19  | 75  | ns   |
|                          |                                            | $V_{CC} = 4.5\text{ V}$ ; $C_L = 50\text{ pF}$ | -   | 7   | 15  | ns   |
|                          |                                            | $V_{CC} = 6.0\text{ V}$ ; $C_L = 50\text{ pF}$ | -   | 6   | 13  | ns   |
| $t_W$                    | clock pulse width HIGH or LOW              | see <a href="#">Figure 8</a>                   |     |     |     |      |
|                          |                                            | $V_{CC} = 2.0\text{ V}$ ; $C_L = 50\text{ pF}$ | 80  | 14  | -   | ns   |
|                          |                                            | $V_{CC} = 4.5\text{ V}$ ; $C_L = 50\text{ pF}$ | 16  | 5   | -   | ns   |
|                          |                                            | $V_{CC} = 6.0\text{ V}$ ; $C_L = 50\text{ pF}$ | 14  | 4   | -   | ns   |
|                          | master reset pulse width; HIGH             | see <a href="#">Figure 8</a>                   |     |     |     |      |
|                          |                                            | $V_{CC} = 2.0\text{ V}$ ; $C_L = 50\text{ pF}$ | 80  | 22  | -   | ns   |
|                          |                                            | $V_{CC} = 4.5\text{ V}$ ; $C_L = 50\text{ pF}$ | 16  | 8   | -   | ns   |
|                          |                                            | $V_{CC} = 6.0\text{ V}$ ; $C_L = 50\text{ pF}$ | 14  | 6   | -   | ns   |
| $t_{rec}$                | recovery time $MR$ to $\overline{CP}$      | see <a href="#">Figure 8</a>                   |     |     |     |      |
|                          |                                            | $V_{CC} = 2.0\text{ V}$ ; $C_L = 50\text{ pF}$ | 50  | 8   | -   | ns   |
|                          |                                            | $V_{CC} = 4.5\text{ V}$ ; $C_L = 50\text{ pF}$ | 10  | 3   | -   | ns   |
|                          |                                            | $V_{CC} = 6.0\text{ V}$ ; $C_L = 50\text{ pF}$ | 9   | 2   | -   | ns   |
| $f_{max}$                | maximum operating frequency                | see <a href="#">Figure 8</a>                   |     |     |     |      |
|                          |                                            | $V_{CC} = 2.0\text{ V}$ ; $C_L = 50\text{ pF}$ | 6.0 | 27  | -   | MHz  |
|                          |                                            | $V_{CC} = 4.5\text{ V}$ ; $C_L = 50\text{ pF}$ | 30  | 82  | -   | MHz  |
|                          |                                            | $V_{CC} = 5.0\text{ V}$ ; $C_L = 15\text{ pF}$ | -   | 90  | -   | MHz  |
|                          |                                            | $V_{CC} = 6.0\text{ V}$ ; $C_L = 50\text{ pF}$ | 35  | 98  | -   | MHz  |
| $C_{PD}$                 | power dissipation capacitance              |                                                | -   | 20  | -   | pF   |

Table 9: Dynamic characteristics for type 74HC4040 ...continued

GND = 0 V;  $t_r = t_f = 6$  ns. For test circuit see Figure 9.

| Symbol                                                                  | Parameter                                     | Conditions                                  | Min | Typ | Max | Unit |
|-------------------------------------------------------------------------|-----------------------------------------------|---------------------------------------------|-----|-----|-----|------|
| $T_{amb} = -40\text{ }^{\circ}\text{C to } +85\text{ }^{\circ}\text{C}$ |                                               |                                             |     |     |     |      |
| $t_{PHL}, t_{PLH}$                                                      | propagation delay $\overline{CP}$ to Q0       | see Figure 8                                |     |     |     |      |
|                                                                         |                                               | $V_{CC} = 2.0\text{ V}; C_L = 50\text{ pF}$ | -   | -   | 190 | ns   |
|                                                                         |                                               | $V_{CC} = 4.5\text{ V}; C_L = 50\text{ pF}$ | -   | -   | 38  | ns   |
|                                                                         |                                               | $V_{CC} = 6.0\text{ V}; C_L = 50\text{ pF}$ | -   | -   | 33  | ns   |
|                                                                         | propagation delay Qn to Qn+1                  | see Figure 8                                |     |     |     |      |
|                                                                         |                                               | $V_{CC} = 2.0\text{ V}; C_L = 50\text{ pF}$ | -   | -   | 125 | ns   |
|                                                                         |                                               | $V_{CC} = 4.5\text{ V}; C_L = 50\text{ pF}$ | -   | -   | 25  | ns   |
|                                                                         |                                               | $V_{CC} = 6.0\text{ V}; C_L = 50\text{ pF}$ | -   | -   | 21  | ns   |
|                                                                         | $t_{PHL}$ propagation delay MR to Qn          | see Figure 8                                |     |     |     |      |
|                                                                         |                                               | $V_{CC} = 2.0\text{ V}; C_L = 50\text{ pF}$ | -   | -   | 230 | ns   |
|                                                                         |                                               | $V_{CC} = 4.5\text{ V}; C_L = 50\text{ pF}$ | -   | -   | 46  | ns   |
|                                                                         |                                               | $V_{CC} = 6.0\text{ V}; C_L = 50\text{ pF}$ | -   | -   | 39  | ns   |
| $t_{THL}, t_{TLH}$                                                      | output transition time                        | see Figure 8                                |     |     |     |      |
|                                                                         |                                               | $V_{CC} = 2.0\text{ V}; C_L = 50\text{ pF}$ | -   | -   | 95  | ns   |
|                                                                         |                                               | $V_{CC} = 4.5\text{ V}; C_L = 50\text{ pF}$ | -   | -   | 19  | ns   |
|                                                                         |                                               | $V_{CC} = 6.0\text{ V}; C_L = 50\text{ pF}$ | -   | -   | 16  | ns   |
| $t_W$                                                                   | clock pulse width HIGH or LOW                 | see Figure 8                                |     |     |     |      |
|                                                                         |                                               | $V_{CC} = 2.0\text{ V}; C_L = 50\text{ pF}$ | 100 | -   | -   | ns   |
|                                                                         |                                               | $V_{CC} = 4.5\text{ V}; C_L = 50\text{ pF}$ | 20  | -   | -   | ns   |
|                                                                         |                                               | $V_{CC} = 6.0\text{ V}; C_L = 50\text{ pF}$ | 17  | -   | -   | ns   |
|                                                                         | master reset pulse width; HIGH                | see Figure 8                                |     |     |     |      |
|                                                                         |                                               | $V_{CC} = 2.0\text{ V}; C_L = 50\text{ pF}$ | 100 | -   | -   | ns   |
|                                                                         |                                               | $V_{CC} = 4.5\text{ V}; C_L = 50\text{ pF}$ | 20  | -   | -   | ns   |
|                                                                         |                                               | $V_{CC} = 6.0\text{ V}; C_L = 50\text{ pF}$ | 17  | -   | -   | ns   |
|                                                                         | $t_{rec}$ recovery time MR to $\overline{CP}$ | see Figure 8                                |     |     |     |      |
|                                                                         |                                               | $V_{CC} = 2.0\text{ V}; C_L = 50\text{ pF}$ | 65  | -   | -   | ns   |
|                                                                         |                                               | $V_{CC} = 4.5\text{ V}; C_L = 50\text{ pF}$ | 13  | -   | -   | ns   |
|                                                                         |                                               | $V_{CC} = 6.0\text{ V}; C_L = 50\text{ pF}$ | 11  | -   | -   | ns   |
| $f_{max}$                                                               | maximum operating frequency                   | see Figure 8                                |     |     |     |      |
|                                                                         |                                               | $V_{CC} = 2.0\text{ V}; C_L = 50\text{ pF}$ | 4.8 | -   | -   | MHz  |
|                                                                         |                                               | $V_{CC} = 4.5\text{ V}; C_L = 50\text{ pF}$ | 24  | -   | -   | MHz  |
|                                                                         |                                               | $V_{CC} = 6.0\text{ V}; C_L = 50\text{ pF}$ | 28  | -   | -   | MHz  |

Table 9: Dynamic characteristics for type 74HC4040 ...continued

GND = 0 V;  $t_r = t_f = 6$  ns. For test circuit see Figure 9.

| Symbol                                                                   | Parameter                                     | Conditions                                  | Min | Typ | Max | Unit |
|--------------------------------------------------------------------------|-----------------------------------------------|---------------------------------------------|-----|-----|-----|------|
| $T_{amb} = -40\text{ }^{\circ}\text{C to } +125\text{ }^{\circ}\text{C}$ |                                               |                                             |     |     |     |      |
| $t_{PHL}, t_{PLH}$                                                       | propagation delay $\overline{CP}$ to Q0       | see Figure 8                                |     |     |     |      |
|                                                                          |                                               | $V_{CC} = 2.0\text{ V}; C_L = 50\text{ pF}$ | -   | -   | 225 | ns   |
|                                                                          |                                               | $V_{CC} = 4.5\text{ V}; C_L = 50\text{ pF}$ | -   | -   | 45  | ns   |
|                                                                          |                                               | $V_{CC} = 6.0\text{ V}; C_L = 50\text{ pF}$ | -   | -   | 38  | ns   |
|                                                                          | propagation delay Qn to Qn+1                  | see Figure 8                                |     |     |     |      |
|                                                                          |                                               | $V_{CC} = 2.0\text{ V}; C_L = 50\text{ pF}$ | -   | -   | 150 | ns   |
|                                                                          |                                               | $V_{CC} = 4.5\text{ V}; C_L = 50\text{ pF}$ | -   | -   | 30  | ns   |
|                                                                          |                                               | $V_{CC} = 6.0\text{ V}; C_L = 50\text{ pF}$ | -   | -   | 26  | ns   |
|                                                                          | $t_{PHL}$ propagation delay MR to Qn          | see Figure 8                                |     |     |     |      |
|                                                                          |                                               | $V_{CC} = 2.0\text{ V}; C_L = 50\text{ pF}$ | -   | -   | 280 | ns   |
|                                                                          |                                               | $V_{CC} = 4.5\text{ V}; C_L = 50\text{ pF}$ | -   | -   | 56  | ns   |
|                                                                          |                                               | $V_{CC} = 6.0\text{ V}; C_L = 50\text{ pF}$ | -   | -   | 48  | ns   |
| $t_{THL}, t_{TLH}$                                                       | output transition time                        | see Figure 8                                |     |     |     |      |
|                                                                          |                                               | $V_{CC} = 2.0\text{ V}; C_L = 50\text{ pF}$ | -   | -   | 110 | ns   |
|                                                                          |                                               | $V_{CC} = 4.5\text{ V}; C_L = 50\text{ pF}$ | -   | -   | 22  | ns   |
|                                                                          |                                               | $V_{CC} = 6.0\text{ V}; C_L = 50\text{ pF}$ | -   | -   | 19  | ns   |
| $t_W$                                                                    | clock pulse width HIGH or LOW                 | see Figure 8                                |     |     |     |      |
|                                                                          |                                               | $V_{CC} = 2.0\text{ V}; C_L = 50\text{ pF}$ | 120 | -   | -   | ns   |
|                                                                          |                                               | $V_{CC} = 4.5\text{ V}; C_L = 50\text{ pF}$ | 24  | -   | -   | ns   |
|                                                                          |                                               | $V_{CC} = 6.0\text{ V}; C_L = 50\text{ pF}$ | 20  | -   | -   | ns   |
|                                                                          | master reset pulse width; HIGH                | see Figure 8                                |     |     |     |      |
|                                                                          |                                               | $V_{CC} = 2.0\text{ V}; C_L = 50\text{ pF}$ | 120 | -   | -   | ns   |
|                                                                          |                                               | $V_{CC} = 4.5\text{ V}; C_L = 50\text{ pF}$ | 24  | -   | -   | ns   |
|                                                                          |                                               | $V_{CC} = 6.0\text{ V}; C_L = 50\text{ pF}$ | 20  | -   | -   | ns   |
|                                                                          | $t_{rec}$ recovery time MR to $\overline{CP}$ | see Figure 8                                |     |     |     |      |
|                                                                          |                                               | $V_{CC} = 2.0\text{ V}; C_L = 50\text{ pF}$ | 75  | -   | -   | ns   |
|                                                                          |                                               | $V_{CC} = 4.5\text{ V}; C_L = 50\text{ pF}$ | 15  | -   | -   | ns   |
|                                                                          |                                               | $V_{CC} = 6.0\text{ V}; C_L = 50\text{ pF}$ | 13  | -   | -   | ns   |
| $f_{max}$                                                                | maximum operating frequency                   | see Figure 8                                |     |     |     |      |
|                                                                          |                                               | $V_{CC} = 2.0\text{ V}; C_L = 50\text{ pF}$ | 4.0 | -   | -   | MHz  |
|                                                                          |                                               | $V_{CC} = 4.5\text{ V}; C_L = 50\text{ pF}$ | 20  | -   | -   | MHz  |
|                                                                          |                                               | $V_{CC} = 6.0\text{ V}; C_L = 50\text{ pF}$ | 24  | -   | -   | MHz  |

[1]  $C_{PD}$  is used to determine the dynamic power dissipation ( $P_D$  in  $\mu\text{W}$ ): $P_D = C_{PD} \times V_{CC}^2 \times f_i + \sum(C_L \times V_{CC}^2 \times f_o)$  where: $f_i$  = input frequency in MHz; $f_o$  = output frequency in MHz; $\sum(C_L \times V_{CC}^2 \times f_o)$  = sum of outputs; $C_L$  = output load capacitance in pF; $V_{CC}$  = supply voltage in V.

**Table 10: Dynamic characteristics for type 74HCT4040***GND = 0 V;  $t_r = t_f = 6$  ns. For test circuit see Figure 9.*


| Symbol                                                        | Parameter                                 | Conditions                                                    | Min   | Typ | Max | Unit |
|---------------------------------------------------------------|-------------------------------------------|---------------------------------------------------------------|-------|-----|-----|------|
| <b><math>T_{amb} = 25\text{ °C}</math></b>                    |                                           |                                                               |       |     |     |      |
| $t_{PHL}, t_{PLH}$                                            | propagation delay $\overline{CP}$ to Q0   | see Figure 8                                                  |       |     |     |      |
|                                                               |                                           | $V_{CC} = 4.5\text{ V}; C_L = 50\text{ pF}$                   | -     | 19  | 40  | ns   |
|                                                               |                                           | $V_{CC} = 5.0\text{ V}; C_L = 15\text{ pF}$                   | -     | 16  | -   | ns   |
|                                                               | propagation delay Qn to Qn+1              | see Figure 8                                                  |       |     |     |      |
|                                                               |                                           | $V_{CC} = 4.5\text{ V}; C_L = 50\text{ pF}$                   | -     | 10  | 20  | ns   |
|                                                               |                                           | $V_{CC} = 5.0\text{ V}; C_L = 15\text{ pF}$                   | -     | 8   | -   | ns   |
| $t_{PHL}$                                                     | propagation delay MR to Qn                | $V_{CC} = 4.5\text{ V}; C_L = 50\text{ pF};$<br>see Figure 8; | -     | 23  | 45  | ns   |
| $t_{THL}, t_{TLH}$                                            | output transition time                    | $V_{CC} = 4.5\text{ V}; C_L = 50\text{ pF};$<br>see Figure 8; | -     | 7   | 15  | ns   |
| $t_W$                                                         | clock pulse width HIGH or LOW             | $V_{CC} = 4.5\text{ V}; C_L = 50\text{ pF};$<br>see Figure 8; | 16    | 7   | -   | ns   |
|                                                               | master reset pulse width; HIGH            | $V_{CC} = 4.5\text{ V}; C_L = 50\text{ pF};$<br>see Figure 8; | 16    | 6   | -   | ns   |
| $t_{rec}$                                                     | recovery time MR to $\overline{CP}$       | $V_{CC} = 4.5\text{ V}; C_L = 50\text{ pF};$<br>see Figure 8; | 10    | 2   | -   | ns   |
| $f_{max}$                                                     | maximum operating frequency               | see Figure 8                                                  |       |     |     |      |
|                                                               |                                           | $V_{CC} = 4.5\text{ V}; C_L = 50\text{ pF}$                   | 30    | 72  | -   | MHz  |
|                                                               |                                           | $V_{CC} = 5.0\text{ V}; C_L = 15\text{ pF}$                   | -     | 79  | -   | MHz  |
| $C_{PD}$                                                      | power dissipation capacitance per package |                                                               | [1] - | 20  | -   | pF   |
| <b><math>T_{amb} = -40\text{ °C to }+85\text{ °C}</math></b>  |                                           |                                                               |       |     |     |      |
| $t_{PHL}, t_{PLH}$                                            | propagation delay $\overline{CP}$ to Q0   | $V_{CC} = 4.5\text{ V}; C_L = 50\text{ pF};$<br>see Figure 8; | -     | -   | 50  | ns   |
|                                                               | propagation delay Qn to Qn+1              | $V_{CC} = 4.5\text{ V}; C_L = 50\text{ pF};$<br>see Figure 8; | -     | -   | 25  | ns   |
| $t_{PHL}$                                                     | propagation delay MR to Qn                | $V_{CC} = 4.5\text{ V}; C_L = 50\text{ pF};$<br>see Figure 8; | -     | -   | 56  | ns   |
| $t_{THL}, t_{TLH}$                                            | output transition time                    | $V_{CC} = 4.5\text{ V}; C_L = 50\text{ pF};$<br>see Figure 8; | -     | -   | 19  | ns   |
| $t_W$                                                         | clock pulse width HIGH or LOW             | $V_{CC} = 4.5\text{ V}; C_L = 50\text{ pF};$<br>see Figure 8; | 20    | -   | -   | ns   |
|                                                               | master reset pulse width; HIGH            | $V_{CC} = 4.5\text{ V}; C_L = 50\text{ pF};$<br>see Figure 8; | 20    | -   | -   | ns   |
| $t_{rec}$                                                     | recovery time MR to $\overline{CP}$       | $V_{CC} = 4.5\text{ V}; C_L = 50\text{ pF};$<br>see Figure 8; | 13    | -   | -   | ns   |
| $f_{max}$                                                     | maximum operating frequency               | $V_{CC} = 4.5\text{ V}; C_L = 50\text{ pF};$<br>see Figure 8; | 24    | -   | -   | MHz  |
| <b><math>T_{amb} = -40\text{ °C to }+125\text{ °C}</math></b> |                                           |                                                               |       |     |     |      |
| $t_{PHL}, t_{PLH}$                                            | propagation delay $\overline{CP}$ to Q0   | $V_{CC} = 4.5\text{ V}; C_L = 50\text{ pF};$<br>see Figure 8; | -     | -   | 60  | ns   |
|                                                               | propagation delay Qn to Qn+1              | $V_{CC} = 4.5\text{ V}; C_L = 50\text{ pF};$<br>see Figure 8  | -     | -   | 30  | ns   |


**Table 10: Dynamic characteristics for type 74HCT4040 ...continued**GND = 0 V;  $t_r = t_f = 6$  ns. For test circuit see [Figure 9](#).

| Symbol             | Parameter                           | Conditions                                                    | Min | Typ | Max | Unit |
|--------------------|-------------------------------------|---------------------------------------------------------------|-----|-----|-----|------|
| $t_{PHL}$          | propagation delay MR to Qn          | $V_{CC} = 4.5$ V; $C_L = 50$ pF; see <a href="#">Figure 8</a> | -   | -   | 68  | ns   |
| $t_{THL}, t_{TLH}$ | output transition time              | $V_{CC} = 4.5$ V; $C_L = 50$ pF; see <a href="#">Figure 8</a> | -   | -   | 22  | ns   |
| $t_W$              | clock pulse width HIGH or LOW       | $V_{CC} = 4.5$ V; $C_L = 50$ pF; see <a href="#">Figure 8</a> | 24  | -   | -   | ns   |
|                    | master reset pulse width; HIGH      | $V_{CC} = 4.5$ V; $C_L = 50$ pF; see <a href="#">Figure 8</a> | 24  | -   | -   | ns   |
| $t_{rec}$          | recovery time MR to $\overline{CP}$ | $V_{CC} = 4.5$ V; $C_L = 50$ pF; see <a href="#">Figure 8</a> | 15  | -   | -   | ns   |
| $f_{max}$          | maximum operating frequency         | $V_{CC} = 4.5$ V; $C_L = 50$ pF; see <a href="#">Figure 8</a> | 20  | -   | -   | MHz  |

[1]  $C_{PD}$  is used to determine the dynamic power dissipation ( $P_D$  in  $\mu$ W): $P_D = C_{PD} \times V_{CC}^2 \times f_i + \sum (C_L \times V_{CC}^2 \times f_o)$  where: $f_i$  = input frequency in MHz; $f_o$  = output frequency in MHz; $\sum (C_L \times V_{CC}^2 \times f_o)$  = sum of outputs; $C_L$  = output load capacitance in pF; $V_{CC}$  = supply voltage in V.

### 13. Waveforms

74HC4040:  $V_M = 50\%$ ;  $V_I = \text{GND to } V_{CC}$ .74HCT4040:  $V_M = 1.3$  V;  $V_I = \text{GND to } 3$  V.**Fig 8. Clock ( $\overline{CP}$ ) to output (Qn) propagation delays, clock pulse width, output transition times, maximum clock pulse frequency, master reset (MR) pulse width, master reset to output (Qn) propagation delays and master reset to clock ( $\overline{CP}$ ) removal time.**



Definitions for test circuit:

$C_L$  = load capacitance including jig and probe capacitance (See [Section 12](#) for the value).

$R_T$  = termination resistance should be equal to output impedance  $Z_O$  of the pulse generator.

**Fig 9. Test circuit**

14. Package outline

DIP16: plastic dual in-line package; 16 leads (300 mil); long body

SOT38-1





Fig 10. Package outline SOT38-1 (DIP16)

SO16: plastic small outline package; 16 leads; body width 3.9 mm

SOT109-1



DIMENSIONS (inch dimensions are derived from the original mm dimensions)

| UNIT   | A<br>max. | A <sub>1</sub> | A <sub>2</sub> | A <sub>3</sub> | b <sub>p</sub> | c                | D <sup>(1)</sup> | E <sup>(1)</sup> | e    | H <sub>E</sub> | L     | L <sub>p</sub> | Q              | v    | w    | y     | z <sup>(1)</sup> | θ        |
|--------|-----------|----------------|----------------|----------------|----------------|------------------|------------------|------------------|------|----------------|-------|----------------|----------------|------|------|-------|------------------|----------|
| mm     | 1.75      | 0.25<br>0.10   | 1.45<br>1.25   | 0.25           | 0.49<br>0.36   | 0.25<br>0.19     | 10.0<br>9.8      | 4.0<br>3.8       | 1.27 | 6.2<br>5.8     | 1.05  | 1.0<br>0.4     | 0.7<br>0.6     | 0.25 | 0.25 | 0.1   | 0.7<br>0.3       | 8°<br>0° |
| inches | 0.069     | 0.010<br>0.004 | 0.057<br>0.049 | 0.01           | 0.019<br>0.014 | 0.0100<br>0.0075 | 0.39<br>0.38     | 0.16<br>0.15     | 0.05 | 0.244<br>0.228 | 0.041 | 0.039<br>0.016 | 0.028<br>0.020 | 0.01 | 0.01 | 0.004 | 0.028<br>0.012   |          |


**Note**  
1. Plastic or metal protrusions of 0.15 mm (0.006 inch) maximum per side are not included.

| OUTLINE<br>VERSION | REFERENCES |        |       |  | EUROPEAN<br>PROJECTION | ISSUE DATE           |
|--------------------|------------|--------|-------|--|------------------------|----------------------|
|                    | IEC        | JEDEC  | JEITA |  |                        |                      |
| SOT109-1           | 076E07     | MS-012 |       |  |                        | 99-12-27<br>03-02-19 |

Fig 11. Package outline SOT109-1 (SO16)

SSOP16: plastic shrink small outline package; 16 leads; body width 5.3 mm

SOT338-1



TSSOP16: plastic thin shrink small outline package; 16 leads; body width 4.4 mm

SOT403-1




Fig 13. Package outline SOT403-1 (TSSOP16)

DHVQFN16: plastic dual in-line compatible thermal enhanced very thin quad flat package; no leads; 16 terminals; body 2.5 x 3.5 x 0.85 mm

SOT763-1




Fig 14. Package outline SOT763-1 (DHVQFN16)

## 15. Revision history

**Table 11: Revision history**

| Document ID                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Release date | Data sheet status     | Change notice | Doc. number | Supersedes         |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|-----------------------|---------------|-------------|--------------------|
| 74HC_HCT4040_3                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 20050914     | Product data sheet    | -             | -           | 74HC_HCT4040_CNV_2 |
| Modifications:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |              |                       |               |             |                    |
| <ul style="list-style-type: none"><li>• The format of this data sheet has been redesigned to comply with the new presentation and information standard of Philips Semiconductors</li><li>• Reference to family specifications is replaced by the actual information: <a href="#">Section 5 "Ordering information"</a>, <a href="#">Section 7 "Pinning information"</a>, <a href="#">Section 9 "Limiting values"</a>, <a href="#">Section 10 "Recommended operating conditions"</a>, <a href="#">Section 11 "Static characteristics"</a>, <a href="#">Figure 9 "Test circuit"</a></li><li>• <a href="#">Section 14 "Package outline"</a> (DHVQFN16) added</li></ul> |              |                       |               |             |                    |
| 74HC_HCT4040_CNV_2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 19901231     | Product specification | -             | -           | -                  |

## 16. Data sheet status

| Level | Data sheet status <sup>[1]</sup> | Product status <sup>[2] [3]</sup> | Definition                                                                                                                                                                                                                                                                                     |
|-------|----------------------------------|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| I     | Objective data                   | Development                       | This data sheet contains data from the objective specification for product development. Philips Semiconductors reserves the right to change the specification in any manner without notice.                                                                                                    |
| II    | Preliminary data                 | Qualification                     | This data sheet contains data from the preliminary specification. Supplementary data will be published at a later date. Philips Semiconductors reserves the right to change the specification without notice, in order to improve the design and supply the best possible product.             |
| III   | Product data                     | Production                        | This data sheet contains data from the product specification. Philips Semiconductors reserves the right to make changes at any time in order to improve the design, manufacturing and supply. Relevant changes will be communicated via a Customer Product/Process Change Notification (CPCN). |

[1] Please consult the most recently issued data sheet before initiating or completing a design.

[2] The product status of the device(s) described in this data sheet may have changed since this data sheet was published. The latest information is available on the Internet at URL <http://www.semiconductors.philips.com>.

[3] For data sheets describing multiple type numbers, the highest-level product status determines the data sheet status.

## 17. Definitions

**Short-form specification** — The data in a short-form specification is extracted from a full data sheet with the same type number and title. For detailed information see the relevant data sheet or data handbook.

**Limiting values definition** — Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 60134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.

**Application information** — Applications that are described herein for any of these products are for illustrative purposes only. Philips Semiconductors make no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips Semiconductors for any damages resulting from such application.

**Right to make changes** — Philips Semiconductors reserves the right to make changes in the products - including circuits, standard cells, and/or software - described or contained herein in order to improve design and/or performance. When the product is in full production (status 'Production'), relevant changes will be communicated via a Customer Product/Process Change Notification (CPCN). Philips Semiconductors assumes no responsibility or liability for the use of any of these products, conveys no license or title under any patent, copyright, or mask work right to these products, and makes no representations or warranties that these products are free from patent, copyright, or mask work right infringement, unless otherwise specified.

## 19. Trademarks

**Notice** — All referenced brands, product names, service names and trademarks are the property of their respective owners.

## 18. Disclaimers

**Life support** — These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips Semiconductors

## 20. Contact information

For additional information, please visit: <http://www.semiconductors.philips.com>

For sales office addresses, send an email to: [sales.addresses@www.semiconductors.philips.com](mailto:sales.addresses@www.semiconductors.philips.com)



21. Contents

1 General description . . . . . 1

2 Features . . . . . 1

3 Applications . . . . . 1

4 Quick reference data . . . . . 1

5 Ordering information . . . . . 2

6 Functional diagram . . . . . 3

7 Pinning information . . . . . 4

7.1 Pinning . . . . . 4

7.2 Pin description . . . . . 5

8 Functional description . . . . . 5

8.1 Function table . . . . . 5

8.2 Timing diagram . . . . . 6

9 Limiting values . . . . . 6

10 Recommended operating conditions . . . . . 7

11 Static characteristics . . . . . 7

12 Dynamic characteristics . . . . . 11

13 Waveforms . . . . . 15

14 Package outline . . . . . 17

15 Revision history . . . . . 22

16 Data sheet status . . . . . 23

17 Definitions . . . . . 23

18 Disclaimers . . . . . 23

19 Trademarks . . . . . 23

20 Contact information . . . . . 23





**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331