

FEATURES

- 6.95V Shunt Reference
- Guaranteed 0.5ppm/°C Temperature Coefficient
- Guaranteed 1Ω Maximum Dynamic Impedance
- Guaranteed 20μV_{RMS} Maximum Noise
- Guaranteed Initial Tolerance of 2%
- Wide Operating Current Range
- Available in 4-Lead TO-46 Metal Can

APPLICATIONS

- Precision Voltage Reference for Multimeters
- Calibration Equipment Voltage Standards
- Laboratory Measurement Equipment
- Industrial Monitor/Control Instruments
- High Accuracy Data Converters

DESCRIPTION


The [LM199/LM399](#) precision shunt reference features excellent temperature stability over a wide range of voltage, temperature and operating current conditions. A stabilizing heater is incorporated with the active Zener on a monolithic substrate which nearly eliminates changes in voltage with temperature. The subsurface Zener operates over a current range of 0.5mA to 10mA, and offers minimal noise and excellent long-term stability.

Ideal applications for the LM199/LM399 include digital voltmeters, precision calibration equipment, current sources and a variety of other precision low cost references. A 10V buffered reference application is shown below.


LT, LT, LTC, LTM, Linear Technology and the Linear logo are registered trademarks of Linear Technology Corporation. All other trademarks are the property of their respective owners.

TYPICAL APPLICATION

10V Buffered Reference



Reverse Voltage Change



LM199 TA01b

LM199/LM399


LM199A/LM399A

ABSOLUTE MAXIMUM RATINGS

(Note 1)

| | |
|--|----------------|
| Temperature Stabilizer | 40V |
| Reverse Breakdown Current..... | 20mA |
| Forward Current..... | 1mA |
| Reference to Substrate Voltage, V_{RS} (Note 2)..... | -0.1V |
| Operating Temperature Range | |
| LM199/LM199A (OBSOLETE)..... | -55°C to 125°C |
| LM399/LM399A | 0°C to 70°C |
| Storage Temperature Range | |
| LM199/LM199A (OBSOLETE)..... | -65°C to 150°C |
| LM399/LM399A | -65°C to 150°C |
| Lead Temperature (Soldering, 10 sec)..... | 300°C |

PIN CONFIGURATION



ORDER INFORMATION

| LEAD FREE FINISH | TAPE AND REEL | PART MARKING | PACKAGE DESCRIPTION | TEMPERATURE RANGE |
|------------------|------------------|--------------|------------------------|-------------------|
| LM399H | LM399H#TRPBF | LM399H | 4-Lead TO-46 Metal Can | 0°C to 70°C |
| LM399AH | LM399AH#TRPBF | LM399AH | 4-Lead TO-46 Metal Can | 0°C to 70°C |
| OBSOLETE PACKAGE | | | | |
| LM199H | LM199H#TRPBF | | 4-Lead TO-46 Metal Can | -55°C to 125°C |
| LM199AH | LM199AH#TRPBF | | 4-Lead TO-46 Metal Can | -55°C to 125°C |
| LM199AH-20 | LM199AH-20#TRPBF | | 4-Lead TO-46 Metal Can | -55°C to 125°C |
| LM399AH-20 | LM399AH-20#TRPBF | | 4-Lead TO-46 Metal Can | 0°C to 70°C |
| LM399AH-50 | LM399AH-50#TRPBF | | 4-Lead TO-46 Metal Can | 0°C to 70°C |

Consult LTC Marketing for parts specified with wider operating temperature ranges.

Consult LTC Marketing for information on nonstandard lead based finish parts.

For more information on lead free part marking, go to: <http://www.linear.com/leadfree/>

For more information on tape and reel specifications, go to: <http://www.linear.com/tapeandreel/>

ELECTRICAL CHARACTERISTICS

The ● denotes the specifications which apply over the full operating temperature range, otherwise specifications are at $T_A = 25^\circ\text{C}$. (Note 3)

| SYMBOL | PARAMETER | CONDITIONS | | LM199/LM199A | | | LM399/LM399A | | | UNITS |
|---|---|--|---|--------------|------|-----|--------------|------|-----|---------------|
| | | | | MIN | TYP | MAX | MIN | TYP | MAX | |
| V_Z | Reverse Breakdown Voltage | $0.5\text{mA} \leq I_R \leq 10\text{mA}$ | ● | 6.8 | 6.95 | 7.1 | 6.75 | 6.95 | 7.3 | V |
| ΔV_Z | Reverse Breakdown Voltage Change with Current | $0.5\text{mA} \leq I_R \leq 10\text{mA}$ | ● | | 6 | 9 | | 6 | 12 | mV |
| r_Z | Reverse Dynamic Impedance | $I_R = 1\text{mA}$ (Note 6) ($10\text{Hz} \leq f \leq 100\text{Hz}$) | ● | | 0.5 | 1 | | 0.5 | 1.5 | Ω |
| $\frac{\Delta V_Z}{\Delta \text{Temp}}$ | Temperature Coefficient LM199/LM399 | $-55^\circ\text{C} \leq T_A \leq 85^\circ\text{C}$ | | | 0.3 | 1 | | | | ppm/°C |
| | | $85^\circ\text{C} \leq T_A \leq 125^\circ\text{C}$ | | | 5 | 15 | | | | ppm/°C |
| | LM199A/LM399A | $0^\circ\text{C} \leq T_A \leq 70^\circ\text{C}$ | | | | | 0.3 | 2 | | ppm/°C |
| | | $-55^\circ\text{C} \leq T_A \leq 85^\circ\text{C}$ | | | 0.2 | 0.5 | | | | ppm/°C |
| | | $85^\circ\text{C} \leq T_A \leq 125^\circ\text{C}$ | | | 5 | 10 | | | | ppm/°C |
| | | $0^\circ\text{C} \leq T_A \leq 70^\circ\text{C}$ | | | | | 0.3 | 1 | | ppm/°C |
| e_n | RMS Noise | $10\text{Hz} \leq f \leq 10\text{kHz}$ | ● | | 7 | 20 | | 7 | 50 | μV |

199399fc

ELECTRICAL CHARACTERISTICS The ● denotes the specifications which apply over the full operating temperature range, otherwise specifications are at $T_A = 25^\circ\text{C}$. (Note 3)

| SYMBOL | PARAMETER | CONDITIONS | LM199/LM199A | | | LM399/LM399A | | | UNITS |
|---|---------------------------------------|--|--------------|-----------|----------|--------------|-----------|----------|-------------------------|
| | | | MIN | TYP | MAX | MIN | TYP | MAX | |
| $\frac{\Delta V_Z}{\Delta \text{Time}}$ | Long-Term Stability | Stabilized, $22^\circ\text{C} \leq T_A \leq 28^\circ\text{C}$, 1000 Hours, $I_R = 1\text{mA} \pm 0.1\%$ | | 8 | (Note 4) | | 8 | (Note 4) | ppm/ $\sqrt{\text{kH}}$ |
| I_H | Temperature Stabilizer Supply Current | $T_A = 25^\circ\text{C}$, Still Air, $V_H = 30\text{V}$ $T_A = -55^\circ\text{C}$ (Note 5) | | 8.5 22 | 14 28 | | 8.5 15 | | mA |
| V_H | Temperature Stabilizer Supply Voltage | | ● | 9 | 40 | | 9 | 40 | V |
| | Warm-Up Time to $\pm 0.05\% V_Z$ | $V_H = 30\text{V}$ | | 3 | | | 3 | | Seconds |
| | Initial Turn-On Current | $9\text{V} \leq V_H \leq 40\text{V}$ (Note 5) | | 140 | 200 | | 140 | 200 | mA |

Note 1: Stresses beyond those listed under Absolute Maximum Ratings may cause permanent damage to the device. Exposure to any Absolute Maximum Rating condition for extended periods may affect device reliability and lifetime.

Note 2: The substrate is electrically connected to the negative terminal of the temperature stabilizer. The voltage that can be applied to either terminal of the reference is 40V more positive or 0.1V more negative than the substrate.




Note 3: These specifications apply for 30V applied to the temperature stabilizer and $-55^\circ\text{C} \leq T_A \leq 125^\circ\text{C}$ for the LM199; and $0^\circ\text{C} \leq T_A \leq 70^\circ\text{C}$ for the LM399.

Note 4: Devices with maximum guaranteed long-term stability of 20ppm/ $\sqrt{\text{kH}}$ are available. Drift decreases with time.


Note 5: This initial current can be reduced by adding an appropriate resistor and capacitor to the heater circuit. See the Typical Performance Characteristics graphs to determine values.

Note 6: Guaranteed by "Reverse Breakdown Change with Current."


TYPICAL PERFORMANCE CHARACTERISTICS




TYPICAL PERFORMANCE CHARACTERISTICS




LM199 G04




LM199 G05




LM199 G06



LM199 G07




LM199 G08




HEATER MUST BE BYPASSED WITH A 2μF OR LARGER TANTALUM CAPACITOR IF RESISTORS ARE USED

LM199 G09




LM199 G10




LM199 G11

FUNCTIONAL BLOCK DIAGRAM




TYPICAL APPLICATIONS


Single Supply Operation




Split Supply Operation



Negative Heater Supply with Positive Reference




Standard Cell Replacement




TYPICAL APPLICATIONS

Portable Calibrator




SCHEMATIC DIAGRAMS

Temperature Stabilizer




Reference



PACKAGE DESCRIPTION

Please refer to <http://www.linear.com/designtools/packaging/> for the most recent package drawings.


H Package
4-Lead TO-46 Metal Can
(Reference LTC DWG # 05-08-1341)



*LEAD DIAMETER IS UNCONTROLLED BETWEEN THE REFERENCE PLANE AND .050" BELOW THE REFERENCE PLANE

**FOR SOLDER DIP LEAD FINISH, LEAD DIAMETER IS $\frac{.016 - .024}{(0.406 - 0.610)}$

Thermal Shield* for TO-46, H Package



*THERMAL SHIELD MATERIAL IS VALOX

REVISION HISTORY (Revision history begins at Rev C)

| REV | DATE | DESCRIPTION | PAGE NUMBER |
|-----|-------|-------------------------------------|-------------|
| C | 12/14 | Package/Order Information updated | 2 |
| | | Thermal shield dimensions corrected | 7 |

LM199/LM399

LM199A/LM399A

RELATED PARTS

| PART NUMBER | DESCRIPTION | COMMENTS |
|------------------------------------|--|--|
| LT[®]1021 | Precision References for Series or Shunt Operation | Industry Standard Pinout, -40°C to 125°C |
| LT1389 | 1.25V, 2.5V, 4V and 5V Nanopower Shunt Reference | 800nA, 0.05% Accuracy, 10ppm/°C Drift |
| LT1634 | 1.25 and 2.5V Micropower Shunt Reference | 0.05%, 10ppm/°C, 10µA Current |
| LTZ1000 | 7V Ultra Precision, Stable Shunt Reference | 0.05ppm/°C, 1.2mV _{P-P} Noise |



Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331