

**TO - 92 BIPOLAR TRANSISTORS
TRANSISTOR(NPN)**

FEATURES


- * Power dissipation
P_{CM}: 625mW(T_{amb}=25°C)
- * Collector current
I_{CM}: 0.6 A
- * Collector-base voltage
V_{(BR)CBO}: 75 V
- * Operating and storage junction temperature range
T_J, T_{stg}: -55°C to +150°C

MECHANICAL DATA

- * Case: Molded plastic
- * Epoxy: UL 94V-O rate flame retardant
- * Lead: MIL-STD-202E method 208C guaranteed
- * Mounting position: Any
- * Weight: 0.008 gram

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.
Single phase, half wave, 60 Hz, resistive or inductive load.
For capacitive load, derate current by 20%.



MAXIMUM RATINGS (@ T_A = 25°C unless otherwise noted)

| RATINGS | SYMBOL | VALUE | UNITS |
|--|------------------|-------------|-------|
| Max. Steady State Power Dissipation ⁽¹⁾ @T _A =25°C Derate above 25°C | P _D | 625 | mW |
| Max. Operating Temperature Range | T _J | 150 | °C |
| Storage Temperature Range | T _{STG} | -55 to +150 | °C |

ELECTRICAL CHARACTERISTICS (@ T_A = 25°C unless otherwise noted)

| CHARACTERISTICS | SYMBOL | MIN. | TYP. | MAX. | UNITS |
|--|------------------|------|------|------|-------|
| Thermal Resistance Junction to Ambient | R _{θJA} | - | - | 200 | °C/W |

Notes : 1. Alumina=0.4*0.3*0.024in.99.5% alumina
2. "Fully ROHS Compliant", "100% Sn plating (Pb-free)".

ELECTRICAL CHARACTERISTICS (@TA=25°C unless otherwise noted)

| Chatacteristic | Symbol | Min | Max | Unit |
|----------------|--------|-----|-----|------|
|----------------|--------|-----|-----|------|

OFF CHARACTERISTICS

| | | | | |
|---|---------------|-----|------------|------|
| Collector-Emitter Breakdown Voltage ($I_C = 10\text{mA}$, $I_B = 0$) | $V_{(BR)CEO}$ | 40 | - | Vdc |
| Collector-Base Breakdown Voltage ($I_C = 10\text{uA}$, $I_E = 0$) | $V_{(BR)CBO}$ | 75 | - | Vdc |
| Emitter-Base Breakdown Voltage ($I_E = 10\text{uA}$, $I_C = 0$) | $V_{(BR)EBO}$ | 6.0 | - | Vdc |
| Collector Cutoff Current ($V_{CE} = 60\text{Vdc}$, $V_{EB(off)} = 3.0\text{Vdc}$) | I_{CEX} | - | 0.01 | uAdc |
| Collector Cutoff Current ($V_{CB} = 60\text{Vdc}$, $I_E = 0$) ($V_{CB} = 60\text{Vdc}$, $I_E = 0$, $T_A = 150^\circ\text{C}$) | I_{CBO} | - | 0.01 10 | uAdc |
| Emitter Cutoff Current ($V_{EB} = 3.0\text{Vdc}$, $I_C = 0$) | I_{EBO} | - | 0.01 | uAdc |
| Base Cutoff Current ($V_{CE} = 60\text{Vdc}$, $V_{EB(off)} = 3.0\text{Vdc}$) | I_{BL} | - | 20 | nAdc |

ON CHARACTERISTICS

| | | | | |
|---|---------------|----------|------------|-----|
| DC Current Gain ($I_C = 10\text{mA}$, $V_{CE} = 10\text{Vdc}$, $T_A = -55^\circ\text{C}$) ($I_C = 500\text{mA}$, $V_{CE} = 10\text{Vdc}$) (1) | hFE | 35 40 | - - | - |
| Collector-Emitter Saturation Voltage (1) ($I_C = 150\text{mA}$, $I_B = 15\text{mA}$) ($I_C = 500\text{mA}$, $I_B = 50\text{mA}$) | $V_{CE(sat)}$ | - - | 0.3 1.0 | Vdc |
| Base-Emitter Saturation Voltage (1) ($I_C = 150\text{mA}$, $I_B = 15\text{mA}$) ($I_C = 500\text{mA}$, $I_B = 50\text{mA}$) | $V_{BE(sat)}$ | 0.6 - | 1.2 2.0 | Vdc |

SMALL-SIGNAL CHARACTERISTICS

| | | | | |
|---|---------------|-------------|-------------|------------------|
| Current-Gain-Bandwidth Product (2) ($I_C = 20\text{mA}$, $V_{CE} = 20\text{Vdc}$, $f = 100\text{MHz}$) | f_T | 300 | - | MHz |
| Input Capacitance ($V_{EB} = 0.5\text{Vdc}$, $I_C = 0$, $f = 1.0\text{MHz}$) | C_{ibo} | - | 25 | pF |
| Input Impedance ($I_C = 1.0\text{mA}$, $V_{CE} = 10\text{Vdc}$, $f = 1.0\text{kHz}$) ($I_C = 10\text{mA}$, $V_{CE} = 10\text{Vdc}$, $f = 1.0\text{kHz}$) | h_{ie} | 2.0 0.25 | 8.0 1.25 | kohms |
| Voltage Feedback Ratio ($I_C = 1.0\text{mA}$, $V_{CE} = 10\text{Vdc}$, $f = 1.0\text{kHz}$) ($I_C = 10\text{mA}$, $V_{CE} = 10\text{Vdc}$, $f = 1.0\text{kHz}$) | h_{re} | - - | 8.0 4.0 | $\times 10^{-4}$ |
| Small-Signal Current Gain ($I_C = 1.0\text{mA}$, $V_{CE} = 10\text{Vdc}$, $f = 1.0\text{kHz}$) ($I_C = 10\text{mA}$, $V_{CE} = 10\text{Vdc}$, $f = 1.0\text{kHz}$) | h_{fe} | 50 75 | 300 375 | - |
| Output Admittance ($I_C = 1.0\text{mA}$, $V_{CE} = 10\text{Vdc}$, $f = 1.0\text{kHz}$) ($I_C = 10\text{mA}$, $V_{CE} = 10\text{Vdc}$, $f = 1.0\text{kHz}$) | h_{oe} | 5.0 25 | 35 200 | umhos |
| Collector Base Time Constant ($I_E = 20\text{mA}$, $V_{CB} = 20\text{Vdc}$, $f = 31.8\text{MHz}$) | $\tau_{b,Cc}$ | - | 150 | ps |
| Noise Figure ($I_C = 100\text{uA}$, $V_{CE} = 10\text{Vdc}$, $R_S = 1.0\text{kohms}$, $f = 1.0\text{kHz}$) | NF | - | 4.0 | dB |

SWITCHING CHARACTERISTICS

| | | | | | |
|---------------------------|--|----------------|--------|-----------|----|
| Delay Time Rise Time | ($V_{CC} = 30\text{Vdc}$, $V_{BE(off)} = -0.5\text{Vdc}$, $I_C = 150\text{mA}$, $I_{B1} = 15\text{mA}$) | t_d t_r | - - | 10 25 | ns |
| Storage Time Fall Time | ($V_{CC} = 30\text{Vdc}$, $I_C = 150\text{mA}$, $I_{B1} = I_{B2} = 15\text{mA}$) | t_s t_f | - - | 225 60 | ns |

NOTES : 1. Pulse Test: Pulse Width ≤ 300ms, Duty Cycle ≤ 2.0%
2. f_T is defined as the frequency at which $|h_{fe}|$ extrapolates to unity

RATING AND CHARACTERISTICS CURVES (PN2222A)




Figure 1. DC Current Gain




Figure 2. Collector Saturation Region




Figure 3. Turn-On Time




Figure 4. Turn-Off Time

RATING AND CHARACTERISTICS CURVES (PN2222A)




Figure 5. Frequency Effects




Figure 6. Source Resistance Effects




Figure 7. Capacitances




Figure 8. Current-Gain Bandwidth Product




Figure 9. "On" Voltages




Figure 10. Temperature Coefficients

DISCLAIMER NOTICE

Rectron Inc reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. Rectron Inc or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on RECTRON data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. Rectron Inc does not assume any liability arising out of the application or use of any product or circuit.

Rectron products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of Rectron Inc. Customers using or selling Rectron components for use in such applications do so at their own risk and shall agree to fully indemnify Rectron Inc and its subsidiaries harmless against all claims, damages and expenditures.



Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331