89 Series

Metal-Mite® Aluminum Housed Axial Term. Wirewound, 1% Tolerance

The 89 Series is a high-performance axial type resistor. These molded-construction metal-housed resistors are available in higher power ratings than standard axial resistors and are better suited to withstanding vibration, shock and harsh environmental conditions.

The 89 Series Metal-Mite® resistors are aluminum housed to maintain high stability during operation and to permit secure mounting to chassis surfaces.

The metal housing also provides heat-sinking capabilities.

FEATURES

- High Stability: ±0.5% ΔR.
- High power to size ratio.
- Metal housing allows chassis mounting and provides heat sink capability.

As of September 2006, the 89 Series is no longer offered as Mil. Spec.

SPECIFICATIONS

Material

Housing: Metal, anodized aluminum.

Internal Coating: Silicone.

Core: Ceramic.

Terminals: Solder-coated axial.

Derating: Linearly from 100% @ +25°C to 0% @ +275°C.

Electrical

Tolerance: ±1% and ±5% (other tolerances available).


Power rating: Rating is based on chassis mounting area and temperature stability. Proper heat sink as follows: 5W and 10W units, 4" x 6" x 2" x .040" Aluminum chassis; 25W units, 5" x 7" x 2" x .040" Aluminum chassis; 50W units, 12" x 12" x .059" Aluminum panel.

Maximum ohmic values: See chart.

Overload: 5 times rated wattage for 5 seconds.

Temperature coefficient:
Under 1Ω: ±90 ppm/°C
1 to 9.99Ω: ±50 ppm/°C
10Ω and over: ±20 ppm/°C.

Dielectric withstanding voltage: 5W and 10W rating,1000 VAC; 25 and 50W ratings, 2250 VAC.



Series	Wattage	Ohms	Voltage
805	5	0.10-25K	210
810	10	0.10-50K	320
825	25	0.005-75K	520
850	50	0.005-100K	1170

Non-Inductive versions available. Insert "N" before tolerance code. Example: 850NF560

	5 watt	10 watt	25 watt	50 watt
Series (Industrial)	**805**	**810**	**825**	**850**
		Dimensions		
Dim. A (in. ±0.062 / mm ±1.57)	1.125 / 28.59	1.375 / 34.93	1.938 / 49.23	2.781 / 70.64
Dim. B (in. ±0.010 / mm ±0.25)	0.490 / 12.45	0.625 / 15.88	0.781 / 19.84	0.844 / 21.44
Dim. C (in. ±0.031 / mm ±0.79)	0.078 / 1.98	0.094 / 2.39	0.172 / 4.37	0.188 / 4.78
Dim. D (in. ±0.010 / mm ±0.25)	0.444 / 11.28	0.562 / 14.28	0.719 / 18.26	1.562 / 39.68
Dim. E (in. ±0.062 / mm ±1.57)	0.600 / 15.24	0.750 / 19.05	1.062 / 26.98	1.938 / 49.23
Dim. F (in. ±0.062 / mm ±1.57)	0.266 / 6.76	0.312 / 7.93	0.438 / 11.13	0.438 / 11.13
Dim. G (in. ±0.062 / mm ±1.57)	0.334 / 8.48	0.438 / 11.13	0.531 / 13.49	0.594 / 15.09
Dim. H (in. ±0.031 / mm ±0.79)	0.245 / 6.22	0.312 / 7.93	0.391 / 9.93	0.422 / 10.72
Dim. J (in. ±0.031 / mm ±0.79)	0.646 / 16.41	0.812 / 20.63	1.094 / 27.79	1.156 / 29.36
Dim. K (in. ±0.005 / mm ±0.13)	0.093 / 2.36	0.094 / 2.39	0.125 / 3.18	0.125 / 3.18
Dim. L (in. ±0.031 / mm ±0.79)	0.320 / 8.13	0.406 / 10.31	0.562 / 14.28	0.625 / 15.88
Dim. M (in. ±0.062 / mm ±1.57)	0.133 / 3.38	0.203 / 5.16	0.281 / 7.14	0.312 / 7.92
Dim. N (in. ±0.031 / mm ±0.79)	0.065 / 1.65	0.094 / 2.39	0.094 / 2.39	0.094 / 2.39
Dim. P (in. ±0.005 / mm ±0.13)	0.050 / 1.27	0.085 / 2.16	0.085 / 2.16	0.085 / 2.16
Q min AWG	16	12	12	12
Dim. R (in., min/mm, min)	0.085/ 2.16	0.140/ 3.56	0.140/ 3.56	0.140/ 3.56

ORDERING INFORMATION

Non-Inductive Winding
Optional (blank = std. winding)

805NF5R0E

Series
805 = 5 Watt
810 = 10 watt
825 = 25 watt
850 = 50 watt

Tolerance
F = 1%
J = 5%

Ohms
R005= 0.005Ω
R10 = 0.1Ω
1R0 = 1.0Ω
250 = 250Ω
1K0 = 1,000Ω
1K5 = 1,500Ω
25K = 25,000Ω

RoHS Compliant

STANDARD PART NUMBERS

Ohmic value	Part No. Prefix ➤ / Suffix ▼	Wattage 5 (805F)	10 (810F)	25 (825F)	50 (850F)
0.005	R005			✔	✔
0.010	R010			✔	✔
0.025	R025			✔	✔
0.1	R10			✔	✔
0.3	R30			✔	✤
0.5	R50			✔	✤
0.7	R70			✤	✤
1.0	1R0	✔	✔	✔	✔
1.5	1R5	✤	✔		
2.0	2R0	✤	✔	✔	✔
3.0	3R0	✔	✔	✔	✔
4.0	4R0	✤	✔		
5.0	5R0	✔	✔	✔	✔
10.0	10R	✔	✔	✔	✔
15.0	15R	✔	✔	✔	✔
20	20R	✔	✔		
25	25R	✔	✔	✔	✔
30	30R	✤	✤		
40	40R	✤	✔		
50	50R	✔	✔	✔	✔
75	75R	✔	✤	✔	✔
100	100	✔	✔	✔	✔
150	150	✔	✔	✔	✔
200	200	✤	✤	✔	✔
250	250	✔	✔	✔	✔
300	300	✔	✤		
400	400	✤	✤		
500	500	✔	✤	✔	✔
750	750	✤	✤	✔	✔
1,000	1K0	✤	✔	✔	✔
1,500	1K5	✔	✤	✤	✔
2,000	2K0	✔	✔	✤	✤
2,500	2K5	✔	✔		
3,000	3K0	✤	✔	✔	✤
3,500	3K5	✤	✤		
4,000	4K0	✔	✔		
4,500	4K5	✤	✤		
5,000	5K0	✔	✔	✔	✔
6,000	6K0	✤	✤		
10,000	10K	✔	✤	✔	✔
15,000	15K	✔	✔	✤	✤
20,000	20K	✤	✤		
25,000	25K	✔	✤	✤	✤
50,000	50K		✤		
75,000	75K			✤	
100,000	100K				✤

✔ = Standard values

✤ = Non-standard values subject to minimum handling charge per item

Shaded values involve very fine resistance wire and should not be used in critical applications without burn-in and/or thermal cycling.

Check product availability at **www.ohmite.com**

Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург, Промышленная ул, дом № 19, литера Н, помещение 100-Н Офис 331