

FEATURES

- **Guaranteed** $\pm 4\text{mV}$ Initial Accuracy LT1004-1.2
- **Guaranteed** $\pm 20\text{mV}$ Accuracy LT1004-2.5
- **Guaranteed** $10\mu\text{A}$ Operating Current
- **Guaranteed** Temperature Performance
- Operates up to 20mA
- Very Low Dynamic Impedance

APPLICATIONS

- Portable Meter References
- Portable Test Instruments
- Battery-Operated Systems
- Current Loop Instrumentation

DESCRIPTION

The LT[®]1004 Micropower Voltage Reference is a 2-terminal bandgap reference diode designed to provide high accuracy and excellent temperature characteristics at very low operating currents. Optimization of the key parameters in the design, processing and testing of the device results in accuracy specifications previously attainable only with selected units. Below is a distribution plot of reference voltage for a typical lot of LT1004-1.2. Virtually all of the units fall well within the prescribed limits of $\pm 4\text{mV}$.


The LT1004 is a pin-for-pin replacement for the LM185/LM385 series of references with improved accuracy specifications. More important, the LT1004 is an attractive device for use in systems where accuracy was previously obtained at the expense of power consumption and trimming.

For a low drift micropower reference with guaranteed temperature coefficient, see the LT1034 data sheet.


 LTC and LT are registered trademarks of Linear Technology Corporation.

TYPICAL APPLICATION

Micropower Cold Junction Compensation for Thermocouples



Typical Distribution of
Reference Voltage (LT1004-1.2)






ABSOLUTE MAXIMUM RATINGS

(Note 1)

Reverse Breakdown Current	30mA
Forward Current	10mA
Operating Temperature Range	
LT1004M	–55°C to 125°C
LT1004I	–40°C to 85°C
LT1004C	0°C to 70°C
Storage Temperature Range	–65°C to 150°C
Lead Temperature (Soldering, 10 sec.)	300°C

PACKAGE/ORDER INFORMATION

BOTTOM VIEW  H PACKAGE 2-LEAD TO-46 METAL CAN	ORDER PART NUMBER	
	LT1004MH-1.2 LT1004MH-2.5 LT1004CH-1.2 LT1004CH-2.5	
BOTTOM VIEW  Z PACKAGE 3-LEAD PLASTIC TO-92	LT1004CZ-1.2 LT1004CZ-2.5 LT1004IZ-1.2 LT1004IZ-2.5	
TOP VIEW  S8 PACKAGE 8-LEAD PLASTIC SO	LT1004CS8-1.2 LT1004CS8-2.5 LT1004IS8-1.2 LT1004IS8-2.5	
	S8 PART MARKING	
	0412	0425
	0412I	0425I

ELECTRICAL CHARACTERISTICS (Note 2)

SYMBOL	PARAMETER	CONDITIONS	LT1004-1.2			LT1004-2.5			UNITS
			MIN	TYP	MAX	MIN	TYP	MAX	
V _Z	Reverse Breakdown Voltage	I _R = 100μA	1.231	1.235	1.239	2.480	2.500	2.520	V
		LT1004M: –55°C ≤ T _A ≤ 125°C	● 1.220	1.230	1.245	2.460	2.500	2.535	V
		LT1004C: 0°C ≤ T _A ≤ 70°C	● 1.225	1.235	1.245	2.470	2.500	2.530	V
		LT1004I: –40°C ≤ T _A ≤ 85°C	● 1.220	1.230	1.245	2.460	2.500	2.530	V
$\frac{\Delta V_Z}{\Delta T_{\text{Temp}}}$	Average Temperature Coefficient	I _{MIN} ≤ I _R ≤ 20mA (Note 3)		50		50			ppm/°C
I _{MIN}	Minimum Operating Current		● 8	10		12	20		μA
$\frac{\Delta V_Z}{\Delta I_R}$	Reverse Breakdown Voltage Change with Current	I _{MIN} ≤ I _R ≤ 1mA			1.0			1.0	mV
					1.5			1.5	mV
		1mA ≤ I _R ≤ 20mA			10			10	mV
					20			20	mV
r _Z	Reverse Dynamic Impedance	I _R = 100μA		0.2	0.6	0.2	0.6		Ω
					1.5		1.5		Ω
e _n	Wide Band Noise (RMS)	I _R = 100μA 10Hz ≤ f ≤ 10kHz		60		120			μV
$\frac{\Delta V_Z}{\Delta T_{\text{Time}}}$	Long Term Stability	I _R = 100μA T _A = 25°C ± 0.1°C		20		20			ppm/kHr

The ● denotes the specifications which apply over the full operating temperature range.

Note 1: Absolute Maximum Ratings are those values beyond which the life of a device may be impaired.


Note 2: All specifications are for T_A = 25°C unless otherwise noted.

Note 3: Selected devices with guaranteed maximum temperature coefficient are available upon request.

For MIL-STD components, please refer to LTC 883C data sheet for test listing and parameters.


TYPICAL PERFORMANCE CHARACTERISTICS (1.2V)

Reverse Characteristics




1004 G01

Reverse Voltage Change




1004 G02

Forward Characteristics




1004 G11

Temperature Drift




1004 G04

Reverse Dynamic Impedance




1004 G05

Reverse Dynamic Impedance




1004 G06

Noise Voltage




1004 G07

Filtered Output Noise



1004 G08


Reponse Time



1004 G09


TYPICAL PERFORMANCE CHARACTERISTICS (2.5V)

Reverse Characteristics




1004 G10

Forward Characteristics




1004 G11

Temperature Drift




1004 G12

Reverse Dynamic Impedance




1004 G13

Reverse Dynamic Impedance




1004 G14

Noise Voltage




1004 G15

Filtered Output Noise



1004 G16


Reponse Time




1004 G17

TYPICAL APPLICATIONS


High Stability 5V Regulator




Variable Output Supply




Constant Gain Amplifier Over Temperature



Micropower 5V Reference




Lead Acid Low Battery Detector



$\dagger R1$ SETS TRIP POINT, $60.4k$ PER CELL FOR $1.8V/CELL$


Ground Referenced Current Source




* MAY BE INCREASED FOR SMALL OUTPUT CURRENTS

TYPICAL APPLICATIONS


VPP Generator for Eeproms — No Trim Required




1.2V Reference from 1.5V Battery




Micropower Reference from 9V Battery



2.5V Reference




Low Noise Reference




SCHEMATIC DIAGRAMS

LT1004-1.2




LT1004-2.5



PACKAGE DESCRIPTION

Dimensions in inches (millimeters) unless otherwise noted.


H Package
2-Lead and 3-Lead TO-46 Metal Can
(LTC DWG # 05-08-1340)




*LEAD DIAMETER IS UNCONTROLLED BETWEEN THE REFERENCE PLANE AND 0.045" BELOW THE REFERENCE PLANE

**FOR SOLDER DIP LEAD FINISH, LEAD DIAMETER IS 0.016 - 0.024 (0.406 - 0.610)

Z Package
3-Lead Plastic TO-92 (Similar to TO-226)
(LTC DWG # 05-08-1410)





S8 Package
8-Lead Plastic Small Outline (Narrow 0.150)
(LTC DWG # 05-08-1610)




*DIMENSION DOES NOT INCLUDE MOLD FLASH. MOLD FLASH SHALL NOT EXCEED 0.006" (0.152mm) PER SIDE

**DIMENSION DOES NOT INCLUDE INTERLEAD FLASH. INTERLEAD FLASH SHALL NOT EXCEED 0.010" (0.254mm) PER SIDE




TYPICAL APPLICATIONS

0°C to 100°C Linear Output Thermometer



Low Temperature Coefficient
2-Terminal Current Source



RELATED PARTS

PART NUMBER	DESCRIPTION	COMMENTS
LT1634	Micropower Precision Shunt Reference	10μA Operating Current, 10ppm/°C Maximum Drift, 0.05% Initial Accuracy
LT1460S3-2.5	Micropower Series Reference in SOT-23	100μA Operating Current, 20ppm/°C Maximum Drift, 0.2% Initial Accuracy



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331