



### HF RoHS PLED Series



#### Agency Approvals

| Agency | Agency File Number |
|--------|--------------------|
|        | E133083            |

#### Schematic Symbol



#### Description

PLED Series open LED protectors provide a switching electronic shunt path when an LED in an LED string fails as an open circuit. This ensures that the remaining string of LEDs will continue to function if a single LED does not.

PLED Series devices were designed to enable higher reliability in outdoor LED lighting applications such as street lighting, outdoor signage, aircraft runway lighting, roadside warning lights and other applications.

Compatible with one, two and three watt LEDs that have a nominal 3V forward characteristic, PLED Series devices are available in two surface mount packages, the DO-214 and the Quad Flat Pak No-lead (QFN). The QFN's low profile, chip scale package (CSP) is ideal for dense board applications.


#### Features & Benefits

- Fast switching
- Automatically resets after power cycle
- Available in low profile, small footprint QFN and Standard DO214AA packages
- Compatible with industrial lighting environments
- Compatible with PWM frequencies up to 30 kHz
- RoHS compliant and halogen-free

#### Electrical Characteristics (All parameters are measured at T=25°C unless otherwise noted)

| Part Number | Marking | V <sub>BR</sub><br>breakdown |     | V <sub>DRM</sub><br>breakdown | I <sub>H</sub> | I <sub>S</sub> | I <sub>T</sub> @V <sub>T</sub> | V <sub>T</sub> @ I <sub>T</sub> = 1<br>Amp | Critical rate of<br>rise dV/dt |
|-------------|---------|------------------------------|-----|-------------------------------|----------------|----------------|--------------------------------|--------------------------------------------|--------------------------------|
|             |         | Volts                        |     | Volts                         | mAmps          | mAmps          | Amps                           | Volts                                      | Volts                          |
|             |         | Min                          | Max | Min                           | Min            | Max            | Max                            | Max                                        | Max                            |
| PLED6Q12    | PL6     | 6                            | 16  | 6                             | 5              | 100            | 1.0                            | 1.2                                        | 250V/μs                        |
| PLED6S      | PL6     |                              |     |                               |                |                |                                |                                            |                                |
| PLED9Q12    | PL9     | 9                            | 18  | 9                             |                |                |                                |                                            |                                |
| PLED9S      | PL9     |                              |     |                               |                |                |                                |                                            |                                |
| PLED13Q12   | PL13    | 13                           | 26  | 13                            |                |                |                                |                                            |                                |
| PLED13S     | PL13    |                              |     |                               |                |                |                                |                                            |                                |
| PLED18Q12   | PL18    | 18                           | 33  | 18                            |                |                |                                |                                            |                                |
| PLED18S     | PL18    |                              |     |                               |                |                |                                |                                            |                                |

### Thermal Considerations

| Package                                                                           | Symbol          | Parameter                               | Value                                                                                               | Unit |
|-----------------------------------------------------------------------------------|-----------------|-----------------------------------------|-----------------------------------------------------------------------------------------------------|------|
|  | $T_J$           | Operating Junction Temperature Range    | -40 to +150                                                                                         | °C   |
|                                                                                   | $T_S$           | Storage Temperature Range               | -65 to +150                                                                                         | °C   |
|                                                                                   | $R_{\theta JA}$ | Thermal Resistance: Junction to Ambient | DO-214: 90 <sup>1</sup><br>DO-214: 40 <sup>2</sup><br>QFN: 120 <sup>1</sup><br>QFN: 60 <sup>3</sup> | °C/W |

Notes:

1) Standard FR-4 PCB with Copper Pads (Recommended Size)

2) Aluminum PCB

Thickness: 1.6mm

Grade: 1-2 W/mK Thermal Conductivity

Trace thickness: 2 oz

Insulation layer thickness: 215  $\mu$ m

Solder Pad Dimensions: 2.0mm x 2.8mm (Recommended Size)

3) Aluminum PCB

Thickness: 1.6mm


Grade: 1-2 W/mK Thermal Conductivity

Trace thickness: 2 oz


Insulation layer thickness: 60  $\mu$ m

Solder Pad Dimensions: 1.27mm x 2.54mm (Recommended Size)


### V-I Characteristics




### $V_{BR}$ vs. Junction Temperature




### Normalized DC Holding Current vs. Case Temperature




### LED Interference Test Circuit



### 6 LEDs in Series 50% Duty Cycle 10kHz




### 5 LEDs and 1 PLED in Series 50% Duty Cycle 10kHz




Note: These two graphs show the current magnitude through the LED string with and without the PLED included. There is no noticeable effect on the LED current magnitude when the PLED is included in the circuit as compared to the LED current magnitude when the PLED is not in the circuit. (The conversion factor for the test measurement in the graphs above is 10mA/mV for the Pearson coil measurement, therefore, the current magnitude in the first figure is 10mA\*8.9 = 89mA, while the second figure is 91mA.)

### PLED in the Off-State 10kHz



Channel 1: current through LEDs (318 mA)  
Channel 2: voltage across PLED device (4.5 V)


### PLED device zeners and then turns fully on 10kHz



Channel 1: current through LEDs (346 mA) and PLED device once it is fully turned on 2.5 µsec later  
Channel 2: voltage across PLED device (21.3 V before PLED crowbars with 2 V drop)

### Soldering Parameters

|                                                        |                                    |                         |
|--------------------------------------------------------|------------------------------------|-------------------------|
| Reflow Condition                                       |                                    | Pb – Free assembly      |
| Pre Heat                                               | - Temperature Min ( $T_{s(min)}$ ) | 150°C                   |
|                                                        | - Temperature Max ( $T_{s(max)}$ ) | 200°C                   |
|                                                        | - Time (min to max) ( $t_s$ )      | 60 – 180 secs           |
| Average ramp up rate (Liquidus Temp ( $T_L$ ) to peak) |                                    | 3°C/second max          |
| $T_{s(max)}$ to $T_L$ - Ramp-up Rate                   |                                    | 3°C/second max          |
| Reflow                                                 | - Temperature ( $T_L$ ) (Liquidus) | 217°C                   |
|                                                        | - Temperature ( $t_L$ )            | 60 – 150 seconds        |
| Peak Temperature ( $T_p$ )                             |                                    | 260 <sup>+0/-5</sup> °C |
| Time within 5°C of actual peak Temperature ( $t_p$ )   |                                    | 30 seconds              |
| Ramp-down Rate                                         |                                    | 6°C/second max          |
| Time 25°C to peak Temperature ( $T_p$ )                |                                    | 8 minutes max           |
| Do not exceed                                          |                                    | 260°C                   |




### Physical Specifications

|                          |                                                               |
|--------------------------|---------------------------------------------------------------|
| <b>Terminal Material</b> | Copper Alloy                                                  |
| <b>Terminal Finish</b>   | 100% Matte Tin Plated                                         |
| <b>Body Material</b>     | UL recognized epoxy meeting flammability classification 94V-0 |

### Environmental Specifications


|                                          |                                                                                         |
|------------------------------------------|-----------------------------------------------------------------------------------------|
| <b>High Temperature Voltage Blocking</b> | MIL-STD-750: Method 1040, Condition A<br>80% min $V_{DRM}$ (VAC-peak), 150°C, 504 hours |
| <b>Temperature Cycling</b>               | MIL-STD-750: Method 1051<br>-65°C to 150°C, 15-minute dwell, 100 cycles                 |
| <b>Biased Temperature &amp; Humidity</b> | EIA/JEDEC: JESD22-A101<br>52VDC, 85°C, 85%RH, 1008 hours                                |
| <b>High Temperature Storage</b>          | MIL-STD-750: Method 1031<br>150°C, 1008 hours                                           |
| <b>Low Temperature Storage</b>           | -65°C, 1008 hours                                                                       |
| <b>Thermal Shock</b>                     | MIL-STD-750: Method 1056<br>0°C to 100°C, 5-minute dwell, 10-second transfer, 10 cycles |
| <b>Resistance to Solder Heat</b>         | MIL-STD-750: Method 2031<br>260°C, 10 seconds                                           |

### Dimensions - QFN (3x3) Package




| Dimensions | Inches |       |       | Millimeters |       |       |
|------------|--------|-------|-------|-------------|-------|-------|
|            | Min    | Typ   | Max   | Min         | Typ   | Max   |
| A          | 0.114  | 0.118 | 0.122 | 2.900       | 3.000 | 3.100 |
| B          | 0.114  | 0.118 | 0.122 | 2.900       | 3.000 | 3.100 |
| C          | 0.075  | 0.079 | 0.083 | 1.900       | 2.000 | 2.100 |
| E          | 0.011  | 0.015 | 0.019 | 0.285       | 0.385 | 0.485 |
| F          | 0.076  | 0.080 | 0.084 | 1.930       | 2.030 | 2.130 |
| H          | 0.035  | 0.039 | 0.043 | 0.900       | 1.000 | 1.100 |
| J          | 0.000  | 0.004 | 0.008 | 0.000       | 0.100 | 0.200 |
| K1         | 0.004  | 0.008 | 0.012 | 0.100       | 0.200 | 0.300 |
| K2         | 0.004  | 0.008 | 0.012 | 0.100       | 0.200 | 0.300 |
| M1         | 0.056  | 0.060 | 0.064 | 1.143       | 1.530 | 1.630 |
| M2         | 0.038  | 0.042 | 0.046 | 0.970       | 1.070 | 1.170 |
| N1         | 0.096  | 0.100 | 0.104 | 2.440       | 2.540 | 2.640 |
| N2         | 0.082  | 0.086 | 0.090 | 2.080       | 2.180 | 2.280 |

### Dimensions - DO-214 AA Package




| Dimensions | Inches |       | Millimeters |      |
|------------|--------|-------|-------------|------|
|            | Min    | Max   | Min         | Max  |
| A          | 0.130  | 0.156 | 3.30        | 3.95 |
| B          | 0.201  | 0.220 | 5.10        | 5.60 |
| C          | 0.077  | 0.087 | 1.95        | 2.20 |
| D          | 0.159  | 0.181 | 4.05        | 4.60 |
| E          | 0.030  | 0.063 | 0.75        | 1.60 |
| F          | 0.075  | 0.096 | 1.90        | 2.45 |
| G          | 0.002  | 0.008 | 0.05        | 0.20 |
| H          | 0.077  | 0.104 | 1.95        | 2.65 |
| K          | 0.006  | 0.016 | 0.15        | 0.41 |

### Part Numbering System




### Part Marking System

DO-214






QFN



### Packaging

| Package | Description | Packaging Quantity | Industry Standard |
|---------|-------------|--------------------|-------------------|
| Q12     | QFN 3x3     | 5000               | EIA-481-1         |
| S       | DO-214      | 2500               | EIA-481-1         |


### Tape and Reel Specification - QFN (3x3)



| Symbols | Description                  | Inches  |         | Millimeters |         |
|---------|------------------------------|---------|---------|-------------|---------|
|         |                              | Minimum | Maximum | Minimum     | Maximum |
| A       | Reel Diameter                | N/A     | 12.992  | N/A         | 330.0   |
| B       | Drive Spoke Width            | 0.059   | N/A     | 1.50        | N/A     |
| C       | Arbor Hole Diameter          | 0.504   | 0.531   | 12.80       | 13.50   |
| D       | Drive Spoke Diameter         | 0.795   | N/A     | 20.20       | N/A     |
| N       | Hub Diameter                 | 1.969   | N/A     | 50.00       | N/A     |
| W1      | Reel Inner Width at Hub      | 0.488   | 0.567   | 12.40       | 14.40   |
| A0      | Pocket Width at bottom       | 0.126   | 0.134   | 3.20        | 3.40    |
| B0      | Pocket Length at bottom      | 0.126   | 0.134   | 3.20        | 3.40    |
| D0      | Feed Hole Diameter           | 0.059   | 0.063   | 1.50        | 1.60    |
| D1      | Pocket Hole Diameter         | 0.059   | N/A     | 1.50        | N/A     |
| E1      | Feed hole Position 1         | 0.065   | 0.073   | 1.65        | 1.85    |
| E2      | Feed hole Position 2         | 0.400   | 0.408   | 10.15       | 10.35   |
| F       | Feed hole center-Pocket hole | 0.215   | 0.219   | 5.45        | 5.55    |
| K0      | Pocket Depth                 | 0.039   | 0.051   | 1.00        | 1.30    |
| P0      | Feed hole Pitch              | 0.153   | 0.161   | 3.90        | 4.10    |
| P1      | Component Spacing            | 0.311   | 0.319   | 7.90        | 8.10    |
| P2      | Feed hole center-Pocket hole | 0.077   | 0.081   | 1.90        | 2.06    |
| T       | Carrier Tape Thickness       | 0.010   | 0.014   | 0.25        | 0.35    |
| W       | Embossed Carrier Tape Width  | 0.453   | 0.484   | 11.50       | 12.30   |
| W0      | Cover Tape Width             | 0.358   | 0.366   | 9.10        | 9.30    |

**DO-214 Embossed Carrier Reel Pack (RP)**

**Meets all EIA-481-1 Standards**





**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331