482 Series Alarm Indicating Fuseholder

The Alarm Indicating Fuseholder is designed for use with the Littelfuse 481 Alarm Fuse. It is designed to accept other manufacturer's replacement fuses as well.

• Ideal for telecommunications and control panel circuits.

The fuseholder is available in three versions:

PCB Mount: Can be soldered directly to a printed circuit board. Rated up to 15 amperes. Available in single pole or gangable up to 20 poles. Fuseholder is keyed to prevent insertion of 20 ampere fuse.

Panel Mount – 20A: Available in a single pole version rated up to 20 amperes. Large leads for wire attachment.

Panel Mount – 15A: 15 ampere gangable version of fuseholder is keyed to prevent insertion of 20 ampere fuse.

AGENCY APPROVALS: Recognized under the Components Program of Underwriters Laboratories and the Components Acceptance Program of CSA.

AGENCY FILE NUMBERS: UL E14721, CSA LR 29862

SPECIFICATIONS:

PCB Mount and Panel Mount – 15A: Rated at 15 amperes up to 125 VAC/VDC

Body Material: Thermoplastic

Fuse Terminals: Tin-plated Beryllium Copper

Alarm Terminal: Tin-plated Brass

Operating Temperature: -55°C to + 125°C


Panel Mount – 20A: Rated at 20 amperes up to 125 VAC/VDC


Body Material: Black Phenolic

Fuse Terminals: Tin-plated Beryllium Copper

Alarm Terminal: Tin-plated Brass

Operating Temperature: -40°C to + 85°C






5 POLE HOLDER ASSEMBLY
WITH FLUSH OPTION

482 Series PCB Mount Fuseholder

PCB Mount – 15A: 15 ampere gangable version of fuseholder is keyed to prevent insertion of 20 ampere fuse. Please contact Littelfuse for ordering information.




ORDERING INFORMATION: PCB Mount

Catalog Number PCB Mount	Catalog Number PCB Mount Flush	Type	Length (A)
0482 0001ZXB	**0482** 0001ZXBF	1 Pole	6.40mm (.25")
0482 0002ZXB	**0482** 0002ZXBF	2 Pole	12.80mm (.50")
0482 0003ZXB	**0482** 0003ZXBF	3 Pole	19.05mm (.75")
0482 0004ZXB	**0482** 0004ZXBF	4 Pole	25.40mm (1.0")
0482 0005ZXB	**0482** 0005ZXBF	5 Pole	31.75mm (1.25")
0482 0006ZXB	**0482** 0006ZXBF	6 Pole	38.10mm (1.50")
0482 0007ZXB	**0482** 0007ZXBF	7 Pole	44.45mm (1.75")
0482 0008ZXB	**0482** 0008ZXBF	8 Pole	50.80mm (2.00")
0482 0009ZXB	**0482** 0009ZXBF	9 Pole	57.15mm (2.25")
0482 00010ZXB	**0482** 00010ZXBF	10 Pole	63.50mm (2.50")
0482 00011ZXB	**0482** 00011ZXBF	11 Pole	69.85mm (2.75")
0482 00012ZXB	**0482** 00012ZXBF	12 Pole	76.20mm (3.00")
0482 00013ZXB	**0482** 00013ZXBF	13 Pole	82.55mm (3.25")
0482 00014ZXB	**0482** 00014ZXBF	14 Pole	88.90mm (3.50")
0482 00015ZXB	**0482** 00015ZXBF	15 Pole	95.25mm (3.75")
0482 00016ZXB	**0482** 00016ZXBF	16 Pole	101.60mm (4.00")
0482 00017ZXB	**0482** 00017ZXBF	17 Pole	107.95mm (4.25")
0482 00018ZXB	**0482** 00018ZXBF	18 Pole	114.30mm (4.50")
0482 00019ZXB	**0482** 00019ZXBF	19 Pole	120.65mm (4.75")
0482 00020ZXB	**0482** 00020ZXBF	20 Pole	127.00mm (5.00")

482 Series Panel Mount Fuseholder

Panel Mount – 15A: 15 ampere gangable version of fuseholder is keyed to prevent insertion of 20 ampere fuse. Please contact Littelfuse for ordering information.



ORDERING INFORMATION: Panel Mount –15A

Catalog Number Panel Mount	Catalog Number Panel Mount Flush	Type	Length (A)
0482 0001ZXP	**0482** 0001ZXPF	1 Pole	6.40mm (.25")
0482 0002ZXP	**0482** 0002ZXPF	2 Pole	12.80mm (.50")
0482 0003ZXP	**0482** 0003ZXPF	3 Pole	19.05mm (.75")
0482 0004ZXP	**0482** 0004ZXPF	4 Pole	25.40mm (1.0")
0482 0005ZXP	**0482** 0005ZXPF	5 Pole	31.75mm (1.25")
0482 0006ZXP	**0482** 0006ZXPF	6 Pole	38.10mm (1.50")
0482 0007ZXP	**0482** 0007ZXPF	7 Pole	44.45mm (1.75")
0482 0008ZXP	**0482** 0008ZXPF	8 Pole	50.80mm (2.00")
0482 0009ZXP	**0482** 0009ZXPF	9 Pole	57.15mm (2.25")
0482 00010ZXP	**0482** 00010ZXPF	10 Pole	63.50mm (2.50")
0482 00011ZXP	**0482** 00011ZXPF	11 Pole	69.85mm (2.75")
0482 00012ZXP	**0482** 00012ZXPF	12 Pole	76.20mm (3.00")
0482 00013ZXP	**0482** 00013ZXPF	13 Pole	82.55mm (3.25")
0482 00014ZXP	**0482** 00014ZXPF	14 Pole	88.90mm (3.50")
0482 00015ZXP	**0482** 00015ZXPF	15 Pole	95.25mm (3.75")
0482 00016ZXP	**0482** 00016ZXPF	16 Pole	101.60mm (4.00")
0482 00017ZXP	**0482** 00017ZXPF	17 Pole	107.95mm (4.25")
0482 00018ZXP	**0482** 00018ZXPF	18 Pole	114.30mm (4.50")
0482 00019ZXP	**0482** 00019ZXPF	19 Pole	120.65mm (4.75")
0482 00020ZXP	**0482** 00020ZXPF	20 Pole	127.00mm (5.00")

482 Series 20A Panel Mount Fuseholder

Panel Mount – 20A: The 20 ampere single pole holder is designed to accept all fuse ratings up to 20 amperes. 20 ampere fuseholders should be spaced 12.7mm (0.50) apart when loaded to maximum capacity, center to center to insure proper heat dissipation under normal operation. Heatsinking may be required for operation in higher ambient temperatures or alternate configurations.

AGENCY APPROVALS: Recognized under the Components Program of Underwriters Laboratories and the Components Acceptance Program of CSA.

AGENCY FILE NUMBERS: UL E71611, CSA LR 29862

SPECIFICATIONS:

Panel Mount – 20A: Rated at 20 amperes up to 125 VAC/VDC

Body Material: Black Phenolic


Fuse Terminals: Tin-plated Copper Alloy

Alarm Terminal: Tin-plated Copper Alloy


Operating Temperature: -40º to +85ºC

ORDERING INFORMATION:

CATALOG NUMBER: 0482 2001ZXPF



Panel Mount



RECOMMENDED PANEL MOUNTING HOLES

* For additional terminal lengths please contact Littelfuse.

Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург, Промышленная ул, дом № 19, литера Н, помещение 100-Н Офис 331