

## Hermetically Sealed, 3.3V High Speed, High CMR, Logic Gate Optocouplers



\*See Selection Guide for full matrix of part numbers.


These units are single and dual channel, hermetically sealed optocouplers. The products are capable of operation and storage over the full military temperature range and can be purchased as either standard commercial product or with full MIL-PRF-38534 Class Level H or K testing or from DLA Drawing 5962-08242. All devices are manufactured and tested on a MIL-PRF-38534 certified line and are included in the DLA Qualified Manufacturers List QML-38534 for Hybrid Microcircuits.

## Multichannel Devices

| Input   | Output |
|---------|--------|
| On (H)  | L      |
| Off (L) | H      |

| Input   | Enable | Output |
|---------|--------|--------|
| On (H)  | H      | L      |
| Off (L) | H      | H      |
| On (H)  | L      | H      |
| Off (L) | L      | H      |

Multiple channel devices available



*The connection of a 0.1  $\mu\text{F}$  bypass capacitor between  $V_{cc}$  and GND is recommended.*

- Low power consumption
- 3.3V supply voltages
- Dual marked with device part number and DLA drawing number
- Manufactured and tested on a MIL-PRF-38534 Certified Line
- QML-38534, Class H and K
- Three hermetically sealed package configurations
- Performance guaranteed over full military temperature range: -55°C to +125°C
- High speed: 10 Mbd typical
- CMR: > 10,000 V/μs typical
- 1500 Vdc withstand test voltage
- TTL circuit compatibility
- HCPL-260L/060L/263L/063L function compatibility

- Military and aerospace
- High reliability systems
- Transportation, medical, and life critical systems
- Line receiver
- Voltage level shifting
- Isolated input line receiver
- Isolated output line driver
- Logic ground isolation
- Harsh industrial environments
- Isolation for computer, communication, and test equipment systems

**CAUTION:** It is advised that normal static precautions be taken in handling and assembly of this component to prevent damage and/or degradation which may be induced by ESD.

Each channel contains a GaAsP light emitting diode which is optically coupled to an integrated high speed photon detector. The output of the detector is an open collector Schottky clamped transistor. Internal shields provide a guaranteed common mode transient immunity specification of 1000 V/ $\mu$ s. Package styles for these parts are 8 and 16 pin DIP through hole (case outlines P and E respectively). Devices may be purchased with a variety of lead bend and plating options. See Selection Guide Table for details. Standard Microcircuit Drawing (SMD) parts are available for each package and lead style.


Because the same electrical die (emitters and detectors) are used for each channel of each device listed in this data sheet, absolute maximum ratings, recommended operating conditions, electrical specifications, and performance characteristics shown in the figures are identical for all parts. Occasional exceptions exist due to package variations and limitations, and are as noted. Additionally, the same package assembly processes and materials are used in all devices.

### Selection Guide – Package Styles and Lead Configuration Options

| Package                           | 16 Pin DIP   | 8 Pin DIP    | 8 Pin DIP    |
|-----------------------------------|--------------|--------------|--------------|
| Lead Style                        | Through Hole | Through Hole | Through Hole |
| Channels                          | 2            | 1            | 2            |
| Common Channel Wiring             | VCC, GND     | None         | VCC, GND     |
| Withstand Test Voltage            | 1500 Vdc     | 1500 Vdc     | 1500 Vdc     |
| <b>Avago Part # &amp; Options</b> |              |              |              |
| Standard Commercial               | ACPL-2670L   | ACPL-5600L   | ACPL-5630L   |
| MIL-PRF-38534, Class H            | ACPL-2672L   | ACPL-5601L   | ACPL-5631L   |
| MIL-PRF-38534, Class K            | ACPL-268KL   | ACPL-560KL   | ACPL-563KL   |
| Standard Lead Finish              | Gold Plate   | Gold Plate   | Gold Plate   |
| Solder Dipped*                    | Option -200  | Option -200  | Option -200  |
| Butt Cut/Gold Plate               | Option -100  | Option -100  | Option -100  |
| Gull Wing/Soldered*               | Option -300  | Option -300  | Option -300  |
| <b>Class H SMD Part #</b>         |              |              |              |
| <i>Prescript for all below</i>    | 5962-        | 5962-        | 5962-        |
| Gold Plate                        | 0824203HEC   | 0824201HPC   | 0824202HPC   |
| Solder Dipped*                    | 0824203HEA   | 0824201HPA   | 0824202HPA   |
| Butt Cut/Gold Plate               | 0824203HUC   | 0824201HYC   | 0824202HYC   |
| Butt Cut/Soldered*                | 0824203HUA   | 0824201HYA   | 0824202HYA   |
| Gull Wing/Soldered*               | 0824203HTA   | 0824201HXA   | 0824202HXA   |
| <b>Class K SMD Part #</b>         |              |              |              |
| <i>Prescript for all below</i>    | 5962-        | 5962-        | 5962-        |
| Gold Plate                        | 0824203KEC   | 0824201KPC   | 0824202KPC   |
| Solder Dipped*                    | 0824203KEA   | 0824201KPA   | 0824202KPA   |
| Butt Cut/Gold Plate               | 0824203KUC   | 0824201KYC   | 0824202KYC   |
| Butt Cut/Soldered*                | 0824203KUA   | 0824201KYA   | 0824202KYA   |
| Gull Wing/Soldered*               | 0824203KTA   | 0824201KXA   | 0824202KXA   |

\* Solder contains lead.


## Functional Diagrams



**Note:** Dual channel devices have common V<sub>CC</sub> and ground. Single channel DIP has an enable pin 7. All diagrams are “top view.”


## Outline Drawings

### 16 Pin DIP Through Hole, 2 Channels




**NOTE:** DIMENSIONS IN MILLIMETERS (INCHES).

### 8 Pin DIP Through Hole, 1 and 2 Channels



**NOTE:** DIMENSIONS IN MILLIMETERS (INCHES).

## Device Marking



Note 1. Qualified parts only

## Hermetic Optocoupler Options

| Option | Description                                                                                                                                                                                                                                                                                                              |
|--------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 100    | <p>Surface mountable hermetic optocoupler with leads trimmed for butt joint assembly. This option is available on standard commercial, class H &amp; class K product in 8 and 16 pin DIP (see drawings below for details).</p> <p>NOTE: DIMENSIONS IN MILLIMETERS (INCHES).</p>                                          |
| 200    | <p>Lead finish is solder dipped rather than gold plated. This option is available on standard commercial, class H and class K products in 8 and 16 pin DIP. DLA Drawing part numbers contain provisions for lead finish.</p>                                                                                             |
| 300    | <p>Surface mountable hermetic optocoupler with leads cut and bent for gull wing assembly. This option is available on standard commercial, class H &amp; class K product in 8 and 16 pin DIP (see drawings below for details). This option has solder dipped leads.</p> <p>NOTE: DIMENSIONS IN MILLIMETERS (INCHES).</p> |

Solder contains lead.

## Absolute Maximum Ratings


No derating required up to +125°C.

| Parameter                                                 | Symbol        | Min. | Max.           | Units |
|-----------------------------------------------------------|---------------|------|----------------|-------|
| Storage Temperature                                       | $T_S$         | -65  | +150           | °C    |
| Operating Temperature                                     | $T_A$         | -55  | +125           | °C    |
| Case Temperature                                          | $T_C$         |      | +170           | °C    |
| Junction Temperature                                      | $T_J$         |      | +175           | °C    |
| Lead Solder Temperature                                   |               |      | 260 for 10 sec | °C    |
| Peak Forward Input Current (each channel, ≤1 ms duration) | $I_{F(PEAK)}$ |      | 40             | mA    |
| Average Input Forward Current (each channel)              | $I_{F(AVG)}$  |      | 20             | mA    |
| Input Power Dissipation (each channel)                    |               |      | 35             | mW    |
| Reverse Input Voltage (each channel)                      | $V_R$         |      | 5              | V     |
| Supply Voltage (1 minute maximum)                         | $V_{CC}$      |      | 7.0            | V     |
| Output Current (each channel)                             | $I_O$         |      | 25             | mA    |
| Output Voltage (each channel)                             | $V_O$         |      | 7              | V     |
| Output Power Dissipation (each channel)                   | $P_O$         |      | 40             | mW    |
| Package Power Dissipation (each channel)                  | $P_D$         |      | 200            | mW    |

## Single Channel Product Only

|                      |       |  |     |   |
|----------------------|-------|--|-----|---|
| Enable Input Voltage | $V_E$ |  | 3.6 | V |
|----------------------|-------|--|-----|---|

## 8 Pin Ceramic DIP Single Channel Schematic



Note enable pin 7. An external 0.01  $\mu$ F to 0.1  $\mu$ F bypass capacitor must be connected between  $V_{CC}$  and ground for each package type.

## ESD Classification

MIL-PRF-38534 and MIL-STD-883, Method 3015

|                                    |                  |
|------------------------------------|------------------|
| ACPL-560L/01L/0KL, 5962-0824201    | (▲B), Class 1B   |
| ACPL-5630L/31L/3KL, 5962-0824202   | (▲▲▲A), Class 3A |
| ACPL-2670L/72L/268KL, 5962-0824203 | (▲▲), Class 2    |

## Recommended Operating Conditions

| Parameter                               | Symbol   | Min. | Max. | Units   |
|-----------------------------------------|----------|------|------|---------|
| Input Current, Low Level, Each Channel  | $I_{FL}$ | 0    | 250  | $\mu$ A |
| Input Current, High Level, Each Channel | $I_{FH}$ | 10   | 20   | mA      |
| Supply Voltage, Output                  | $V_{CC}$ | 3.0  | 3.6  | V       |
| Fan Out (TTL Load) Each Channel         | N        |      | 6    |         |

## Recommended Operating Conditions (cont'd.)

Single Channel Product Only<sup>[10]</sup>

| Parameter                 | Symbol   | Min. | Max.     | Units |
|---------------------------|----------|------|----------|-------|
| High Level Enable Voltage | $V_{EH}$ | 2.0  | $V_{CC}$ | V     |
| Low Level Enable Voltage  | $V_{EL}$ | 0    | 0.8      | V     |

## Electrical Characteristics ( $T_A = -55^{\circ}\text{C}$ to $+125^{\circ}\text{C}$ , unless otherwise specified)

| Parameter                         |                | Symbol    | Test Conditions                                                                               | Group A <sup>[13]</sup><br>Sub-groups | Limits |       |      | Units         | Fig. | Note     |
|-----------------------------------|----------------|-----------|-----------------------------------------------------------------------------------------------|---------------------------------------|--------|-------|------|---------------|------|----------|
|                                   |                |           |                                                                                               |                                       | Min.   | Typ.* | Max. |               |      |          |
| High Level Output Current         |                | $I_{OH}$  | $V_{CC} = 3.3\text{ V}$ , $V_O = 3.3\text{ V}$ ,<br>$I_F = 250\text{ }\mu\text{A}$            | 1, 2, 3                               |        | 6     | 250  | $\mu\text{A}$ | 1    | 1        |
| Low Level Output Voltage          |                | $V_{OL}$  | $V_{CC} = 3.3\text{ V}$ , $I_F = 10\text{ mA}$ ,<br>$I_{OL}$ (Sinking) = 10 mA                | 1, 2, 3                               |        | 0.3   | 0.6  | V             | 2    | 1, 8     |
| Current Transfer Ratio            |                | $h_F$ CTR | $V_O = 0.6\text{ V}$ , $I_F = 10\text{ mA}$ ,<br>$V_{CC} = 3.3\text{ V}$                      | 1, 2, 3                               | 100    |       |      | %             |      | 1        |
| Logic High Supply Current         | Single Channel | $I_{CCH}$ | $V_{CC} = 3.3\text{ V}$ , $I_F = 0\text{ mA}$                                                 | 1, 2, 3                               |        | 5     | 11   | mA            |      | 1        |
|                                   | Dual Channel   |           | $V_{CC} = 3.3\text{ V}$ ,<br>$I_{F1} = I_{F2} = 0\text{ mA}$                                  |                                       |        | 10    | 22   | mA            |      |          |
| Logic low Supply Current          | Single Channel | $I_{CCL}$ | $V_{CC} = 3.3\text{ V}$ ,<br>$I_F = 20\text{ mA}$                                             | 1, 2, 3                               |        | 6     | 15   | mA            |      | 1        |
|                                   | Dual Channel   |           | $V_{CC} = 3.3\text{ V}$ ,<br>$I_{F1} = I_{F2} = 20\text{ mA}$                                 |                                       |        | 12    | 30   | mA            |      |          |
| Input Forward Voltage             |                | $V_F$     | $I_F = 20\text{ mA}$                                                                          | 1, 2                                  |        | 1.55  | 1.75 | V             | 3    | 1        |
|                                   |                |           |                                                                                               | 3                                     |        |       | 1.85 |               |      |          |
| Input Reverse Breakdown Voltage   |                | $BV_R$    | $I_R = 10\text{ }\mu\text{A}$                                                                 | 1, 2, 3                               | 5      |       |      | V             |      | 1        |
| Input-Output Leakage Current      |                | $I_{I-O}$ | $RH \leq 65\%$ , $T_A = 25^{\circ}\text{C}$<br>$t = 5\text{ s}$ , $V_{I-O} = 1500\text{ Vdc}$ | 1                                     |        |       | 1.0  | $\mu\text{A}$ |      | 2, 7     |
| Capacitance Between Input/ Output |                | $C_{I-O}$ | $f = 1\text{ MHz}$ , $T_C = 25^{\circ}\text{C}$                                               | 4                                     |        | 1.0   | 4.0  | pF            |      | 1, 3, 13 |

\*All typical values are at  $V_{CC} = 3.3\text{ V}$ ,  $T_A = 25^{\circ}\text{C}$ .

**Electrical Characteristics (cont'd)  $T_A = -55^{\circ}\text{C}$  to  $+125^{\circ}\text{C}$  unless otherwise specified**

| Parameter                                                       | Symbol           | Test Conditions                                                                                                                                | Group A <sup>[13]</sup><br>Subgroups | Limits |        |      | Units | Fig.    | Note        |
|-----------------------------------------------------------------|------------------|------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|--------|--------|------|-------|---------|-------------|
|                                                                 |                  |                                                                                                                                                |                                      | Min.   | Typ.*  | Max. |       |         |             |
| Propagation Delay<br>Time to High Output<br>Level               | t <sub>PLH</sub> | V <sub>CC</sub> = 3.3 V, R <sub>L</sub> = 510 Ω,<br>C <sub>L</sub> = 50 pF, I <sub>F</sub> = 13 mA                                             | 9                                    |        | 43     | 100  | ns    | 4, 5, 6 | 1, 5        |
|                                                                 |                  |                                                                                                                                                | 10, 11                               |        |        | 140  |       |         |             |
| Propagation Delay<br>Time to Low Output<br>Level                | t <sub>PHL</sub> |                                                                                                                                                | 9                                    |        | 54     | 100  | ns    |         |             |
|                                                                 |                  |                                                                                                                                                | 10, 11                               |        |        | 120  |       |         |             |
| Output Rise Time                                                | t <sub>LH</sub>  | R <sub>L</sub> = 510 Ω, C <sub>L</sub> = 50 pF,<br>I <sub>F</sub> = 13 mA                                                                      | 9, 10, 11                            |        | 20     | 90   | ns    |         | 1           |
| Output Fall Time                                                | t <sub>HL</sub>  |                                                                                                                                                |                                      |        | 8      | 40   |       |         |             |
| Common Mode<br>Transient<br>Immunity at<br>High Output<br>Level | CM <sub>H</sub>  | V <sub>CM</sub> = 50 V (PEAK),<br>V <sub>CC</sub> = 3.3 V,<br>V <sub>O</sub> (min.) = 2 V,<br>R <sub>L</sub> = 510 Ω, I <sub>F</sub> = 0 mA    | 9, 10, 11                            | 1000   | >10000 |      | V/μs  | 7       | 1, 6,<br>13 |
| Common Mode<br>Transient<br>Immunity at Low<br>Output Level     | CM <sub>L</sub>  | V <sub>CM</sub> = 50 V (PEAK),<br>V <sub>CC</sub> = 3.3 V,<br>V <sub>O</sub> (max.) = 0.8 V,<br>R <sub>L</sub> = 510 Ω, I <sub>F</sub> = 10 mA | 9, 10, 11                            | 1000   | >10000 |      | V/μs  | 7       | 1, 6,<br>13 |

**Single Channel Product Only**

|                              |          |                                                   |         |      |       |     |    |  |   |
|------------------------------|----------|---------------------------------------------------|---------|------|-------|-----|----|--|---|
| Low Level<br>Enable Current  | $I_{EL}$ | $V_{CC} = 3.3\text{ V}$ ,<br>$V_E = 0.5\text{ V}$ | 1, 2, 3 | -2.0 | -0.54 |     | mA |  |   |
| High Level<br>Enable Voltage | $V_{EH}$ |                                                   | 1, 2, 3 | 2.0  |       |     | V  |  | 9 |
| Low Level<br>Enable Voltage  | $V_{EL}$ |                                                   | 1, 2, 3 |      |       | 0.8 | V  |  |   |

\*All typical values are at  $V_{CC} = 3.3\text{ V}$ ,  $T_A = 25^{\circ}\text{C}$ .

**Typical Characteristics,  $T_A = 25^{\circ}\text{C}$ ,  $V_{CC} = 3.3\text{ V}$** 

| Parameter                              | Sym.                            | Typ.      | Units                  | Test Conditions                         | Fig. | Note |
|----------------------------------------|---------------------------------|-----------|------------------------|-----------------------------------------|------|------|
| Input Capacitance                      | $C_{IN}$                        | 60        | pF                     | $V_F = 0\text{ V}$ , $f = 1\text{ MHz}$ |      | 1    |
| Input Diode Temperature<br>Coefficient | $\frac{\Delta V_F}{\Delta T_A}$ | -1.5      | mV/ $^{\circ}\text{C}$ | $I_F = 20\text{ mA}$                    |      | 1    |
| Resistance (Input-Output)              | $R_{I-O}$                       | $10^{12}$ | $\Omega$               | $V_{I-O} = 500\text{ V}$                |      | 2    |

**Single Channel Product Only**

|                                                               |           |    |    |                                                                                                                       |      |       |
|---------------------------------------------------------------|-----------|----|----|-----------------------------------------------------------------------------------------------------------------------|------|-------|
| Propagation Delay Time of<br>Enable from $V_{EH}$ to $V_{EL}$ | $t_{ELH}$ | 32 | ns | $R_L = 510\ \Omega$ , $C_L = 50\text{ pF}$<br>$I_F = 13\text{ mA}$ , $V_{EH} = 3\text{ V}$ ,<br>$V_{EL} = 0\text{ V}$ | 8, 9 | 1, 10 |
| Propagation Delay Time of<br>Enable from $V_{EL}$ to $V_{EH}$ | $t_{EHL}$ | 28 | ns |                                                                                                                       |      | 1, 11 |

**Dual Channel Product Only**

|                                |           |           |          |                                                                              |  |   |
|--------------------------------|-----------|-----------|----------|------------------------------------------------------------------------------|--|---|
| Input-Input<br>Leakage Current | $I_{I-I}$ | 0.5       | nA       | Relative Humidity $\leq 65\%$<br>$V_{I-I} = 500\text{ V}$ , $t = 5\text{ s}$ |  | 4 |
| Resistance (Input-Input)       | $R_{I-I}$ | $10^{12}$ | $\Omega$ | $V_{I-I} = 500\text{ V}$                                                     |  | 4 |
| Capacitance (Input-Input)      | $C_{I-I}$ | 0.55      | pF       | $f = 1\text{ MHz}$                                                           |  | 4 |

#### Notes:

1. Each channel.
2. All devices are considered two-terminal devices;  $I_{IO}$  is measured between all input leads or terminals shorted together and all output leads or terminals shorted together.
3. Measured between each input pair shorted together and all output connections for that channel shorted together.
4. Measured between adjacent input pairs shorted together for each multichannel device.
5.  $t_{PHL}$  propagation delay is measured from the 50% point on the leading edge of the input pulse to the 1.5 V point on the leading edge of the output pulse. The  $t_{PLH}$  propagation delay is measured from the 50% point on the trailing edge of the input pulse to the 1.5 V point on the trailing edge of the output pulse.
6.  $CM_L$  is the maximum rate of rise of the common mode voltage that can be sustained with the output voltage in the logic low state ( $V_O < 0.8$  V).  $CM_H$  is the maximum rate of fall of the common mode voltage that can be sustained with the output voltage in the logic high state ( $V_O > 2.0$  V).
7. This is a momentary withstand test, not an operating condition.
8. It is essential that a bypass capacitor (0.01 to 0.1  $\mu$ F, ceramic) be connected from  $V_{CC}$  to ground. Total lead length between both ends of this external capacitor and the isolator connections should not exceed 20 mm.
9. No external pull up is required for a high logic state on the enable input.
10. The  $t_{ELH}$  enable propagation delay is measured from the 1.5 V point on the trailing edge of the enable input pulse to the 1.5 V point on the trailing edge of the output pulse.
11. The  $t_{EHL}$  enable propagation delay is measured from the 1.5 V point on the leading edge of the enable input pulse to the 1.5 V point on the leading edge of the output pulse.
12. Standard commercial parts receive 100% testing at 25°C (Subgroups 1 and 9). Class H and K parts receive 100% testing at 25, 125, and -55°C (Subgroups 1 and 9, 2 and 10, 3 and 11, respectively).
13. Parameters are tested as part of device initial characterization and after design and process changes. Parameters are guaranteed to limits specified for all lots not specifically tested.




Figure 1. High Level Output Current vs. Temperature.




Figure 2. Input-Output Characteristics.




Figure 3. Input Diode Forward Characteristics.





Figure 4. Test Circuit for  $t_{PHL}$  and  $t_{PLH}$  \*




Figure 6. Propagation Delay vs. Temperature.




Figure 5. Propagation Delay,  $t_{PHL}$  and  $t_{PLH}$  vs. Pulse Input Current,  $I_{FH}$ .




Figure 7. Test Circuit for Common Mode Transient Immunity and Typical Waveforms.



## **MIL-PRF-38534 Class H, Class K, and DLA SMD Test Program**

Avago's Hi-Rel Optocouplers are in compliance with MIL-PRF-38534 Classes H and K. Class H and Class K devices are also in compliance with DLA drawing 5962-08242.

Testing consists of 100% screening and quality conformance inspection to MIL-PRF-38534.

For product information and a complete list of distributors, please go to our website: **[www.avagotech.com](http://www.avagotech.com)**

Avago, Avago Technologies, and the A logo are trademarks of Avago Technologies Limited in the United States and other countries. Data subject to change. Copyright © 2005-2012 Avago Technologies Limited. All rights reserved.  
AV02-1327EN - October 2, 2012





**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331