Storm Interface

Secured, sealed and toughened data entry devices

5100 SERIES





All dimensions in mm

- Impact, shock and vibration resistant
- Sealed for use in wet or dirty environments
- Weather resistant for use in exposed locations (optional feature)
- Extended operational temperature range -20°C to +70°C (optional feature)
- Programmable USB display controller and system interface
- Display connects to the host system via a single USB cable with a USB Mini-B connector (cable supplied separately)
- Resistant to petrochemicals, detergents and most commonly used non-abrasive cleaning agents
- Responsive, illuminated menu navigation keys under software control (on/off /flashing) (optional feature)
- Easy to use API with downloadable object code libraries
- USB 2.0 HID compliant device

Toughened, weather resistant, data displays with integral USB 2.0 interface

These robust, monochrome displays are ideal for use in exposed or industrial environments. Bright white transflective display technology is securely encased within a sealed and impact resistant bezel. The bezel features a hard coated UV and scratch resistant, polycarbonate window.

Available in either 20 character x 4 line, 20 character x 8 line or 128 x 64 pixel graphic versions these USB 2.0 display devices can be easily installed into any control panel or equipment enclosure.

The display assemblies can be specified with or without three independently illuminated menu navigation keys. Illumination is under software control (on/off/flashing).

Offered in eight different configurations/specifications, Storm 5100 Series Displays are rated for use in either Industrial (IND) or Extreme (EXM) environments. They offer a 'ready to use' display solution for a wide range of indoor or outdoor applications.

Performance

Operational key life:	**>2 million cycles per key**

Environmental

Operational temperature:	**0°C to +60°C (optionally -20°C to +70°C)**
Storage temperature:	**-20°C to +70°C**
Humidity:	**5%RH to 95%RH non-condensing**
Vibration and shock:	**ETSI 300 019 5M3 (optionally 6M3)**
Water and dust resistance:	**IP54 (optionally IP65)**
Impact resistant:	**5J (optionally 10J)**

Electrical

Insulation resistance:	**50Mohms (min)**
Breakdown voltage:	**500V a.c. (60 secs)**
Max Operating voltage:	**5V**
Max Operating current:	**50mA**

Compliance

This device is designed to meet:

- **EU RoHS**
- **EU Low Voltage Directive**
- **ESD: Up to +/- 15kV air discharge, +/- 7.5kV contact discharge**
- **WEEE Directive**
- **EMC-CE, FCC Part 15B Class B**
- **EN55022 Class B, EN60950, EN55024**

Additional Information

(downloads available at www.storm-interface.com)

- Engineering Manual including product dimensions and installation / configuration instructions
- CAD files (dxf, dwg)
- API Object code libraries
- Test data and reports

Accessories

- USB Cable for use with USB Interface
- Under panel fitting kit



Storm Interface

Secured, sealed and toughened data entry devices

5100 SERIES

Configuration Utility Software for Storm 5100 Series Toughened USB 2.0 Data Displays

Storm 5100 Series Toughened Data Displays can be configured by the Configuration Utility Software via the Application Programming Interface for Windows (API). These software tools are available free of charge and can be downloaded from **www.storm-interface.com**. Please note: Registration is required for download.

Primary Features of the Configuration Utility

- Selection of font for 5100 Series character displays
  Two standard fonts are available:
  6 x 8. This provides 8 lines with 20 characters per line
  6 x 16. This provides 4 lines with 20 characters per line
  Each font includes the following character set:
  !"#$%&'()*+,.\0123456789:;<=>?@ABCDEFGHIJKLMNOPQR STUVWXYZ[/]^_'abcdefghijklmnopqstuvwxyz{|}~
  There is also a large font numeric character set:
  0123456789,.°±
- The 5100 Series graphic display is 128 x 64 pixels.
- Features supported by the Configuration Utility and API include:

Integral display backlight (on/off/flashing)
Illumination of three navigation keys (on/off/flashing)
Display contrast level
Flip (180° rotation)
Inverse (white on black)
Circle, rectangle and line
Bar graph
Large font
Re-set to factory default
Firmware updates

- The utility will load up to four bitmap graphic icons (maximum size 128 x 64 pixels). Any one icon can be set as the default 'power-up' screen. Icons can be originated using Microsoft Paint and previewed using the Configuration Utility before loading to the display.
- The display enumerates as an HID compliant device.

Windows and Microsoft Paint are recognised trademarks of the Microsoft Corporation.

	5100 (IND)	5100 (EXM)
Storm 5100 Series character display	• USB • 3 keys or display only • 4 or 8 line x 20 characters • IP54 • 0°C to 60°C • 5J impact • shock and vibration IEC721-5M3	• USB • 3 keys or display only • 4 or 8 line x 20 characters • IP65 • -20°C to 70°C • 10J impact • shock and vibration IEC721-6M3
Storm 5100 Series graphic display	• USB • 3 keys or display only • 128 x 64 pixels • IP54 • 0°C to 60°C • 5J impact • shock and vibration IEC721-5M3	• USB • 3 keys or display only • 128 x 64 pixels • IP65 • -20°C to 70°C • 10J impact • shock and vibration IEC721-6M3

Part Numbers

5100 (IND) – INDUSTRIAL

4 or 8 x 20 character display, 3 keys	5103-000
128 x 64 pixel graphic display, 3 keys	5103-100
4 or 8 x 20 character display, display only	5100-000
128 x 64 pixel graphic display, display only	5100-100

5100 (EXM) – EXTREME

4 or 8 x 20 character display, 3 keys	5103-010
128 x 64 pixel graphic display, 3 keys	5103-110
4 or 8 x 20 character display, display only	5100-010
128 x 64 pixel graphic display, display only	5100-110

Accessories

USB Cable (USB A to 90° USB mini-B)	4500-01
Under panel fitting kit	5100-FK0



For more information & to order:

www.storm-interface.com

Whilst every effort is made to ensure details are correct at time of print, specifications are subject to change without notice.

Designed & produced by **NIK Design** nik@nikdesign.co.uk

Storm Interface products include technology protected by international patents and design registration. All rights reserved.

Storm is a trademark of Keymat Technology Ltd
Storm Interface is a trading name of Keymat Technology Ltd

5100 Jan 2014

FM 39602



Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург, Промышленная ул, дом № 19, литера Н, помещение 100-Н Офис 331