


## Fast Switching Plastic Rectifier


**DO-204AL (DO-41)**

### FEATURES

- Fast switching for high efficiency
- Low forward voltage drop
- Low leakage current
- High forward surge capability
- Solder dip 275 °C max. 10 s, per JESD 22-B106
- Compliant to RoHS directive 2002/95/EC and in accordance to WEEE 2002/96/EC


**RoHS**  
COMPLIANT

### TYPICAL APPLICATIONS

For use in fast switching rectification of power supply, inverters, converters and freewheeling diodes for consumer and telecommunication.

#### Note

- These devices are not AEC-Q101 qualified.

### MECHANICAL DATA

**Case:** DO-204AL, molded epoxy body  
Molding compound meets UL 94 V-0 flammability rating  
Base P/N-E3 - RoHS compliant, commercial grade

**Terminals:** Matte tin plated leads, solderable per J-STD-002 and JESD 22-B102

E3 suffix meets JESD 201 class 1A whisker test

**Polarity:** Color band denotes cathode end

### PRIMARY CHARACTERISTICS

|             |               |
|-------------|---------------|
| $I_{F(AV)}$ | 1.0 A         |
| $V_{RRM}$   | 50 V to 600 V |
| $I_{FSM}$   | 30 A          |
| $t_{rr}$    | 200 ns        |
| $I_R$       | 5.0 $\mu$ A   |
| $V_F$       | 1.2 V         |
| $T_J$ max.  | 150 °C        |

### MAXIMUM RATINGS ( $T_A = 25$ °C unless otherwise noted)

| PARAMETER                                                                                 | SYMBOL         | 1N4933        | 1N4934 | 1N4935 | 1N4936 | 1N4937 | UNIT |
|-------------------------------------------------------------------------------------------|----------------|---------------|--------|--------|--------|--------|------|
| Maximum repetitive peak reverse voltage                                                   | $V_{RRM}$      | 50            | 100    | 200    | 400    | 600    | V    |
| Maximum RMS voltage                                                                       | $V_{RMS}$      | 35            | 70     | 145    | 280    | 420    | V    |
| Maximum DC blocking voltage                                                               | $V_{DC}$       | 50            | 100    | 200    | 400    | 600    | V    |
| Maximum average forward rectified current<br>0.375" (9.5 mm) lead length at $T_A = 75$ °C | $I_{F(AV)}$    | 1.0           |        |        |        |        | A    |
| Peak forward surge current 8.3 ms single half sine-wave<br>superimposed on rated load     | $I_{FSM}$      | 30            |        |        |        |        | A    |
| Maximum reverse recovery current                                                          | $I_{RM}$       | 2.0           |        |        |        |        | A    |
| Operating junction and storage temperature range                                          | $T_J, T_{STG}$ | - 50 to + 150 |        |        |        |        | °C   |

### ELECTRICAL CHARACTERISTICS ( $T_A = 25$ °C unless otherwise noted)

| PARAMETER                                               | TEST CONDITIONS                                                                                        |                         | SYMBOL          | 1N4933 | 1N4934 | 1N4935 | 1N4936 | 1N4937 | UNIT |
|---------------------------------------------------------|--------------------------------------------------------------------------------------------------------|-------------------------|-----------------|--------|--------|--------|--------|--------|------|
| Maximum instantaneous forward voltage                   | 1.0 A                                                                                                  |                         | V <sub>F</sub>  | 1.2    |        |        |        |        | V    |
| Maximum DC reverse current at rated DC blocking voltage |                                                                                                        | T <sub>A</sub> = 25 °C  | I <sub>R</sub>  | 5.0    |        |        |        |        | μA   |
|                                                         |                                                                                                        | T <sub>A</sub> = 100 °C |                 | 100    |        |        |        |        |      |
| Maximum reverse recovery time                           | I <sub>F</sub> = 1.0 A, V <sub>R</sub> = 30 V, dI/dt = 50 A/μs, I <sub>rr</sub> = 10 % I <sub>RM</sub> |                         | t <sub>rr</sub> | 200    |        |        |        |        | ns   |
| Typical junction capacitance                            | 4.0 V, 1 MHz                                                                                           |                         | C <sub>J</sub>  | 12     |        |        |        |        | pF   |

| THERMAL CHARACTERISTICS (T <sub>A</sub> = 25 °C unless otherwise noted) |                                 |        |        |        |        |        |      |
|-------------------------------------------------------------------------|---------------------------------|--------|--------|--------|--------|--------|------|
| PARAMETER                                                               | SYMBOL                          | 1N4933 | 1N4934 | 1N4935 | 1N4936 | 1N4937 | UNIT |
| Typical thermal resistance                                              | R <sub>θJA</sub> <sup>(1)</sup> | 55     |        |        |        |        | °C/W |
|                                                                         | R <sub>θJL</sub> <sup>(1)</sup> | 25     |        |        |        |        |      |

### Note

(1) Thermal resistance from junction to ambient and from junction to lead at 0.375" (9.5 mm) lead length, P.C.B. mounted

| ORDERING INFORMATION (Example) |                 |                        |               |                                  |
|--------------------------------|-----------------|------------------------|---------------|----------------------------------|
| PREFERRED P/N                  | UNIT WEIGHT (g) | PREFERRED PACKAGE CODE | BASE QUANTITY | DELIVERY MODE                    |
| 1N4933-E3/54                   | 0.33            | 54                     | 5500          | 13" diameter paper tape and reel |
| 1N4933-E3/73                   | 0.33            | 73                     | 3000          | Ammo pack packaging              |

## RATINGS AND CHARACTERISTICS CURVES

( $T_A = 25\text{ }^{\circ}\text{C}$  unless otherwise noted)




Fig. 1 - Forward Current Derating Curves




Fig. 3 - Maximum Non-repetitive Peak Forward Surge Current




Fig. 2 - Forward Power Loss Characteristics




Fig. 4 - Typical Instantaneous Forward Characteristics




Fig. 5 - Typical Reverse Characteristics




Fig. 7 - Typical Transient Thermal Impedance





Fig. 6 - Typical Junction Capacitance

### PACKAGE OUTLINE DIMENSIONS in inches (millimeters)



#### Note

- Lead diameter is  $\frac{0.026}{0.023}$  ( $\frac{0.66}{0.58}$ ) for suffix "E" part numbers



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331