


**SERIES: PBK-3 | DESCRIPTION: AC-DC POWER SUPPLY**
**FEATURES**

- up to 3 W continuous output
- compact SIP package
- single regulated outputs from 3.3~24 V
- 3,000 Vac isolation
- over current and short circuit protections
- CE, UL60950-1 safety approval
- wide input voltage: 100~400 Vdc (85~264 Vac)
- efficiency up to 78%



| MODEL                | output voltage | output current | output power | ripple and noise <sup>2</sup> | efficiency |
|----------------------|----------------|----------------|--------------|-------------------------------|------------|
|                      | (Vdc)          | max (mA)       | max (W)      | max (mVp-p)                   | typ (%)    |
| PBK-3-3 <sup>1</sup> | 3.3            | 500            | 1.65         | 150                           | 66         |
| PBK-3-5              | 5              | 500            | 2.5          | 150                           | 69         |
| PBK-3-9              | 9              | 333            | 3            | 120                           | 76         |
| PBK-3-12             | 12             | 250            | 3            | 120                           | 78         |
| PBK-3-15             | 15             | 200            | 3            | 120                           | 78         |
| PBK-3-24             | 24             | 125            | 3            | 120                           | 78         |

Note: 1. The PBK-3-3 & PBK-3-3-B do not meet UL and CE standards.  
 2. Measured at 20 MHz bandwidth, see Test Configuration section.

**PART NUMBER KEY**


## INPUT

| parameter                 | conditions/description                         | min       | typ      | max        | units      |
|---------------------------|------------------------------------------------|-----------|----------|------------|------------|
| voltage                   |                                                | 85<br>100 |          | 264<br>400 | Vac<br>Vdc |
| frequency                 |                                                | 47        |          | 440        | Hz         |
| current                   | at 115 Vac<br>at 230 Vac                       |           |          | 120<br>60  | mA<br>mA   |
| inrush current            | at 115 Vac<br>at 230 Vac                       |           | 20<br>40 |            | A<br>A     |
| no load power consumption |                                                |           |          | 0.5        | W          |
| input fuse                | 1 A/250 V, slow-blow type (external, required) |           |          |            |            |

## OUTPUT

| parameter               | conditions/description             | min | typ   | max  | units |
|-------------------------|------------------------------------|-----|-------|------|-------|
| output current          |                                    | 10  |       |      | %     |
| capacitive load         | 3.3 Vdc output models              |     |       | 2300 | μF    |
|                         | 5 Vdc output models                |     |       | 470  | μF    |
|                         | 9 Vdc output models                |     |       | 150  | μF    |
|                         | all other models                   |     |       | 100  | μF    |
| line regulation         | 3.3 Vdc models, at full load       |     | ±0.5  |      | %     |
|                         | all other models, at full load     |     | ±1.5  |      | %     |
| load regulation         | 3.3 Vdc models, at 10%~100% load   |     | ±1.5  |      | %     |
|                         | all other models, at 10%~100% load |     | ±2.5  |      | %     |
| voltage set accuracy    | 3.3 Vdc output models              |     |       | ±3   | %     |
|                         | 9 & 12 Vdc output models           |     |       | ±8   | %     |
|                         | all other models                   |     |       | ±5   | %     |
| hold-up time            | at 115 Vac                         | 60  |       |      | ms    |
|                         | at 230 Vac                         | 300 |       |      | ms    |
| switching frequency     | 3.3 Vdc output models              |     | 100   |      | kHz   |
|                         | all other models                   |     |       | 50   | kHz   |
| temperature coefficient |                                    |     | ±0.15 |      | %/°C  |

## PROTECTIONS

| parameter                | conditions/description   | min | typ | max | units |
|--------------------------|--------------------------|-----|-----|-----|-------|
| short circuit protection | continuous, auto restart |     |     |     |       |
| over current protection  | auto restart             |     |     |     |       |

## SAFETY & COMPLIANCE

| parameter            | conditions/description                                                                    | min   | typ | max | units |
|----------------------|-------------------------------------------------------------------------------------------|-------|-----|-----|-------|
| isolation voltage    | input to output, for 1 minute                                                             | 3,000 |     |     | Vac   |
| isolation resistance |                                                                                           | 100   |     |     | MΩ    |
| safety approvals     | UL60950-1, CE                                                                             |       |     |     |       |
| safety class         | Class II                                                                                  |       |     |     |       |
| conducted emissions  | CISPR22/EN55022 external circuit required, Class A (see figure 2); Class B (see figure 3) |       |     |     |       |
| radiated emissions   | CISPR22/EN55022 external circuit required, Class A (see figure 2); Class B (see figure 3) |       |     |     |       |
| ESD                  | IEC/EN61000-4-2 Class B, contact ±4 kV                                                    |       |     |     |       |
| radiated immunity    | IEC/EN61000-4-3 Class A, 10V/m (external circuit required, see figure 3)                  |       |     |     |       |
| EFT/burst            | IEC/EN61000-4-4 Class B, ±2 kV (external circuit required, see figure 2)                  |       |     |     |       |
|                      | IEC/EN61000-4-4 Class B, ±4 kV (external circuit required, see figure 3)                  |       |     |     |       |
| surge                | IEC/EN61000-4-5 Class B, ±1 kV/±2 kV (external circuit required, see figure 3)            |       |     |     |       |
| conducted immunity   | IEC/EN61000-4-6 Class A, 3 Vr.m.s (external circuit required, see figure 3)               |       |     |     |       |
| PFM                  | IEC/EN61000-4-8 Class A, 10 A/m                                                           |       |     |     |       |




## SAFETY & COMPLIANCE (CONTINUED)

| parameter                    | conditions/description           | min     | typ | max | units |
|------------------------------|----------------------------------|---------|-----|-----|-------|
| voltage dips & interruptions | IEC/EN61000-4-11 Class B, 0%-70% |         |     |     |       |
| MTBF                         | at 25°C, max. load               | 300,000 |     |     | hours |
| RoHS                         | 2011/65/EU                       |         |     |     |       |





## ENVIRONMENTAL

| parameter             | conditions/description | min | typ | max | units |
|-----------------------|------------------------|-----|-----|-----|-------|
| operating temperature | see derating curves    | -40 |     | 85  | °C    |
| storage temperature   |                        | -40 |     | 105 | °C    |
| case temperature      |                        |     |     | 90  | °C    |
| humidity              | non-condensing         |     |     | 85  | %     |

## DERATING CURVES



## EFFICIENCY CURVES



## SOLDERABILITY

| parameter      | conditions/description | min | typ | max | units |
|----------------|------------------------|-----|-----|-----|-------|
| hand soldering | for 3~5 seconds        | 350 | 360 | 370 | °C    |
| wave soldering | for 5~10 seconds       | 255 | 260 | 265 | °C    |

## MECHANICAL

| parameter  | conditions/description                     | min | typ | max | units |
|------------|--------------------------------------------|-----|-----|-----|-------|
| dimensions | PBK-3-3 vertical model: 37 x 11 x 25       |     |     |     | mm    |
|            | all other vertical models: 35 x 11 x 25    |     |     |     | mm    |
|            | PBK-3-3 right-angle model: 37 x 13 x 25    |     |     |     | mm    |
|            | all other right-angle models: 35 x 13 x 25 |     |     |     | mm    |
| material   | UL94V-0                                    |     |     |     |       |
| weight     |                                            |     | 8   |     | g     |

## MECHANICAL DRAWING


### PBK-3-3 VERTICAL ORIENTATION

units: mm[inch]


tolerance:  $\pm 0.5[\pm 0.020]$ pin tolerance:  $\pm 0.1[\pm 0.004]$ 

| PIN CONNECTIONS |          |
|-----------------|----------|
| PIN             | FUNCTION |
| 1               | -Vin (N) |
| 3               | +Vin (L) |
| 5               | +V(CAP)  |
| 7               | -V(CAP)  |
| 10              | -Vo      |
| 12              | +Vo      |


Note: 1. It is required to add C1 between pins 5 & 7 (see application circuits).



Front View



Top View  
PCB Layout



Bottom View

## MECHANICAL DRAWING (CONTINUED)

### VERTICAL ORIENTATION (ALL OTHER MODELS)


units: mm[inch]

tolerance:  $\pm 0.5[\pm 0.020]$ pin tolerance:  $\pm 0.1[\pm 0.004]$ 



| PIN CONNECTIONS |          |
|-----------------|----------|
| PIN             | FUNCTION |
| 1               | -Vin (N) |
| 3               | +Vin (L) |
| 5               | +V(CAP)  |
| 7               | -V(CAP)  |
| 10              | -Vo      |
| 12              | +Vo      |

Note: 1. It is required to add C1 between pins 5 & 7 (see application circuits).

Note: Grid 2.54\*2.54mm



Top View  
PCB Layout



## MECHANICAL DRAWING (CONTINUED)


### PBK-3-3 RIGHT-ANGLE ORIENTATION

units: mm[inch]


tolerance:  $\pm 0.5[\pm 0.020]$ pin tolerance:  $\pm 0.1[\pm 0.004]$ 

| PIN CONNECTIONS |          |
|-----------------|----------|
| PIN             | FUNCTION |
| 1               | -Vin (N) |
| 3               | +Vin (L) |
| 5               | +V(CAP)  |
| 7               | -V(CAP)  |
| 10              | -Vo      |
| 12              | +Vo      |

Note: 1. It is required to add C1 between pins 5 & 7 (see application circuits).




Front View




Side View

Note: Grid 2.54\*2.54mm



Top View  
PCB Layout



Bottom View

## MECHANICAL DRAWING (CONTINUED)


### RIGHT-ANGLE ORIENTATION (ALL OTHER MODELS)

units: mm[inch]


tolerance:  $\pm 0.5[\pm 0.020]$ pin tolerance:  $\pm 0.1[\pm 0.004]$ 

| PIN CONNECTIONS |          |
|-----------------|----------|
| PIN             | FUNCTION |
| 1               | -Vin (N) |
| 3               | +Vin (L) |
| 5               | +V(CAP)  |
| 7               | -V(CAP)  |
| 10              | -Vo      |
| 12              | +Vo      |

Note: 1. It is required to add C1 between pins 5 & 7 (see application circuits).


Note: Grid 2.54<sup>+</sup>2.54mm

Top View  
PCB Layout



Front View

Side View



Bottom View

## TEST CONFIGURATION

Figure 1




Table 1

| Recommended External Circuit Components |                 |                 |                 |                 |                 |                       |
|-----------------------------------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------------|
| $V_{OUT}$<br>(Vdc)                      | C1 <sup>1</sup> | C2 <sup>1</sup> | L1 <sup>1</sup> | C3 <sup>1</sup> | C4              | CY0<br>(Y1 capacitor) |
| 3.3                                     | 22 $\mu$ F/400V | 330 $\mu$ F/25V | 2.2 $\mu$ H     | 120 $\mu$ F/25V | 0.1 $\mu$ F/50V | 1nF/400Vac            |
| 5                                       | 22 $\mu$ F/400V | 330 $\mu$ F/25V | 2.2 $\mu$ H     | 68 $\mu$ F/35V  | 0.1 $\mu$ F/50V | 1nF/400Vac            |
| 9                                       | 22 $\mu$ F/400V | 330 $\mu$ F/25V | 2.2 $\mu$ H     | 68 $\mu$ F/35V  | 0.1 $\mu$ F/50V | 1nF/400Vac            |
| 12                                      | 22 $\mu$ F/400V | 150 $\mu$ F/35V | 2.2 $\mu$ H     | 68 $\mu$ F/35V  | 0.1 $\mu$ F/50V | 1nF/400Vac            |
| 15                                      | 22 $\mu$ F/400V | 150 $\mu$ F/35V | 2.2 $\mu$ H     | 68 $\mu$ F/35V  | 0.1 $\mu$ F/50V | 1nF/400Vac            |
| 24                                      | 22 $\mu$ F/400V | 100 $\mu$ F/35V | 2.2 $\mu$ H     | 68 $\mu$ F/35V  | 0.1 $\mu$ F/50V | 1nF/400Vac            |

Note: 1. Required components.  
2. 1 A/250 V fuse required.

## TYPICAL APPLICATION CIRCUIT

Figure 2




Table 2

| Recommended External Circuit Components |                 |     |                 |                 |                 |                 |            |                   |          |      |         |
|-----------------------------------------|-----------------|-----|-----------------|-----------------|-----------------|-----------------|------------|-------------------|----------|------|---------|
| $V_{OUT}$ (Vdc)                         | C1 <sup>1</sup> | L2  | C2 <sup>1</sup> | L1 <sup>1</sup> | C3 <sup>1</sup> | C4              | CY0        | FUSE <sup>1</sup> | TVS      | NTC  | MOV1    |
| 3.3                                     | 22 $\mu$ F/400V | 5mH | 330 $\mu$ F/25V | 2.2 $\mu$ H     | 120 $\mu$ F/25V | 0.1 $\mu$ F/50V | 1nF/400Vac | 1A/250V           | SMBJ7.0A | 5D-9 | S14K350 |
| 5                                       | 22 $\mu$ F/400V | 5mH | 330 $\mu$ F/25V | 2.2 $\mu$ H     | 68 $\mu$ F/35V  | 0.1 $\mu$ F/50V | 1nF/400Vac | 1A/250V           | SMBJ7.0A | 5D-9 | S14K350 |
| 9                                       | 22 $\mu$ F/400V | 5mH | 330 $\mu$ F/25V | 2.2 $\mu$ H     | 68 $\mu$ F/35V  | 0.1 $\mu$ F/50V | 1nF/400Vac | 1A/250V           | SMBJ12A  | 5D-9 | S14K350 |
| 12                                      | 22 $\mu$ F/400V | 5mH | 150 $\mu$ F/35V | 2.2 $\mu$ H     | 68 $\mu$ F/35V  | 0.1 $\mu$ F/50V | 1nF/400Vac | 1A/250V           | SMBJ20A  | 5D-9 | S14K350 |
| 15                                      | 22 $\mu$ F/400V | 5mH | 150 $\mu$ F/35V | 2.2 $\mu$ H     | 68 $\mu$ F/35V  | 0.1 $\mu$ F/50V | 1nF/400Vac | 1A/250V           | SMBJ20A  | 5D-9 | S14K350 |
| 24                                      | 22 $\mu$ F/400V | 5mH | 100 $\mu$ F/35V | 2.2 $\mu$ H     | 68 $\mu$ F/35V  | 0.1 $\mu$ F/50V | 1nF/400Vac | 1A/250V           | SMBJ30A  | 5D-9 | S14K350 |

Note: 1. Required components.

## EMC RECOMMENDED CIRCUIT

Figure 3




Table 3

| Recommended External Circuit Components |                    |
|-----------------------------------------|--------------------|
| MOV2                                    | S10K300            |
| CY1, CY2                                | 1nF/400Vac         |
| CX                                      | 0.1 $\mu$ F/275Vac |
| LCM                                     | 3.5mH              |
| LDM                                     | 5mH                |
| FUSE                                    | 1A/250V, slow blow |

Note: Also refer to Table 2.

- Notes:
1. C1 and C3 are electrolytic capacitors. They are required for both AC input and DC input.
  2. For AC input, C1 is used as a filter capacitor. The recommended C1 value is 22  $\mu$ F/400 V.
  3. For DC input, C1 is used as an EMC filter capacitor. The recommended C1 value is 10 $\mu$ F/400V. When the input voltage is above 370VDC, we recommend a 10 $\mu$ F/450V capacitor.
  4. C2 and C3 are output filter capacitors, we recommend high frequency and low impedance electrolytic capacitors. For capacitance and rated ripple current of capacitors refer to the datasheets provided by the manufacturers, voltage derating of capacitors should be 80% or above.
  5. C4 is a ceramic capacitor which is used to filter high frequency noise. C2, C3 and L1 form a pi-type filter circuit. For current of L1 and L2 refer to the datasheets provided by the manufacturers, current derating should be 80% or above. TVS is a recommended component to protect post-circuits (if converter fails). We recommend using a 5D-9 external input NTC.
  6. For standard EMC requirements, please refer to figure 2. If a higher EMC is required, please refer to figure 3.
  7. All specifications measured at Ta=25C, humidity <75%, 115 Vac & 230 Vac input voltage, and rated output load, unless otherwise specified.

## REVISION HISTORY

| rev. | description                                                                           | date       |
|------|---------------------------------------------------------------------------------------|------------|
| 1.0  | initial release                                                                       | 08/09/2013 |
| 1.01 | added 3.3 Vdc output model, added bent pin model options, updated emc recommendations | 03/25/2014 |

The revision history provided is for informational purposes only and is believed to be accurate.

**CUI INC<sup>®</sup>**

**Headquarters**  
20050 SW 112th Ave.  
Tualatin, OR 97062  
**800.275.4899**

Fax 503.612.2383  
**cui.com**  
techsupport@cui.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331